

LA50QS404 Information

Categ

Part NumberLA50QS404ManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 40A 500VAC/VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LA50QS404 Specifications

Manufacturer Part Number Manufacturer Littelfuse Inc. Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? LA50QS Fuse Type Cartridge Current Rating 40A Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension Littelfuse Inc. Circuit Protection Electrical, Blade Terminal (Bolt) LA50QS Cylindrical, Blade Terminal (Bolt) Report errors?		
Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? LA50QS Fuse Type Cartridge Current Rating 40A Voltage Rating - AC 500V Voltage Rating - DC Sonov Response Time Fast Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Electrical, Industrial CSA, UR Operating Temperature Bolt Mount Size / Dimension Circuit Protection Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension	Manufacturer Part Number	LA50QS404
Beckage Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? LA50QS Fuse Type Cartridge Current Rating 40A Voltage Rating - AC 500V Voltage Rating - DC 500V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Cylindrical, Blade Terminal (Bolt) Size / Dimension Industrial (Solt)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA50QSFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC500VVoltage Rating - DC500VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 2.130" L (25.40mm x 54.10mm)	Category	Circuit Protection
Series POWR-GARD? LA50QS Fuse Type Cartridge Current Rating 40A Voltage Rating - AC 500V Voltage Rating - DC 500V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 2.130" L (25.40mm x 54.10mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 40A Voltage Rating - AC 500V Voltage Rating - DC 500V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Cartridge 40A Contined Souv Contined Souv Souv Souv Souv Souv Souv Souv Souv	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 500V Voltage Rating - DC 500V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 40A 40A 40A 40A 40A 40A 40A 40	Series	POWR-GARD? LA50QS
Voltage Rating - AC Voltage Rating - DC Soov Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Soov Soov Soov Fast Coov Fast Approvals CSA, UR Cylindrical, Blade Terminal (Bolt) 1.000" Dia x 2.130" L (25.40mm x 54.10mm)	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 500V Fast Fast Fast Cov Case Foat Cov	Current Rating	40A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Electrical, Industrial CSA, UR CSA, UR CSA, UR COBA AC, 100kA DC Bolt Mount Bolt Mount Cylindrical, Blade Terminal (Bolt) 1.000" Dia x 2.130" L (25.40mm x 54.10mm)	Voltage Rating - AC	500V
Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 2.130" L (25.40mm x 54.10mm)	Voltage Rating - DC	500V
Features - Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 2.130" L (25.40mm x 54.10mm)	Response Time	Fast
Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 2.130" L (25.40mm x 54.10mm)	Applications	Electrical, Industrial
Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 2.130" L (25.40mm x 54.10mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 2.130" L (25.40mm x 54.10mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 2.130" L (25.40mm x 54.10mm)	Approvals	CSA, UR
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 2.130" L (25.40mm x 54.10mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 2.130" L (25.40mm x 54.10mm)	Breaking Capacity @ Rated Voltage	200kA AC, 100kA DC
Size / Dimension 1.000" Dia x 2.130" L (25.40mm x 54.10mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.000" Dia x 2.130" L (25.40mm x 54.10mm)
		Report errors?

LA50QS404 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LA50QS404 Payment Methods



















LA50QS404 Shipping Methods













If you have any question about LA50QS404, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com