

LA50QS6004 Information

Heisener.com

For Reference Only

Part Number LA50QS6004
Manufacturer Littelfuse Inc.
Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 600A 500VAC/VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LA50QS6004 Specifications

Manufacturer Part NumberLA50Q86004ManufacturerLittelfuse Inc.CategoryCircuit ProtectionBecktical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA50QSFuse TypeCartridgeCurrent Rating600AVoltage Rating - AC500VVoltage Rating - DC500VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.000" Dia x 2.220" L (50.80mm x 56.40mm)		
Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? LA50QS Fuse Type Cartridge Current Rating 600A Voltage Rating - AC 500V Voltage Rating - DC 500V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals Cesa, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Cartridge Ca	Manufacturer Part Number	LA50QS6004
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? LA50QS Fuse Type Cartridge Current Rating 600A Voltage Rating - AC Voltage Rating - DC So0V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CysA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Industrial Features - CSA, UR CysA, UR Cys	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA50QSFuse TypeCartridgeCurrent Rating600AVoltage Rating - AC500VVoltage Rating - DC500VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.000" Dia x 2.220" L (50.80mm x 56.40mm)	Category	Circuit Protection
SeriesPOWR-GARD? LA50QSFuse TypeCartridgeCurrent Rating600AVoltage Rating - AC500VVoltage Rating - DC500VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.000" Dia x 2.220" L (50.80mm x 56.40mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 600A Voltage Rating - AC 500V Voltage Rating - DC 500V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Canactive Cartridge 600A 6	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 500V Voltage Rating - DC 500V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 600A 60A 600A	Series	POWR-GARD? LA50QS
Voltage Rating - AC Voltage Rating - DC Soov Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension Soov 500V 500	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 500V Fast Fast Fast CRA CUIN Fast CON	Current Rating	600A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Fast Fast Fast Fast Fast Foature - CSA, UR CSA, UR - Bolt Mount CSA, UR - Cylindrical, Blade Terminal (Bolt) Size / Dimension	Voltage Rating - AC	500V
Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.000" Dia x 2.220" L (50.80mm x 56.40mm)	Voltage Rating - DC	500V
Features - Class - CSA, UR Approvals CSA, UR Operating Temperature - Estadous Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.000" Dia x 2.220" L (50.80mm x 56.40mm)	Response Time	Fast
Class - CSA, UR Operating Temperature - Sereking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.000" Dia x 2.220" L (50.80mm x 56.40mm)	Applications	Electrical, Industrial
Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension CSA, UR CVSA, UR CV	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.000" Dia x 2.220" L (50.80mm x 56.40mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.000" Dia x 2.220" L (50.80mm x 56.40mm)	Approvals	CSA, UR
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.000" Dia x 2.220" L (50.80mm x 56.40mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.000" Dia x 2.220" L (50.80mm x 56.40mm)	Breaking Capacity @ Rated Voltage	200kA AC, 100kA DC
Size / Dimension 2.000" Dia x 2.220" L (50.80mm x 56.40mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	2.000" Dia x 2.220" L (50.80mm x 56.40mm)
		Report errors?

LA50QS6004 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LA50QS6004 Payment Methods



















LA50QS6004 Shipping Methods













If you have any question about LA50QS6004, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com