

LA50QS804 Information

Heisener.com

For Reference Only

Part Number LA50QS804
Manufacturer Littelfuse Inc.
Category Circuit Protec

Circuit Protection Electrical, Specialty Fuses

Description FUSE CARTRIDGE 80A 500VAC/VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LA50QS804 Specifications

Manufacturer Part NumberLA50Q8804ManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA50QSFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC500VVoltage Rating - DC500VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 2.130" L (25.40mm x 54.10mm)Report errors?		
Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? LA50QS Fuse Type Cartridge Current Rating 80A Voltage Rating - AC 500V Voltage Rating - DC 500V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Sov Cartridge Cartridge Sov Cartridge Cartridge Sov Cartridge C	Manufacturer Part Number	LA50QS804
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? LA50QS Fuse Type Cartridge Current Rating 80A Voltage Rating - AC 500V Voltage Rating - DC 500V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 2.130" L (25.40mm x 54.10mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA50QSFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC500VVoltage Rating - DC500VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 2.130" L (25.40mm x 54.10mm)	Category	Circuit Protection
SeriesPOWR-GARD? LA50QSFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC500VVoltage Rating - DC500VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 2.130" L (25.40mm x 54.10mm)		Electrical, Specialty Fuses
Fuse Type Current Rating RoA Voltage Rating - AC Voltage Rating - DC So0V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Cartridge So0A Roa Cartridge Roa	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 500V Voltage Rating - DC 500V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 80A 80A 80A 80A 80A 80A 80A 80	Series	POWR-GARD? LA50QS
Voltage Rating - AC Voltage Rating - DC 500V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 500V 500	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 500V Fast Fast Fast Fast Class - COMMAN CSA, UR CSA, UR COMMAN CSA, UR CSA, UR COMMAN CSA, UR COMMAN COM	Current Rating	80A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Electrical, Industrial Fast CSA, UR - CSA, U	Voltage Rating - AC	500V
Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 2.130" L (25.40mm x 54.10mm)	Voltage Rating - DC	500V
Features - Class - CSA, UR Approvals CSA, UR Operating Temperature - Experimental (Bolt) Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 2.130" L (25.40mm x 54.10mm)	Response Time	Fast
Class - CSA, UR Operating Temperature - Sereking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 2.130" L (25.40mm x 54.10mm)	Applications	Electrical, Industrial
Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension CSA, UR CVIA - 1.000" Dia x 2.130" L (25.40mm x 54.10mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 2.130" L (25.40mm x 54.10mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 2.130" L (25.40mm x 54.10mm)	Approvals	CSA, UR
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 2.130" L (25.40mm x 54.10mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 2.130" L (25.40mm x 54.10mm)	Breaking Capacity @ Rated Voltage	200kA AC, 100kA DC
Size / Dimension 1.000" Dia x 2.130" L (25.40mm x 54.10mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.000" Dia x 2.130" L (25.40mm x 54.10mm)
		Report errors?

LA50QS804 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LA50QS804 Payment Methods



















LA50QS804 Shipping Methods













If you have any question about LA50QS804, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com