

LA50QS904 Information

(A) Heisener.com

Part Number LA50QS904

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 90A 500VAC/VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LA50QS904 Specifications

Manufacturer Part NumberLA50Q8904ManufacturerLittelfuse Inc.CategoryCircuit ProtectionFlectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA50QSFuse TypeCartridgeCurrent Rating90AVoltage Rating - AC500VVoltage Rating - DC500VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 2.130" L (25.40mm x 54.10mm)		
Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? LA50QS Fuse Type Cartridge Current Rating 90A Voltage Rating - AC 500V Voltage Rating - DC Sonov Response Time Fast Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Electrical, Industrial CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage COSA, UR Cylindrical, Blade Terminal (Bolt) 1.000" Dia x 2.130" L (25.40mm x 54.10mm)	Manufacturer Part Number	LA50QS904
Beckrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? LA50QS Fuse Type Current Rating 90A Voltage Rating - AC 500V Voltage Rating - DC 500V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals Cya, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Industrial Features CSA, UR CSA, UR CSA, UR Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Blade Terminal (Bolt) Size / Dimension	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA50QSFuse TypeCartridgeCurrent Rating90AVoltage Rating - AC500VVoltage Rating - DC500VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 2.130" L (25.40mm x 54.10mm)	Category	Circuit Protection
SeriesPOWR-GARD? LA50QSFuse TypeCartridgeCurrent Rating90AVoltage Rating - AC500VVoltage Rating - DC500VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 2.130" L (25.40mm x 54.10mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 90A Voltage Rating - AC 500V Voltage Rating - DC 500V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Cartridge S00A Cartridge S00A South S10A Since	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating 90A Voltage Rating - AC 500V Voltage Rating - DC 500V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 2.130" L (25.40mm x 54.10mm)	Series	POWR-GARD? LA50QS
Voltage Rating - AC Voltage Rating - DC 500V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 500V 500V 500V 500V 500V 500V 500V 600V 600	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 500V Fast CSA CSA CSA, UR CONA CONA	Current Rating	90A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Electrical, Industrial Capacity CSA, UR - CYBINGTON CONTROL	Voltage Rating - AC	500V
Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 2.130" L (25.40mm x 54.10mm)	Voltage Rating - DC	500V
Features - Class - CSA, UR Approvals CSA, UR Operating Temperature - CSA, UR Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 2.130" L (25.40mm x 54.10mm)	Response Time	Fast
Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 2.130" L (25.40mm x 54.10mm)	Applications	Electrical, Industrial
Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension CSA, UR CVSA, UR	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 2.130" L (25.40mm x 54.10mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 2.130" L (25.40mm x 54.10mm)	Approvals	CSA, UR
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 2.130" L (25.40mm x 54.10mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 2.130" L (25.40mm x 54.10mm)	Breaking Capacity @ Rated Voltage	200kA AC, 100kA DC
Size / Dimension 1.000" Dia x 2.130" L (25.40mm x 54.10mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Donort amount	Size / Dimension	1.000" Dia x 2.130" L (25.40mm x 54.10mm)
Report errors?		Report errors?

LA50QS904 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LA50QS904 Payment Methods



















LA50QS904 Shipping Methods













If you have any question about LA50QS904, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com