

LA70Q1254 Information

Heisener.com

Part Number LA70Q1254

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 125A 700VAC/650VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LA70Q1254 Specifications

| Manufacturer Part NumberLA70Q1254ManufacturerLittelfuse Inc.CategoryCircuit ProtectionBectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesLA70QFuse TypeCartridgeCurrent Rating125AVoltage Rating - AC700VVoltage Rating - DC650VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.500" Dia x 2.843" L (38.10mm x 72.20mm) | | |
|--|-----------------------------------|---|
| Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series LA70Q Fuse Type Cartridge Current Rating 125A Voltage Rating - AC Voltage Rating - DC 650V Response Time - Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Electrical, Industrial Features - Class - Class - Class - Class - Class - Cylindrical, Blade Terminal (Bolt) | Manufacturer Part Number | LA70Q1254 |
| Beckrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Series LA70Q Fuse Type Cartridge Current Rating 125A Voltage Rating - AC Voltage Rating - DC 650V Response Time - Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Blade Terminal (Bolt) Size / Dimension Electrical, Blade Terminal (Bolt) Size / Dimension | Manufacturer | Littelfuse Inc. |
| Package Cylindrical, Blade Terminal (Bolt) Series LA70Q Fuse Type Cartridge Current Rating 125A Voltage Rating - AC 700V Voltage Rating - DC 650V Response Time - Rating Electrical, Industrial Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 2.843" L (38.10mm x 72.20mm) | Category | Circuit Protection |
| Series LA70Q Fuse Type Cartridge Current Rating 125A Voltage Rating - AC 700V Voltage Rating - DC 650V Response Time - Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 2.843" L (38.10mm x 72.20mm) | | Electrical, Specialty Fuses |
| Fuse Type Current Rating 125A Voltage Rating - AC 700V Voltage Rating - DC 650V Response Time - Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Cartridge Cartridge 125A 100V 100V 100V 100V 100V 100V 100V 100 | Package | Cylindrical, Blade Terminal (Bolt) |
| Current Rating Voltage Rating - AC 700V Voltage Rating - DC 650V Response Time - Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 125A 700V 100V 100 | Series | LA70Q |
| Voltage Rating - AC Voltage Rating - DC 650V Response Time Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 700V 650V 65 | Fuse Type | Cartridge |
| Voltage Rating - DC Response Time Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 650V | Current Rating | 125A |
| Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension - Class - Class CuR | Voltage Rating - AC | 700V |
| Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 2.843" L (38.10mm x 72.20mm) | Voltage Rating - DC | 650V |
| Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 2.843" L (38.10mm x 72.20mm) | Response Time | - |
| Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 2.843" L (38.10mm x 72.20mm) | Applications | Electrical, Industrial |
| Approvals Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension UR - CHACLES OF TEMPERATURE - Bolt Mount Bolt Mount 1.500" Dia x 2.843" L (38.10mm x 72.20mm) | Features | - |
| Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 2.843" L (38.10mm x 72.20mm) | Class | - |
| Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 2.843" L (38.10mm x 72.20mm) | Approvals | UR |
| Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 2.843" L (38.10mm x 72.20mm) | Operating Temperature | - |
| Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 2.843" L (38.10mm x 72.20mm) | Breaking Capacity @ Rated Voltage | 100kA |
| Size / Dimension 1.500" Dia x 2.843" L (38.10mm x 72.20mm) | Mounting Type | Bolt Mount |
| , and the second | Package / Case | Cylindrical, Blade Terminal (Bolt) |
| Report errors? | Size / Dimension | 1.500" Dia x 2.843" L (38.10mm x 72.20mm) |
| | | Report errors? |

LA70Q1254 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LA70Q1254 Payment Methods



















LA70Q1254 Shipping Methods













If you have any question about LA70Q1254, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com