

LA70QS2004 Information

Manufa Categor Heisener.com

Part Number LA70QS2004

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 200A 700VAC/VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LA70QS2004 Specifications

Manufacturer Part NumberLA70Q\$2004ManufacturerLittelfuse Inc.CategoryCircuit ProtectionPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA70Q\$Fuse TypeCartridgeCurrent Rating200AVoltage Rating - AC700VVoltage Rating - DC700VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 2.874" L (31.00mm x 73.00mm)		
Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? LA70QS Fuse Type Cartridge Current Rating 200A Voltage Rating - AC 700V Voltage Rating - DC 700V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Capacity Power Specialty Specia	Manufacturer Part Number	LA70QS2004
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? LA70QS Fuse Type Cartridge Current Rating 200A Voltage Rating - AC 700V Voltage Rating - DC 700V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.874" L (31.00mm x 73.00mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA70QSFuse TypeCartridgeCurrent Rating200AVoltage Rating - AC700VVoltage Rating - DC700VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 2.874" L (31.00mm x 73.00mm)	Category	Circuit Protection
SeriesPOWR-GARD? LA70QSFuse TypeCartridgeCurrent Rating200AVoltage Rating - AC700VVoltage Rating - DC700VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 2.874" L (31.00mm x 73.00mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating200AVoltage Rating - AC700VVoltage Rating - DC700VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 2.874" L (31.00mm x 73.00mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 700V Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 200A 700V 700V 700V Response Time Fast Fast CSA, UR - CSA, UR 200kA AC, 100kA DC Bolt Mount Cylindrical, Blade Terminal (Bolt) 1.220" Dia x 2.874" L (31.00mm x 73.00mm)	Series	POWR-GARD? LA70QS
Voltage Rating - AC Voltage Rating - DC 700V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 700V 700	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast	Current Rating	200A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Electrical, Industrial Fast CSA, UR - CSA, U	Voltage Rating - AC	700V
Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.874" L (31.00mm x 73.00mm)	Voltage Rating - DC	700V
Features - Class - CSA, UR Approvals CSA, UR Operating Temperature - Especial Properation of the Composition of the Compositi	Response Time	Fast
Class - CSA, UR Operating Temperature - Sereking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.874" L (31.00mm x 73.00mm)	Applications	Electrical, Industrial
Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension CSA, UR CVIA COMMON	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.874" L (31.00mm x 73.00mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.874" L (31.00mm x 73.00mm)	Approvals	CSA, UR
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.874" L (31.00mm x 73.00mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.874" L (31.00mm x 73.00mm)	Breaking Capacity @ Rated Voltage	200kA AC, 100kA DC
Size / Dimension 1.220" Dia x 2.874" L (31.00mm x 73.00mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.220" Dia x 2.874" L (31.00mm x 73.00mm)
		Report errors?

LA70QS2004 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LA70QS2004 Payment Methods



















LA70QS2004 Shipping Methods













If you have any question about LA70QS2004, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com