

## **LA70QS3504 Information**

Heisener.com

Part Number LA70QS3504

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 350A 700VAC/VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **LA70QS3504 Specifications**

Manufacturer Part NumberLA70Q\$3504ManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA70Q\$Fuse TypeCartridgeCurrent Rating350AVoltage Rating - AC700VVoltage Rating - DC700VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.500" Dia x 2.843" L (38.10mm x 72.20mm)Report errors?		
Category  Circuit Protection  Electrical, Specialty Fuses  Package  Cylindrical, Blade Terminal (Bolt)  Series  POWR-GARD? LA70QS  Fuse Type  Cartridge  Current Rating  350A  Voltage Rating - AC  700V  Voltage Rating - DC  Response Time  Fast  Applications  Electrical, Industrial  Features  - Class  - Approvals  CSA, UR  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  Cylindrical, Blade Terminal (Bolt)  Size / Dimension	Manufacturer Part Number	LA70QS3504
Electrical, Specialty Fuses  Package Cylindrical, Blade Terminal (Bolt)  Series POWR-GARD? LA70QS  Fuse Type Cartridge  Current Rating 350A  Voltage Rating - AC 700V  Voltage Rating - DC 700V  Response Time Fast  Applications Electrical, Industrial  Features - Class - Approvals CSA, UR  Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 1.500" Dia x 2.843" L (38.10mm x 72.20mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA70QSFuse TypeCartridgeCurrent Rating350AVoltage Rating - AC700VVoltage Rating - DC700VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.500" Dia x 2.843" L (38.10mm x 72.20mm)	Category	Circuit Protection
SeriesPOWR-GARD? LA70QSFuse TypeCartridgeCurrent Rating350AVoltage Rating - AC700VVoltage Rating - DC700VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.500" Dia x 2.843" L (38.10mm x 72.20mm)		Electrical, Specialty Fuses
Fuse Type Current Rating Current Rating 350A Voltage Rating - AC 700V Voltage Rating - DC 700V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  Cartridge 350A Cartridge 360A 360A 360A 360A 360A 360A 360A 360A	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 700V Voltage Rating - DC 700V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals Cyange Temperature Cyange Temperature Cyange Temperature Coperating Temperature Coperating Temperature Coperating Temperature Cyange Temperature Cyan	Series	POWR-GARD? LA70QS
Voltage Rating - AC  Voltage Rating - DC  Response Time  Fast  Applications  Electrical, Industrial  Features  - Class  - Approvals  CSA, UR  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  1.500" Dia x 2.843" L (38.10mm x 72.20mm)	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Fast Fast Fast Foot Foot Foot Fast Foot Foot Foot Foot Fast Foot Foot Foot Foot Foot Foot Foot Fo	Current Rating	350A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Electrical, Industrial Fast CSA, UR - CSA, U	Voltage Rating - AC	700V
Applications Electrical, Industrial  Features - Class - Approvals CSA, UR  Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 2.843" L (38.10mm x 72.20mm)	Voltage Rating - DC	700V
Features - Class - CSA, UR  Approvals CSA, UR  Operating Temperature - Streaking Capacity @ Rated Voltage 200kA AC, 100kA DC  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 1.500" Dia x 2.843" L (38.10mm x 72.20mm)	Response Time	Fast
Class - CSA, UR  Operating Temperature - Streaking Capacity @ Rated Voltage 200kA AC, 100kA DC  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 1.500" Dia x 2.843" L (38.10mm x 72.20mm)	Applications	Electrical, Industrial
Approvals  CSA, UR  Operating Temperature  - Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  CSA, UR  CVIA  CSA, UR  CVIA  CSA, UR  CVIA  CONTROL  CONTROL  CONTROL  CSA, UR  CONTROL  CONTROL  CONTROL  CONTROL  CSA, UR  CONTROL  CONTRO	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  200kA AC, 100kA DC  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  1.500" Dia x 2.843" L (38.10mm x 72.20mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 1.500" Dia x 2.843" L (38.10mm x 72.20mm)	Approvals	CSA, UR
Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  1.500" Dia x 2.843" L (38.10mm x 72.20mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 2.843" L (38.10mm x 72.20mm)	Breaking Capacity @ Rated Voltage	200kA AC, 100kA DC
Size / Dimension 1.500" Dia x 2.843" L (38.10mm x 72.20mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.500" Dia x 2.843" L (38.10mm x 72.20mm)
		Report errors?

### **LA70QS3504 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **LA70QS3504 Payment Methods**



















### LA70QS3504 Shipping Methods













If you have any question about LA70QS3504, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com