



LA70QS5014F Information

Heisener.com

For Reference Only

Part Number LA70QS5014F

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 50A 690VAC/700VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LA70QS5014F Specifications

Manufacturer Part NumberLA70QS5014FManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA70QSFFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC690VVoltage Rating - DC700VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.000" Dia x 2.843" L (50.80mm x 72.20mm)		
Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? LA70QSF Fuse Type Cartridge Current Rating 50A Voltage Rating - AC 690V Voltage Rating - DC 700V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension	Manufacturer Part Number	LA70QS5014F
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? LA70QSF Fuse Type Cartridge Current Rating 50A Voltage Rating - AC 690V Voltage Rating - DC 700V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.000" Dia x 2.843" L (50.80mm x 72.20mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA70QSFFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC690VVoltage Rating - DC700VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.000" Dia x 2.843" L (50.80mm x 72.20mm)	Category	Circuit Protection
SeriesPOWR-GARD? LA70QSFFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC690VVoltage Rating - DC700VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.000" Dia x 2.843" L (50.80mm x 72.20mm)		Electrical, Specialty Fuses
Fuse Type Current Rating Current Rating 50A Voltage Rating - AC 690V Voltage Rating - DC 700V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Cartridge 690V 700V Response Fast Fast Fast Fast Fast CSCA, UR CSA, UR CSA, UR CSA, UR CSA, UR CSA, UR CONGRIG Temperature Bolt Mount CSA, 100kA DC Solt Mount Cylindrical, Blade Terminal (Bolt) Size / Dimension	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 690V Voltage Rating - DC 700V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 50A 690V 690V	Series	POWR-GARD? LA70QSF
Voltage Rating - AC Voltage Rating - DC 700V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 690V 700V 700	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast	Current Rating	50A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Fast Fast Fast Fast Fast Fast Flow Fast Foature - CSA, UR - CS	Voltage Rating - AC	690V
Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.000" Dia x 2.843" L (50.80mm x 72.20mm)	Voltage Rating - DC	700V
Features - Class - CSA, UR Approvals CSA, UR Operating Temperature - Experimental (Bolt) Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.000" Dia x 2.843" L (50.80mm x 72.20mm)	Response Time	Fast
Class - CSA, UR Operating Temperature - Sereking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.000" Dia x 2.843" L (50.80mm x 72.20mm)	Applications	Electrical, Industrial
Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension CSA, UR CVIA CSA, UR CVIA CONTROL CONTROL CONTROL CONTROL CSA, UR CONTROL CONTROL CONTROL CONTROL CONTROL CSA, UR CONTROL CON	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.000" Dia x 2.843" L (50.80mm x 72.20mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.000" Dia x 2.843" L (50.80mm x 72.20mm)	Approvals	CSA, UR
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.000" Dia x 2.843" L (50.80mm x 72.20mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.000" Dia x 2.843" L (50.80mm x 72.20mm)	Breaking Capacity @ Rated Voltage	200kA AC, 100kA DC
Size / Dimension 2.000" Dia x 2.843" L (50.80mm x 72.20mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	2.000" Dia x 2.843" L (50.80mm x 72.20mm)
		Report errors?

LA70QS5014F Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LA70QS5014F Payment Methods



















LA70QS5014F Shipping Methods













If you have any question about LA70QS5014F, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com