



LA70QS8022FI Information

Heisener.com

Part Number LA70QS8022FI
Manufacturer Littelfuse Inc.
Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 80A 690VAC/700VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LA70QS8022FI Specifications

Manufacturer Part NumberLA70Q88022FIManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA70QSFFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC690VVoltage Rating - DC700VResponse TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.866" Dia x 2.283" L (22.00mm x 58.00mm)		
Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? LA70QSF Fuse Type Cartridge Current Rating 80A Voltage Rating - AC 690V Voltage Rating - DC 700V Response Time Fast Applications Electrical, Industrial Features Indicating Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Captridge Captridge Captridge Captridge Cylindrical, Blade Terminal (Bolt) Size / Dimension	Manufacturer Part Number	LA70QS8022FI
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? LA70QSF Fuse Type Cartridge Current Rating 80A Voltage Rating - AC 690V Voltage Rating - DC 700V Response Time Fast Applications Electrical, Industrial Features Indicating Class - Approvals CysA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Industrial Features CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage CoykA AC, 100kA DC Size / Dimension Electrical, Industrial Features	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA70QSFFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC690VVoltage Rating - DC700VResponse TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.866" Dia x 2.283" L (22.00mm x 58.00mm)	Category	Circuit Protection
SeriesPOWR-GARD? LA70QSFFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC690VVoltage Rating - DC700VResponse TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.866" Dia x 2.283" L (22.00mm x 58.00mm)		Electrical, Specialty Fuses
Fuse Type Current Rating RoA Voltage Rating - AC Voltage Rating - DC Response Time Res	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 690V Voltage Rating - DC 700V Response Time Fast Applications Electrical, Industrial Features Indicating Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 80A 80A 80A 80A 80A 80A 80A 80	Series	POWR-GARD? LA70QSF
Voltage Rating - AC Voltage Rating - DC 700V Response Time Fast Applications Electrical, Industrial Indicating Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 690V 700V 700V 700V 700V 700V 700V 700V Fast Fast Clectrical, Industrial Indicating Class - CSA, UR CSA, UR CSA, UR 700kA DC 801k Mount Cylindrical, Blade Terminal (Bolt) No.866" Dia x 2.283" L (22.00mm x 58.00mm)	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features Indicating Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 700V Fast Fast Fast Fast Fast Class CosA, UR CSA, UR COSA, UR	Current Rating	80A
Response Time Applications Electrical, Industrial Features Indicating Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Electrical, Industrial Electrical, Industrial Fast CSA, UR CYBINGTON CONTROL	Voltage Rating - AC	690V
Applications Electrical, Industrial Features Indicating Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.866" Dia x 2.283" L (22.00mm x 58.00mm)	Voltage Rating - DC	700V
Features Indicating Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.866" Dia x 2.283" L (22.00mm x 58.00mm)	Response Time	Fast
Class - CSA, UR Operating Temperature - CSA, UR Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.866" Dia x 2.283" L (22.00mm x 58.00mm)	Applications	Electrical, Industrial
Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension CSA, UR CVSA, UR CV	Features	Indicating
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.866" Dia x 2.283" L (22.00mm x 58.00mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.866" Dia x 2.283" L (22.00mm x 58.00mm)	Approvals	CSA, UR
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.866" Dia x 2.283" L (22.00mm x 58.00mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.866" Dia x 2.283" L (22.00mm x 58.00mm)	Breaking Capacity @ Rated Voltage	200kA AC, 100kA DC
Size / Dimension 0.866" Dia x 2.283" L (22.00mm x 58.00mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	0.866" Dia x 2.283" L (22.00mm x 58.00mm)
		Report errors?

LA70QS8022FI Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LA70QS8022FI Payment Methods



















LA70QS8022FI Shipping Methods













If you have any question about LA70QS8022FI, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com