

LB E63C-S2U1-35-34-Z

LB E63C-S2U1-35-34-Z Information



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



LB E63C-S2U1-35-34-Z Specifications

ManufacturerOSRAM Opto Semiconductors Inc.CategoryOptoelectronicsLED Indication - DiscretePackage4-PLCCSeriesAdvanced Power TOPLED?ColorBlueConfiguration-ConfigurationColorlessLens Stolp ScreteColorlessMillicandela Rating-Voltage - Forward (Vf) (Typ)GowSurface MountSurface MountViewing AngleSurface MountWavelength - PeakGowWavelength - Peak464nmFeatures-Package / Case4-PLCCSupplier Device Package4-PLCCSize / Dimension3.20mm L x 2.80mm W		
Category Optoelectronics LED Indication - Discrete Package 4-PLCC Stries Advanced Power TOPLED? Color Blue Configuration - Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating - Voltage - Forward (Vf) (Typ) 3.9V Current - Test 30mA Viewing Angle Surface Mount Wavelength - Dominant 469nm Wavelength - Peak 464nm Features - Package / Case 4.PLCC Supplier Device Package 4.PLCC Supplier Device Package 3.20mm L x 2.80mm W Height (Max) 3.50mm	Manufacturer Part Number	LB E63C-S2U1-35-34-Z
LED Indication - DiscretePackage4-PLCCSeriesAdvanced Power TOPLED?ColorBlueConfiguration-Lens ColorColorlessLens TansparencyClearMillicandela Rating-Lens Style/SizeRound with Domed Top, 2.60mmVoltage - Forward (Vf) (Typ)3.9VCurrent - Test30mAViewing Angle20°Mounting TypeSurface MountWavelength - Pominant469nmVavelength - Peak-Package / Case-Supplier Device Package4-PLCCSize / Dimension3.20mm L x 2.80mm WHeight (Max)3.50mm	Manufacturer	OSRAM Opto Semiconductors Inc.
Package4-PLCCSeriesAdvanced Power TOPLED?ColorBlueConfiguration-Lens ColorColorlessLens TransparencyClearMillicandela Rating-Voltage - Forward (Vf) (Typ)3.9VCurrent - Test30mAVoltagen - Dominant469nmaWavelength - Poeka464nmaVardength - Peaka-Package / Case-Supplier Device Package4-PLCCSipplier Device Package3.90m L x 2.80mm WSige / Dimension3.00m L x 2.80mm WSige / Dimension3.00m L x 2.80mm W	Category	Optoelectronics
Advanced Power TOPLED?ColorBlueConfiguration-Lens ColorColorlessLens TransparencyClearMillicandela Rating-Lens Style/SizeRound with Domed Top, 2.60mmVoltage - Forward (Vf) (Typ)3.9VCurrent - Test30mAViewing AngleSurface MountWavelength - Dominant469nmWavelength - Peak464nmFeatures-Package / Case4.PLCCSupplier Device Package3.20mm Lx 2.80mm WHeight (Max)3.50mm		LED Indication - Discrete
ColorBlueConfiguration-Lens ColorColorlessLens TransparencyClearMillicandela Rating-Lens Style/SizeRound with Domed Top, 2.60mmVoltage - Forward (Vf) (Typ)3.9VCurrent - Test30mAViewing Angle20°Mounting TypeSurface MountWavelength - Dominant469nmWavelength - Peak464nmFeatures-Package / Case4-PLCCSurplier Device Package3.20mm L x 2.80mm WHeight (Max)3.50mm	Package	4-PLCC
Configuration-Lens ColorColorlessLens TransparencyClearMillicandela Rating-Lens Style/SizeRound with Domed Top, 2.60mmVoltage - Forward (Vf) (Typ)3.9VCurrent - Test30mAViewing Angle20°Mounting TypeSurface MountWavelength - Dominant469nmVavelength - Peak-Features-Package / Case4.PLCCSupplier Device Package3.20mm L x 2.80mm WHeight (Max)3.50mm	Series	Advanced Power TOPLED?
Lens ColorColorlessLens TransparencyClearMillicandel Rating-Lens Style/SizeRound with Domed Top, 2.60mmVoltage - Forward (Vf) (Typ)3.9VCurrent - Test30mACurrent - Test30mAWounting TypeSurface MountWavelength - Dominant469nmWavelength - Peak-Features-Package / Case4.PLCCSupplier Device Package3.20mm L x 2.80mm WHeight (Max)3.50mm	Color	Blue
Lens TransparencyClearMillicandela Rating-Lens Style/SizeRound with Domed Top, 2.60mmVoltage - Forward (Vf) (Typ)3.9VCurrent - Test30mACurrent - Test30mAViewing Angle20°Mounting TypeSurface MountWavelength - Dominant469nmWavelength - Peak-Features-Package / Case4-PLCCSupplier Device Package3.20mm L x 2.80mm WHeight (Max)3.50mm	Configuration	-
Millicandela Rating-Lens Style/SizeRound with Domed Top, 2.60mmVoltage - Forward (Vf) (Typ)3.9VCurrent - Test30mAViewing Angle20°Mounting TypeSurface MountWavelength - Dominant469nmWavelength - Peak464nmFeatures-Package / Case4-PLCCSupplier Device Package4.PLCCSize / Dimension3.20mm L x 2.80mm WHeight (Max)3.50mm	Lens Color	Colorless
Lens Style/SizeRound with Domed Top, 2.60mmVoltage - Forward (Vf) (Typ)3.9VCurrent - Test30mAViewing Angle20°Mounting TypeSurface MountWavelength - Dominant469nmWavelength - Peak464nmFeatures-Package / Case4-PLCCSupplier Device Package3.20mm L x 2.80mm WHeight (Max)3.50mm	Lens Transparency	Clear
Voltage - Forward (Vf) (Typ)3.9VCurrent - Test30mAViewing Angle20°Mounting TypeSurface MountWavelength - Dominant469nmWavelength - Peak464nmFeatures-Package / Case4-PLCCSupplier Device Package3.20mm L x 2.80mm WSize / Dimension3.50mm	Millicandela Rating	-
Current - Test30mAViewing Angle20°Mounting TypeSurface MountWavelength - Dominant469nmWavelength - Peak464nmFeatures-Package / Case4-PLCCSupplier Device Package4-PLCCSize / Dimension3.20mm L x 2.80mm WHeight (Max)3.50mm	Lens Style/Size	Round with Domed Top, 2.60mm
Viewing Angle20°Mounting TypeSurface MountWavelength - Dominant469nmWavelength - Peak464nmFeatures-Package / Case4-PLCCSupplier Device Package4-PLCCSize / Dimension3.20mm L x 2.80mm WHeight (Max)3.50mm	Voltage - Forward (Vf) (Typ)	3.9V
Nounting TypeSurface MountWavelength - Dominant469nmWavelength - Peak464nmFeatures-Package / Case4-PLCCSupplier Device Package4-PLCCSize / Dimension3.20mm L x 2.80mm WHeight (Max)3.50mm	Current - Test	30mA
Wavelength - Dominant469nmWavelength - Peak464nmFeatures-Package / Case4-PLCCSupplier Device Package4-PLCCSize / Dimension3.20mm L x 2.80mm WHeight (Max)3.50mm	Viewing Angle	20°
Wavelength - Peak464nmFeatures-Package / Case4-PLCCSupplier Device Package4-PLCCSize / Dimension3.20mm L x 2.80mm WHeight (Max)3.50mm	Mounting Type	Surface Mount
Features-Package / Case4-PLCCSupplier Device Package4-PLCCSize / Dimension3.20mm L x 2.80mm WHeight (Max)3.50mm	Wavelength - Dominant	469nm
Package / Case4-PLCCSupplier Device Package4-PLCCSize / Dimension3.20mm L x 2.80mm WHeight (Max)3.50mm	Wavelength - Peak	464nm
Supplier Device Package4-PLCCSize / Dimension3.20mm L x 2.80mm WHeight (Max)3.50mm	Features	-
Size / Dimension3.20mm L x 2.80mm WHeight (Max)3.50mm	Package / Case	4-PLCC
Height (Max) 3.50mm	Supplier Device Package	4-PLCC
	Size / Dimension	3.20mm L x 2.80mm W
Report errors?	Height (Max)	3.50mm
		Report errors ⁴

LB E63C-S2U1-35-34-Z Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

LB E63C-S2U1-35-34-Z Payment Methods



LB E63C-S2U1-35-34-Z Shipping Methods



If you have any question about LB E63C-S2U1-35-34-Z, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com