

LCM1500R-T-1

Quote

LCM1500R-T-1 Information

		Part Number	LCM1500R-T-1	
		Manufacturer	Artesyn Embedded Technologies	
	() Heisener.com	Category	Power Supplies - External/Internal (Off-Board) AC DC Converters	- 1
	A COMPANY LOUGH	Description	AC/DC CONVERTER 28V 1500W	- 6-20E
		Package	-	- Hen 256
			For the pricing/inventory/lead time, please contact	
	For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a C

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



LCM1500R-T-1 Specifications

NumberLCM1500R-T-1ManufacturerArtesyn Embedded TechnologiesCategoryPower Supplies - External/Internal (Off-Board)AC DC ConvertersPackage-SeriesLCM1500TypeFront EndNumber of Outputs1Voltage - Input90 ~ 264 VACVoltage - Output 136VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 5-Voltage - Output 6-Voltage - Output 7-Voltage - Output 8-Voltage - Output 9-Voltage - Output 9-Voltage - Output 1-Series-Voltage - Output 4-Voltage - Output 5-Voltage - Output 6-Voltage - Output 7-Voltage - Output 7-Voltage - Output 8-Voltage - Output 9-Voltage - Output 9-Voltage - Output 9-Voltage - Output 1043APower (Watts)ISO0WVoltage - Isolation4kV (4000V)Efficiency91%Operating Temperature-Voltage - Isolation-Aplications-FeaturesAdjustable Output, I2C? Interface, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input					
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series LCM1500 Type Front End Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Output 5 1500W Power (Watts) 1500W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 91% Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, I2C? Interface, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type <td< td=""><td>Manufacturer Part Number</td><td>LCM1500R-T-1</td></td<>	Manufacturer Part Number	LCM1500R-T-1			
AC DC Converters Package - Series LCM1500 Type Front End Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Output 5 500W Current - Output (Max) 43A Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 91% Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, I2C? Interface, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chasis Mount Size / Dimension 10.00° L x 5.20° W x 2.43° H (254.0mm x 132.0mm x 61.7mm)	Manufacturer	cturer Artesyn Embedded Technologies			
Package-SeriesLCM1500TypeFront EndNumber of Outputs10 ~ 264 VAC0 ~ 264 VACVoltage - Output 136V2012ge - Output 2-0 ~ 264 VAC-Voltage - Output 3-0 ~ 264 VAC-Voltage - Output 4-0 ~ 264 VAC-Voltage - Output 5-0 ~ 264 VAC-Voltage - Output 4-0 ~ 264 VAC-Voltage - Output 5-0 ~ 264 VAC-Voltage - Output 4-1 ~ 200 V-Voltage - Output 5-1 ~ 200 V-Voltage - Output 4-1 ~ 200 V-Voltage - Soltation1500VVoltage - Isolation4V (4000V)Efficiency91%Operating Temperatur 200 C (With Derating)Patures-Nouting TypeChasis MouttSiz / Dimension10.00" L x 5.20" W x 2.43" H (254.0mm x 132.0mm x 61.7mm)	Category	Power Supplies - External/Internal (Off-Board)			
Series LCM1500 Type Front End Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Solation HSGOW Applications TE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 91% Operating Temperature -40°C ~ 70°C (With Derating) Paulee Adjustable Output, I2C? Interface, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 10.00" L x 5.20" W x 2.43" H (254.0mm x 132.0mm x 61.7mm)		AC DC Converters			
TypeFront EndNumber of Outputs1Voltage - Input90 ~ 264 VACVoltage - Output 136VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Soltage-Voltage - Soltage-	Package	-			
Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 43A Power (Watts) 1500W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 91% Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, I2C? Interface, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 10.00" L x 5.20" W x 2.43" H (254.0mm x 132.0mm x 61.7mm)	Series	LCM1500			
Voltage - Input 90 ~ 264 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Output 4 - Current - Output (Max) 43A Power (Watts) 1500W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 91% Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, 12C? Interface, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 10.00" L x 5.20" W x 2.43" H (254.0mm x 132.0mm x 61.7mm)	Туре	Front End			
Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Output 4 - Current - Output (Max) 43A Power (Watts) 1500W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 91% Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, 12C? Interface, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 10.00" L x 5.20" W x 2.43" H (254.0mm x 132.0mm x 61.7mm)	Number of Outputs	1			
Voltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)43APower (Watts)1500WApplicationsITE (Commercial), MedicalVoltage - Isolation4kV (4000V)Efficiency91%Operating Temperature-40°C ~ 70°C (With Derating)FeaturesAdjustable Output, I2C? Interface, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension10.00" L x 5.20" W x 2.43" H (254.0mm x 132.0mm x 61.7mm)	Voltage - Input	90 ~ 264 VAC			
Voltage - Output 3-Voltage - Output 4-Current - Output (Max)43APower (Watts)1500WApplicationsITE (Commercial), MedicalVoltage - Isolation4kV (4000V)Efficiency91%Operating Temperature-40°C ~ 70°C (With Derating)FeaturesAdjustable Output, I2C? Interface, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension10.00" L x 5.20" W x 2.43" H (254.0mm x 132.0mm x 61.7mm)	Voltage - Output 1	36V			
Voltage - Output 4-Current - Output (Max)43APower (Watts)1500WApplicationsITE (Commercial), MedicalVoltage - Isolation4kV (4000V)Efficiency91%Operating Temperature-40°C ~ 70°C (With Derating)FeaturesAdjustable Output, I2C? Interface, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension10.00" L x 5.20" W x 2.43" H (254.0mm x 132.0mm x 61.7mm)	Voltage - Output 2	-			
Current - Output (Max)43APower (Watts)1500WApplicationsITE (Commercial), MedicalVoltage - Isolation4kV (4000V)Efficiency91%Operating Temperature-40°C ~ 70°C (With Derating)FeaturesAdjustable Output, I2C? Interface, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension10.00" L x 5.20" W x 2.43" H (254.0mm x 132.0mm x 61.7mm)	Voltage - Output 3	-			
Power (Watts)1500WApplicationsITE (Commercial), MedicalVoltage - Isolation4kV (4000V)Efficiency91%Operating Temperature-40°C ~ 70°C (With Derating)FeaturesAdjustable Output, I2C? Interface, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension10.00" L x 5.20" W x 2.43" H (254.0mm x 132.0mm x 61.7mm)	Voltage - Output 4	-			
ApplicationsITE (Commercial), MedicalVoltage - Isolation4kV (4000V)Efficiency91%Operating Temperature-40°C ~ 70°C (With Derating)FeaturesAdjustable Output, I2C? Interface, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension10.00" L x 5.20" W x 2.43" H (254.0mm x 132.0mm x 61.7mm)	Current - Output (Max)	43A			
NAkV (4000V)Efficiency91%Operating Temperature-40°C ~ 70°C (With Derating)FeaturesAdjustable Output, I2C? Interface, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension10.00" L x 5.20" W x 2.43" H (254.0mm x 132.0mm x 61.7mm)	Power (Watts)	1500W			
Efficiency91%Operating Temperature-40°C ~ 70°C (With Derating)FeaturesAdjustable Output, 12C? Interface, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension10.00" L x 5.20" W x 2.43" H (254.0mm x 132.0mm x 61.7mm)	Applications	ITE (Commercial), Medical			
Operating Temperature-40°C ~ 70°C (With Derating)FeaturesAdjustable Output, I2C? Interface, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension10.00" L x 5.20" W x 2.43" H (254.0mm x 132.0mm x 61.7mm)	Voltage - Isolation	4kV (4000V)			
FeaturesAdjustable Output, I2C? Interface, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension10.00" L x 5.20" W x 2.43" H (254.0mm x 132.0mm x 61.7mm)	Efficiency	91%			
FeaturesInputMounting TypeChassis MountSize / Dimension10.00" L x 5.20" W x 2.43" H (254.0mm x 132.0mm x 61.7mm)	Operating Temperature	-40° C ~ 70° C (With Derating)			
Size / Dimension 10.00" L x 5.20" W x 2.43" H (254.0mm x 132.0mm x 61.7mm)	Features	5 1			
	Mounting Type	Chassis Mount			
Report errors?	Size / Dimension	10.00" L x 5.20" W x 2.43" H (254.0mm x 132.0mm x 61.7mm)			
		Report errors?			

LCM1500R-T-1 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE GUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

LCM1500R-T-1 Payment Methods



LCM1500R-T-1 Shipping Methods



If you have any question about LCM1500R-T-1, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com