

### **LDC240-24 Information**

Part Number LDC240-24

**Manufacturer** Bel Power Solutions

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

**Description** AC/DC CONVERTER 24V 240W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **LDC240-24 Specifications**

Manufacturer Part Number         LDC240-24           Manufacturer         Bel Power Solutions           Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         LDC240           Type         Enclosed           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         10A           Applications         ITE (Commercial)           Voltage - Isolation         4.2kV (4200V)           Efficiency         93%           Operating Temperature         4.0°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, IP20, PFC, Universal Input           Mounting Type         DIN Rail           Size / Dimension         4.33" L x 1.57" W x 4.53" H (110.0mm x 40.0mm x 115.0mm)	•	
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         LDC240           Type         Enclosed           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         10A           Power (Watts)         240W           Applications         ITE (Commercial)           Voltage - Isolation         4.2kV (4200V)           Efficiency         93%           Operating Temperature         -40°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, IP20, PFC, Universal Input           Mounting Type         DIN Rail           Size / Dimension         4.33" L x 1.57" W x 4.53" H (110.0mm x 40.0mm x 115.0mm)	Manufacturer Part Number	LDC240-24
Package         -           Series         LDC240           Type         Enclosed           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         10A           Power (Watts)         240W           Applications         ITE (Commercial)           Voltage - Isolation         4.2kV (4200V)           Efficiency         93%           Operating Temperature         -40°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, IP20, PFC, Universal Input           Mounting Type         DIN Rail           Size / Dimension         4.33" L x 1.57" W x 4.53" H (110.0mm x 40.0mm x 115.0mm)	Manufacturer	Bel Power Solutions
Package         -           Series         LDC240           Type         Enclosed           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         10A           Power (Watts)         240W           Applications         ITE (Commercial)           Voltage - Isolation         4.2kV (4200V)           Efficiency         93%           Operating Temperature         -40°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, IP20, PFC, Universal Input           Mounting Type         DIN Rail           Size / Dimension         4.33" L x 1.57" W x 4.53" H (110.0mm x 40.0mm x 115.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         LDC240           Type         Enclosed           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         10A           Power (Watts)         240W           Applications         ITE (Commercial)           Voltage - Isolation         4.2kV (4200V)           Efficiency         93%           Operating Temperature         -40°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, IP20, PFC, Universal Input           Mounting Type         DIN Rail           Size / Dimension         4.33" L x 1.57" W x 4.53" H (110.0mm x 40.0mm x 115.0mm)		AC DC Converters
Type         Enclosed           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         10A           Power (Watts)         240W           Applications         ITE (Commercial)           Voltage - Isolation         4.2kV (4200V)           Efficiency         93%           Operating Temperature         -40°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, IP20, PFC, Universal Input           Mounting Type         DIN Rail           Size / Dimension         4.33" L x 1.57" W x 4.53" H (110.0mm x 40.0mm x 115.0mm)	Package	-
Number of Outputs       1         Voltage - Input       90 ~ 264 VAC         Voltage - Output 1       24V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       10A         Power (Watts)       240W         Applications       ITE (Commercial)         Voltage - Isolation       4.2kV (4200V)         Efficiency       93%         Operating Temperature       -40°C ~ 70°C (With Derating)         Features       Adjustable Output, DC Input Capable, IP20, PFC, Universal Input         Mounting Type       DIN Rail         Size / Dimension       4.33" L x 1.57" W x 4.53" H (110.0mm x 40.0mm x 115.0mm)	Series	LDC240
Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         10A           Power (Watts)         240W           Applications         ITE (Commercial)           Voltage - Isolation         4.2kV (4200V)           Efficiency         93%           Operating Temperature         -40°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, IP20, PFC, Universal Input           Mounting Type         DIN Rail           Size / Dimension         4.33" L x 1.57" W x 4.53" H (110.0mm x 40.0mm x 115.0mm)	Type	Enclosed
Voltage - Output 1  Voltage - Output 2  - Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  Voltage - Isolation  4.2kV (4200V)  Efficiency  Operating Temperature  -40°C ~ 70°C (With Derating)  Features  Adjustable Output, DC Input Capable, IP20, PFC, Universal Input  Mounting Type  DIN Rail  Size / Dimension  4.33" L x 1.57" W x 4.53" H (110.0mm x 40.0mm x 115.0mm)	Number of Outputs	1
Voltage - Output 2  Voltage - Output 3  - Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  4.2kV (4200V)  Efficiency  Operating Temperature  -40°C ~ 70°C (With Derating)  Features  Adjustable Output, DC Input Capable, IP20, PFC, Universal Input  Mounting Type  DIN Rail  Size / Dimension  4.33" L x 1.57" W x 4.53" H (110.0mm x 40.0mm x 115.0mm)	Voltage - Input	90 ~ 264 VAC
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  4.2kV (4200V)  Efficiency  Operating Temperature  -40°C ~ 70°C (With Derating)  Features  Adjustable Output, DC Input Capable, IP20, PFC, Universal Input  Mounting Type  DIN Rail  Size / Dimension  4.33" L x 1.57" W x 4.53" H (110.0mm x 40.0mm x 115.0mm)	Voltage - Output 1	24V
Voltage - Output 4  Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  4.2kV (4200V)  Efficiency  93%  Operating Temperature  -40°C ~ 70°C (With Derating)  Features  Adjustable Output, DC Input Capable, IP20, PFC, Universal Input  Mounting Type  DIN Rail  Size / Dimension  4.33" L x 1.57" W x 4.53" H (110.0mm x 40.0mm x 115.0mm)	Voltage - Output 2	-
Current - Output (Max)  Power (Watts)  240W  Applications  ITE (Commercial)  Voltage - Isolation  4.2kV (4200V)  Efficiency  93%  Operating Temperature  -40°C ~ 70°C (With Derating)  Features  Adjustable Output, DC Input Capable, IP20, PFC, Universal Input  Mounting Type  DIN Rail  Size / Dimension  4.33" L x 1.57" W x 4.53" H (110.0mm x 40.0mm x 115.0mm)		-
Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  4.2kV (4200V)  Efficiency  93%  Operating Temperature  -40°C ~ 70°C (With Derating)  Features  Adjustable Output, DC Input Capable, IP20, PFC, Universal Input  Mounting Type  DIN Rail  Size / Dimension  4.33" L x 1.57" W x 4.53" H (110.0mm x 40.0mm x 115.0mm)	Voltage - Output 4	-
Applications ITE (Commercial)  Voltage - Isolation 4.2kV (4200V)  Efficiency 93%  Operating Temperature -40°C ~ 70°C (With Derating)  Features Adjustable Output, DC Input Capable, IP20, PFC, Universal Input  Mounting Type DIN Rail  Size / Dimension 4.33" L x 1.57" W x 4.53" H (110.0mm x 40.0mm x 115.0mm)	Current - Output (Max)	10A
Voltage - Isolation 4.2kV (4200V)  Efficiency 93%  Operating Temperature -40°C ~ 70°C (With Derating)  Features Adjustable Output, DC Input Capable, IP20, PFC, Universal Input  Mounting Type DIN Rail  Size / Dimension 4.33" L x 1.57" W x 4.53" H (110.0mm x 40.0mm x 115.0mm)	Power (Watts)	240W
Efficiency 93%  Operating Temperature -40°C ~ 70°C (With Derating)  Features Adjustable Output, DC Input Capable, IP20, PFC, Universal Input  Mounting Type DIN Rail  Size / Dimension 4.33" L x 1.57" W x 4.53" H (110.0mm x 40.0mm x 115.0mm)	Applications	ITE (Commercial)
Operating Temperature  -40°C ~ 70°C (With Derating)  Features  Adjustable Output, DC Input Capable, IP20, PFC, Universal Input  Mounting Type  DIN Rail  Size / Dimension  4.33" L x 1.57" W x 4.53" H (110.0mm x 40.0mm x 115.0mm)	Voltage - Isolation	4.2kV (4200V)
Features Adjustable Output, DC Input Capable, IP20, PFC, Universal Input  Mounting Type DIN Rail  Size / Dimension 4.33" L x 1.57" W x 4.53" H (110.0mm x 40.0mm x 115.0mm)	Efficiency	93%
Mounting Type DIN Rail Size / Dimension 4.33" L x 1.57" W x 4.53" H (110.0mm x 40.0mm x 115.0mm)	Operating Temperature	-40°C ~ $70$ °C (With Derating)
Size / Dimension 4.33" L x 1.57" W x 4.53" H (110.0mm x 40.0mm x 115.0mm)	Features	Adjustable Output, DC Input Capable, IP20, PFC, Universal Input
	Mounting Type	DIN Rail
Report errors?	Size / Dimension	4.33" L x 1.57" W x 4.53" H (110.0mm x 40.0mm x 115.0mm)
		Report errors?

#### LDC240-24 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **LDC240-24 Payment Methods**



















### **LDC240-24 Shipping Methods**













If you have any question about LDC240-24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com