

LDEDD3680JA5N00

LDEDD3680JA5N00 Information



Part Number	LDEDD3680JA5N00
Manufacturer	KEMET
Category	Capacitors Film Capacitors
Description	CAP FILM 0.68UF 5% 63VDC 2220
Package	2220 (5750 Metric)
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



LDEDD3680JA5N00 Specifications

Manufacturer Part NumberLDEDD3680JA5N00ManufacturerKEMETCategoryCapacitorsFilm CapacitorsFilm CapacitorsPackage220 (5750 Metric)SeriesLDECapacitance0.68µFYoltage Rating - AC40VVoltage Rating - DC63VDielectric Material9.09ester, Polyethylene Naphthalate (PEN), Metallized - StackedFigury and Particip55°C ~ 125°CMounting Type9.020 (5750 Metric)Nouting Type220 (5750 Metric)Size / Dimension200 (5750 Metric)Fight - Seated (Max)0.30° (1 x 0.197" W (6.00mm x 5.00mm)Fight - Seated (Max)0.30ler PadsFirminationSolder PadsLead Spacing-Lead Spacing-Stare Spacing-Solder Pads-Solder Pads- <t< th=""><th></th><th></th><th></th></t<>			
CategoryCapacitorsFilm CapacitorsPackage220 (5750 Metric)SeriesLDECapacitance0.68µFTolerance±5%Voltage Rating - AC40VVoltage Rating - DC63VDielectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedSR (Equivalent Series Resistance)-Aponting TypeSufface MountPackage / Case2200 (5750 Metric)Size / Dimension0.236° L x 0.197° W (6.00mm x 5.00mm)Height - Seated (Max)0.100° (3.30mm)Lead Spacing0.101° PackageLead Spacing0.101° Package	Manufacturer Part Number	LDEDD3680JA5N00	
Film CapacitorsPackage2220 (5750 Metric)SeriesLDECapacitance0.68µFTolerance±5%Voltage Rating - AC40VVoltage Rating - DC63VDielectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedSR (Equivalent Series Resistance)-Operating Temperature55°C ~ 125°CMounting TypeSurface MountPackage / Case2200 (5750 Metric)Size / Dimension0.130° (3.30mm)TerminationSolder PadsLead Spacing-	Manufacturer	KEMET	
Package2220 (5750 Metric)SeriesLDECapacitance0.68µFTolerance±5%Voltage Rating - AC40VVoltage Rating - DC63VDielectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case2220 (5750 Metric)Size / Dimension0.130" (3.30mm)Height - Seated (Max)50der PadsLead Spacing-	Category	Capacitors	
SeriesLDECapacitance0.68µFTolerance±5%Voltage Rating - AC40VVoltage Rating - DC63VDielectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedDielectric Material-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case2220 (5750 Metric)Size / Dimension0.330° (1 x 0.197° W (6.00mm x 5.00mm)Height - Seated (Max)Solder PadsLead Spacing-		Film Capacitors	
Capacitance0.68µFTolerance±5%Voltage Rating - AC40VVoltage Rating - DC63VDielectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case0.220 (5750 Metric)Size / Dimension0.130° (3.30mm)Height - Seated (Max)Solder PadsLead Spacing-	Package	2220 (5750 Metric)	
Tolerance±5%Yoltage Rating - AC40VVoltage Rating - DC63VDielectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case2220 (5750 Metric)Size / Dimension0.336" L x 0.197" W (6.00mm x 5.00mm)Height - Seated (Max)0.130" (3.30mm)TerminationSolder PadsLead Spacing-	Series	LDE	
Voltage Rating - AC40VVoltage Rating - DC63VDielectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case2220 (5750 Metric)Size / Dimension0.236" L x 0.197" W (6.00mm x 5.00mm)Height - Seated (Max)0.130" (3.30mm)TerminationSolder PadsLead Spacing-	Capacitance	0.68µF	
Voltage Rating - DC63VDielectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case2220 (5750 Metric)Size / Dimension0.236" L x 0.197" W (6.00mm x 5.00mm)Height - Seated (Max)0.130" (3.30mm)TerminationSolder PadsLead Spacing-	Tolerance	±5%	
Dielectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case2220 (5750 Metric)Size / Dimension0.236" L x 0.197" W (6.00mm x 5.00mm)Height - Seated (Max)0.130" (3.30mm)TerminationSolder PadsLead Spacing-	Voltage Rating - AC	40V	
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case2220 (5750 Metric)Size / Dimension0.236" L x 0.197" W (6.00mm x 5.00mm)Height - Seated (Max)0.130" (3.30mm)TerminationSolder PadsLead Spacing-	Voltage Rating - DC	63V	
Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case2220 (5750 Metric)Size / Dimension0.236" L x 0.197" W (6.00mm x 5.00mm)Height - Seated (Max)0.130" (3.30mm)TerminationSolder PadsLead Spacing-	Dielectric Material	Polyester, Polyethylene Naphthalate (PEN), Metallized - Stacked	
Mounting TypeSurface MountPackage / Case2220 (5750 Metric)Size / Dimension0.236" L x 0.197" W (6.00mm x 5.00mm)Height - Seated (Max)0.130" (3.30mm)TerminationSolder PadsLead Spacing-	ESR (Equivalent Series Resistance)	-	
Package / Case2220 (5750 Metric)Size / Dimension0.236" L x 0.197" W (6.00mm x 5.00mm)Height - Seated (Max)0.130" (3.30mm)TerminationSolder PadsLead Spacing-	Operating Temperature	-55°C ~ 125°C	
Size / Dimension 0.236" L x 0.197" W (6.00mm x 5.00mm) Height - Seated (Max) 0.130" (3.30mm) Termination Solder Pads Lead Spacing -	Mounting Type	Surface Mount	
Height - Seated (Max)0.130" (3.30mm)TerminationSolder PadsLead Spacing-	Package / Case	2220 (5750 Metric)	
Termination Solder Pads Lead Spacing -	Size / Dimension	0.236" L x 0.197" W (6.00mm x 5.00mm)	
Lead Spacing -	Height - Seated (Max)	0.130" (3.30mm)	
	Termination	Solder Pads	
	Lead Spacing	-	
Applications General Purpose	Applications	General Purpose	
Features High Temperature	Features	High Temperature	
Report errors?			Report errors?

LDEDD3680JA5N00 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

LDEDD3680JA5N00 Payment Methods



LDEDD3680JA5N00 Shipping Methods



If you have any question about LDEDD3680JA5N00, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com