

LDS100-24-U00

LDS100-24-U00 Information

WWW.hesenanter	1 41 0 1 (4115)01	LDS100-24-U00 Artesyn Embedded Technologies Power Supplies - External/Internal (Off-Board) LED Drivers LED DVR CC/CV AC/DC 0-24V 4.1A - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



LDS100-24-U00 Specifications

Manufacturer Part NumberLDS100-24-U00ManufacturerArtesyn Embedded TechnologiesCategoryPower Supplies - External/Internal (Off-Board)LED DriversPackage-SeriesLDS100TypeConstant Current, VoltageYopologyAC DC ConverterNumber of Outputs1Voltage - Input (Min)100VACVoltage - Output4.1APower (Watts)100WVoltage - Isolation1.00WVoltage Isolation6.24 VFormer (Matting)1.00WPower (Watts)1.00WVoltage Isolation6.24 NNorting6.24 NStateger (Matting)6.24 NPower (Watts)1.00WVoltage Isolation6.24 NManuf (Matting)6.24 NStateger (Matting)6.24 NStateger (Matting)1.00WStateger (Matting)6.24 NStateger (Matting)1.00WStateger (Matting)6.24 NStateger (Matting)<		
CategoryPower Supplies - External/Internal (Off-Board)IED DriversPackage-SeriesLDS100TypeConstant Current, VoltageTopologyAC DC ConverterNumber of Outputs1Voltage - Input (Max)100VACVoltage - Output0~24 VCurrent - Output (Max)100WACPower (Watts)100WPower (Watts)00WVoltage - Input (Max)5.Power (Watts)0.Power (Watts)0.Power (Watts)0.Power (Watts)-Pomining-FeaturesOTP, OVP, SCPRatingsIP67	Manufacturer Part Number	LDS100-24-U00
LED DriversPackage-SeriesLDS100TypeConstant Current, VoltageTopologyAC DC ConverterNumber of Outputs1Voltage - Input (Min)100VACVoltage - Input (Max)240VACVoltage - Output0 ~ 24 VCurrent - Output (Max)100WPower (Watts)100WVoltage - Input (Max)5Power (Watts)0.0Pomer (Watts)0.0Koltage - Input (Max)9Power (Watts)100WPower (Watts)0.0Power (Watts)9Power (Watts)<	Manufacturer	Artesyn Embedded Technologies
Package - Package - Series LDS100 Type Constant Current, Voltage Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 100VAC Voltage - Input (Max) 240VAC Voltage - Output 0~24 V Current - Output (Max) 100W Voltage - Isolation - Power (Watts) 0.00W Voltage - Isolation - Features OTP, SCP Ratings Ipo	Category	Power Supplies - External/Internal (Off-Board)
SeriesLDS100TypeConstant Current, VoltageTopologyAC DC ConverterNumber of Outputs1Voltage - Input (Max)100VACVoltage - Output240VACVoltage - Output0 ~ 24 VPower (Wats)100WVoltage - Isolation.Pomering-FeaturesOTP, OVP, SCPRatingsIP67		LED Drivers
TypeConstant Current, VoltageTopologyAC DC ConverterNumber of Outputs1Voltage - Input (Min)100VACVoltage - Output240VACVoltage - Output0~24 VCurrent - Output (Max)100WPower (Watts)100WVoltage - Isolation-Pinning-FeaturesOTP, OVEP, SCPRatingsIP67	Package	-
TopologyAC DC ConverterNumber of Outputs1Voltage - Input (Min)100VACVoltage - Input (Max)240VACVoltage - Output0 ~ 24 VCurrent - Output (Max)4.1APower (Watts)100WVoltage - Isolation-Dimming-FeaturesOTP, OVP, SCPRatingsIP67	Series	LDS100
Number of Outputs1Number of Outputs100VACVoltage - Input (Max)240VACVoltage - Output0 ~ 24 VCurrent - Output (Max)4.1APower (Watts)100WVoltage - Isolation-Dimming-FeaturesOTP, OVP, SCPRatingsIP67	Туре	Constant Current, Voltage
Voltage - Input (Min) 100VAC Voltage - Input (Max) 240VAC Voltage - Output 0 ~ 24 V Current - Output (Max) 4.1A Power (Watts) 100W Voltage - Isolation - Dimming - Features OTP, OVP, SCP Ratings IP67	Topology	AC DC Converter
Voltage - Input (Max)240VACVoltage - Output0 ~ 24 VCurrent - Output (Max)4.1APower (Watts)100WVoltage - Isolation-Dimming-FeaturesOTP, OVP, SCPRatingsIP67	Number of Outputs	1
Voltage - Output0 ~ 24 VCurrent - Output (Max)4.1APower (Watts)100WVoltage - Isolation-Dimming-FeaturesOTP, OVP, SCPRatingsIP67	Voltage - Input (Min)	100VAC
Current - Output (Max)4.1APower (Watts)100WVoltage - Isolation-Dimming-FeaturesOTP, OVP, SCPRatingsIP67	Voltage - Input (Max)	240VAC
Power (Watts)100WVoltage - Isolation-Dimming-FeaturesOTP, OVP, SCPRatingsIP67	Voltage - Output	0 ~ 24 V
Voltage - Isolation-Dimming-FeaturesOTP, OVP, SCPRatingsIP67	Current - Output (Max)	4.1A
Dimming-FeaturesOTP, OVP, SCPRatingsIP67	Power (Watts)	100W
FeaturesOTP, OVP, SCPRatingsIP67	Voltage - Isolation	-
Ratings IP67	Dimming	-
	Features	OTP, OVP, SCP
	Ratings	IP67
Operating Temperature $-40^{\circ}\text{C} \sim 90^{\circ}\text{C}$	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 90^{\circ}\mathrm{C}$
Efficiency 89%	Efficiency	89%
Termination Style Wire Leads	Termination Style	Wire Leads
Size / Dimension 9.67" L x 1.65" W x 1.05" H (245.5mm x 42.0mm x 26.7mm)	Size / Dimension	9.67" L x 1.65" W x 1.05" H (245.5mm x 42.0mm x 26.7mm)
Report erro		Report errors?

LDS100-24-U00 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

LDS100-24-U00 Payment Methods



LDS100-24-U00 Shipping Methods



If you have any question about LDS100-24-U00, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com