

LEA150F-9-Y Information

Heisener.com

Part Number LEA150F-9-Y **Manufacturer** Cosel USA, Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC PS (OPEN FRAME)

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LEA150F-9-Y Specifications

| Manufacturer Part Number LEA150F-9-Y Manufacturer Cosel USA, Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series LEA Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 9V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 17A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -20°C ~ 70°C (With Derating) Features Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | | |
|--|--------------------------|---|
| Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series LEA Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 9V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 17A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -20°C ~ 70°C (With Derating) Features Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | Manufacturer Part Number | LEA150F-9-Y |
| Package - Series LEA Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 9V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 17A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -20°C ~ 70°C (With Derating) Features Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | Manufacturer | Cosel USA, Inc. |
| Package - Series LEA Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 9V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 17A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -20°C ~ 70°C (With Derating) Features Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | Category | Power Supplies - External/Internal (Off-Board) |
| Series LEA Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 9V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 17A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -20°C ~ 70°C (With Derating) Features Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | | AC DC Converters |
| Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 9V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 17A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -20°C ~ 70°C (With Derating) Features Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | Package | - |
| Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 9V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 17A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -20°C ~ 70°C (With Derating) Features Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | Series | LEA |
| Voltage - Input 85 ~ 264 VAC Voltage - Output 1 9V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 17A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -20°C ~ 70°C (With Derating) Features Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | Туре | Open Frame |
| Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation Size / Dimension 9V Size / Dimension 9V 9V 9V 9V 9V 9V 9V 9V 9V | Number of Outputs | 1 |
| Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature Features Remote On/Off, Universal Input Mounting Type Size / Dimension - Current - Output (Max) 17A 150W 150W 150W 150W 150W 150W 17E (Commercial) 3kV (3000V) 682% Chassis Mount Size / Dimension 8.74" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | Voltage - Input | 85 ~ 264 VAC |
| Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation Size / Dimension Size / Dimension - Current - Output (Max) ITA - Current - Outp | Voltage - Output 1 | 9V |
| Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -20°C ~ 70°C (With Derating) Features Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension -20°C ~ 70°C W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | Voltage - Output 2 | - |
| Current - Output (Max) Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -20°C ~ 70°C (With Derating) Features Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension 17A 150W 1600 17A 1600 17A 1600 17A 1600 17A 1600 17A 1600 1600 1600 1700 | Voltage - Output 3 | - |
| Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -20°C ~ 70°C (With Derating) Features Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension 150W Remote On/Off With Derating Remote On/Off, Universal Input Chassis Mount 8.74" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | Voltage - Output 4 | - |
| Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -20°C ~ 70°C (With Derating) Features Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | Current - Output (Max) | 17A |
| Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -20°C ~ 70°C (With Derating) Features Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | Power (Watts) | 150W |
| Efficiency 82% Operating Temperature -20°C ~ 70°C (With Derating) Features Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | Applications | ITE (Commercial) |
| Operating Temperature -20°C ~ 70°C (With Derating) Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension -20°C ~ 70°C (With Derating) Remote On/Off, Universal Input Chassis Mount 8.74" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | Voltage - Isolation | 3kV (3000V) |
| Features Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | Efficiency | 82% |
| Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | Operating Temperature | -20°C ~ 70°C (With Derating) |
| Size / Dimension 8.74" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | Features | Remote On/Off, Universal Input |
| | Mounting Type | Chassis Mount |
| Report errors? | Size / Dimension | 8.74" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) |
| | | Report errors? |

LEA150F-9-Y Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LEA150F-9-Y Payment Methods





















LEA150F-9-Y Shipping Methods













If you have any question about LEA150F-9-Y, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com