



LEA50F-5-SNC Information

Part Number LEA50F-5-SNC **Manufacturer** Cosel USA, Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC PS (OPEN FRAME)

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LEA50F-5-SNC Specifications

Manufacturer Part Number LEA50F-5-SNC Manufacturer Cosel USA, Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series LEA Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -20°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 0.91" H (195.0mm x 55.0mm x 23.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series LEA Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -20°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 0.91" H (195.0mm x 55.0mm x 23.0mm)	Manufacturer Part Number	LEA50F-5-SNC
Package - Series LEA Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -20°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 0.91" H (195.0mm x 55.0mm x 23.0mm)	Manufacturer	Cosel USA, Inc.
Package - Series LEA Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -20°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 0.91" H (195.0mm x 55.0mm x 23.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series LEA Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -20°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 0.91" H (195.0mm x 55.0mm x 23.0mm)		AC DC Converters
Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -20°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 0.91" H (195.0mm x 55.0mm x 23.0mm)	Package	-
Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -20°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 0.91" H (195.0mm x 55.0mm x 23.0mm)	Series	LEA
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -20°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 0.91" H (195.0mm x 55.0mm x 23.0mm)	Туре	Enclosed
Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation Sty (3000V) Efficiency Operating Temperature -20°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5V	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation Sity (3000V) Efficiency Operating Temperature Features Universal Input Mounting Type Chassis Mount Size / Dimension - Output (Max) - Current - Outp	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature -20°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension - Output 4 - Chassis Mount	Voltage - Output 1	5V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -20°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 0.91" H (195.0mm x 55.0mm x 23.0mm)	Voltage - Output 2	-
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -20°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 10A 10A 10A 10A 10A 10B 10B 10B	Voltage - Output 3	-
Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -20°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 0.91" H (195.0mm x 55.0mm x 23.0mm)	Voltage - Output 4	-
Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -20°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 0.91" H (195.0mm x 55.0mm x 23.0mm)	Current - Output (Max)	10A
Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -20°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 0.91" H (195.0mm x 55.0mm x 23.0mm)	Power (Watts)	50W
Efficiency 77% Operating Temperature -20°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 0.91" H (195.0mm x 55.0mm x 23.0mm)	Applications	ITE (Commercial)
Operating Temperature -20°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 0.91" H (195.0mm x 55.0mm x 23.0mm)	Voltage - Isolation	3kV (3000V)
Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 0.91" H (195.0mm x 55.0mm x 23.0mm)	Efficiency	77%
Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 0.91" H (195.0mm x 55.0mm x 23.0mm)	Operating Temperature	-20°C ~ 70°C (With Derating)
Size / Dimension 7.68" L x 2.17" W x 0.91" H (195.0mm x 55.0mm x 23.0mm)	Features	Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	7.68" L x 2.17" W x 0.91" H (195.0mm x 55.0mm x 23.0mm)
		Report errors?

LEA50F-5-SNC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LEA50F-5-SNC Payment Methods



















LEA50F-5-SNC Shipping Methods













If you have any question about LEA50F-5-SNC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com