

LEA75F-12-SY Information

Heisener.com

Part Number LEA75F-12-SY Manufacturer Cosel USA, Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC PS (OPEN FRAME)

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only E-mail: salesdept@heisener.com





Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LEA75F-12-SY Specifications

Manufacturer Part Number LEA75F-12-SY Manufacturer Cosel USA, Inc. Category Power Supplies - External/Internal (Off-Board) Package - Series LEA Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.3A Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 80% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	•	
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series LEA Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.3A Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 80% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	Manufacturer Part Number	LEA75F-12-SY
Package - Series LEA Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.3A Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 80% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	Manufacturer	Cosel USA, Inc.
Package - Series LEA Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.3A Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 80% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series LEA Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.3A Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 80% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)		AC DC Converters
Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.3A Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 80% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	Package	-
Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.3A Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 80% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	Series	LEA
Voltage - Input85 ~ 264 VACVoltage - Output 112VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)6.3APower (Watts)75WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency80%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Universal InputMounting TypeChassis MountSize / Dimension8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	Type	Open Frame
Voltage - Output 112VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)6.3APower (Watts)75WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency80%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Universal InputMounting TypeChassis MountSize / Dimension8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type Size / Dimension	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation Sire / Dimension Size / Dimension - Current - Output (Max) 6.3A Power (Watts) 75W ITE (Commercial) 3kV (3000V) 80% Operating Temperature -20°C ~ 70°C (With Derating) Adjustable Output, PFC, Universal Input Size / Dimension 8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	Voltage - Output 1	12V
Voltage - Output 4 Current - Output (Max) 6.3A Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 80% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	Voltage - Output 2	-
Current - Output (Max) 6.3A Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 80% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	Voltage - Output 3	-
Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 80% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	Voltage - Output 4	-
Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 80% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	Current - Output (Max)	6.3A
Voltage - Isolation 3kV (3000V) Efficiency 80% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	Power (Watts)	75W
Efficiency 80% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	Applications	ITE (Commercial)
Operating Temperature -20°C ~ 70°C (With Derating) Adjustable Output, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	Voltage - Isolation	3kV (3000V)
Features Adjustable Output, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	Efficiency	80%
Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	Operating Temperature	-20°C ~ 70°C (With Derating)
Size / Dimension 8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	Features	Adjustable Output, PFC, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)
		Report errors?

LEA75F-12-SY Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LEA75F-12-SY Payment Methods



















LEA75F-12-SY Shipping Methods













If you have any question about LEA75F-12-SY, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com