

# LEA75F-24-S

### **LEA75F-24-S Information**

| Heisener.com       | Part Number<br>Manufacturer<br>Category<br>Description<br>Package | LEA75F-24-S<br>Cosel USA, Inc.<br>Power Supplies - External/Internal (Off-Board)<br>AC DC Converters<br>AC/DC PS (OPEN FRAME)<br>-<br>For the pricing/inventory/lead time, please contact |                 |
|--------------------|---|---|-----------------|
| For Reference Only |   | us<br>Website: https://www.heisener.com<br>E-mail: salesdept@heisener.com   | Request a Quote |

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **LEA75F-24-S Specifications**

| Manufacturer Part NumberLEA75F-24-SManufacturerCosel USA, Inc.CategoryPower Supplies - External/Internal (Off-Board)AC DC ConvertersPackage-SeriesLEATypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 532APower (Watts)75WApplicationsTIF (Commercial)Voltage - Isolation3kV (3000V)Efficiency44%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesPFC, Universal InputMounting TypeChasis MountSize / DimensionKasi MountSize / DimensionKasi MountSize / DimensionKasi MountSize / DimensionSize / Dimension   | _                        |   |                |  |
|---|--------------------------|---|----------------|--|
| CategoryPower Supplies - External/Internal (Off-Board)AC DC ConvertersPackage-SeriesLEATypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 155 ~ 264 VACVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 5-Voltage - Soltation3LA (3000V)Power (Watts)-Voltage - Isolation-Voltage - Isolation-Voltage - Soltation-Voltage - Solta  | Manufacturer Part Number | LEA75F-24-S   |                |  |
| AC DC Converters   Package -   Series LEA   Type Open Frame   Number of Outputs 1   Voltage - Input 85 ~ 264 VAC   Voltage - Output 1 24V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Voltage - Solutoft 3.2A   Power (Watts) 75W   Voltage - Isolation 3kV (3000V)   Efficiency 84%   Operating Temperature -20°C ~ 70°C (With Derating)   Features PFC, Universal Input   Mounting Type Sasi Mount   Size / Dimension 8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)   | Manufacturer             | Cosel USA, Inc.   |                |  |
| Package-SeriesLEATypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 5-Voltage - Output 6-Voltage - Solation-Voltage - Isolation-Voltage - Isolation-Voltage - Solation-Voltage - Solation <td>Category</td> <td colspan="3">Power Supplies - External/Internal (Off-Board)</td> | Category                 | Power Supplies - External/Internal (Off-Board)          |                |  |
| SeriesLEATypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)3.2APower (Watts)TE (Commercial)ApplicationsHE (Commercial)Voltage - Isolation3.9V (3000V)Efficiency64%Operating Temperature-0°C ~ 70°C (With Derating)FeaturesFC, Universal InputMounting Type6.34" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)  |                          | AC DC Converters  |                |  |
| TypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 43.2APower (Wats)75WApplications1FE (commercial)Voltage - Isolation3kV (3000V)Efficiency64%Operating Temperature9C° ~ 70°C (With Derating)FeaturesPC, Universal InputMounting Type6.43" L x 2.17" W x 1.14" H (222.0mm x 29.0mm)   | Package                  | -   |                |  |
| Number of Outputs I   Voltage - Input 85 ~ 264 VAC   Voltage - Output 1 24V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 3.2A   Power (Wats) 75W   Applications ITE (Commercial)   Voltage - Isolation 3kV (3000V)   Efficiency 84%   Operating Temperature -20°C ~ 70°C (With Derating)   Features PFC, Universal Input   Mounting Type Chassis Mount   Size / Dimension 8.74" L x 2.17" W x 1.14" H (222.0mm x 25.0mm x 29.0mm)  | Series                   | LEA   |                |  |
| Voltage - Input 85 ~ 264 VAC   Voltage - Output 1 24V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 3.2A   Power (Watts) 75W   Applications ITE (Commercial)   Voltage - Isolation 3kV (3000V)   Efficiency 84%   Operating Temperature -20°C ~ 70°C (With Derating)   Features PFC, Universal Input   Mounting Type Chassis Mount   Size / Dimension 8.74" L x 2.17" W x 1.14" H (222.0mm x 25.0mm x 29.0mm)   | Туре                     | Open Frame  |                |  |
| Voltage - Output 1 24V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 3.2A   Power (Watts) 75W   Applications ITE (Commercial)   Voltage - Isolation 3kV (3000V)   Efficiency 84%   Operating Temperature -20°C ~ 70°C (With Derating)   Features PFC, Universal Input   Mounting Type S.47" L x 2.17" W x 1.14" H (222.0mm x 25.0mm x 29.0mm)   | Number of Outputs        | 1   |                |  |
| Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 3.2A   Power (Watts) 75W   Applications ITE (Commercial)   Voltage - Isolation 3kV (3000V)   Efficiency 84%   Operating Temperature -20°C ~70°C (With Derating)   Features PFC, Universal Input   Mounting Type Chassis Mount   Size / Dimension 8.74" L x 2.17" W x 1.14" H (222.0mm x 25.0mm x 29.0mm)  | Voltage - Input          | 85 ~ 264 VAC  |                |  |
| Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 3.2A   Power (Watts) 75W   Applications ITE (Commercial)   Voltage - Isolation 3kV (3000V)   Efficiency 84%   Operating Temperature -20°C ~ 70°C (With Derating)   Features PFC, Universal Input   Mounting Type Chassis Mount   Size / Dimension 8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)  | Voltage - Output 1       | 24V   |                |  |
| Voltage - Output 4-Current - Output (Max)3.2APower (Watts)75WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency84%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesPFC, Universal InputMounting TypeChassis MountSize / Dimension8.74" L x 2.17" W x 1.14" H (222.0mm x 29.0mm x 29.0mm)  | Voltage - Output 2       | -   |                |  |
| Current - Output (Max)3.2APower (Watts)75WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency84%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesPFC, Universal InputMounting TypeChassis MountSize / Dimension8.74" L x 2.17" W x 1.14" H (222.0mm x 25.0mm x 29.0mm)   | Voltage - Output 3       | -   |                |  |
| Power (Watts)75WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency84%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesPFC, Universal InputMounting TypeChassis MountSize / Dimension8.74" L x 2.17" W x 1.14" H (222.0mm x 25.0mm x 29.0mm)   | Voltage - Output 4       | -   |                |  |
| ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency84%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesPFC, Universal InputMounting TypeChassis MountSize / Dimension8.74" L x 2.17" W x 1.14" H (222.0mm x 25.0mm x 29.0mm)   | Current - Output (Max)   | 3.2A  |                |  |
| Voltage - Isolation3kV (3000V)Efficiency84%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesPFC, Universal InputMounting TypeChassis MountSize / Dimension8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)   | Power (Watts)            | 75W   |                |  |
| Efficiency84%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesPFC, Universal InputMounting TypeChassis MountSize / Dimension8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)   | Applications             | ITE (Commercial)  |                |  |
| Operating Temperature-20°C ~ 70°C (With Derating)FeaturesPFC, Universal InputMounting TypeChassis MountSize / Dimension8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)  | Voltage - Isolation      | 3kV (3000V)   |                |  |
| FeaturesPFC, Universal InputMounting TypeChassis MountSize / Dimension8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)   | Efficiency               | 84%   |                |  |
| Mounting TypeChassis MountSize / Dimension8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)   | Operating Temperature    | $-20^{\circ}$ C ~ $70^{\circ}$ C (With Derating)        |                |  |
| Size / Dimension 8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)  | Features                 | PFC, Universal Input                                    |                |  |
|   | Mounting Type            | Chassis Mount   |                |  |
| Report errors?  | Size / Dimension         | 8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm) |                |  |
| 1   |                          |   | Report errors? |  |

#### **LEA75F-24-S Guarantees**



#### Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# E Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# LEA75F-24-S Payment Methods WIRE PayPai Methods LEA75F-24-S Shipping Methods EEEEE. In Origination International Internationa

If you have any question about LEA75F-24-S, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com