

### **LEA75F-5-S Information**

Heisener.com

**Part Number** LEA75F-5-S **Manufacturer** Cosel USA, Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

**Description** AC/DC PS (OPEN FRAME)

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com

Request a Quote



# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **LEA75F-5-S Specifications**

Manufacturer Part Number         LEA75F-5-S           Manufacturer         Cosel USA, Inc.           Category         Power Supplies - External/Internal (Off-Board)           Rackage         -           Series         LEA           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         15A           Power (Watts)         75W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         77%           Operating Temperature         -20°C ~ 70°C (With Derating)           Features         PFC, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         LEA           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         15A           Power (Watts)         75W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         77%           Operating Temperature         -20°C ~ 70°C (With Derating)           Features         PFC, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	Manufacturer Part Number	LEA75F-5-S
Package         -           Series         LEA           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         15A           Power (Watts)         75W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         77%           Operating Temperature         -20°C ~ 70°C (With Derating)           Features         PFC, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	Manufacturer	Cosel USA, Inc.
Package         -           Series         LEA           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         15A           Power (Watts)         75W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         77%           Operating Temperature         -20°C ~ 70°C (With Derating)           Features         PFC, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         LEA           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         15A           Power (Watts)         75W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         77%           Operating Temperature         -20°C ~ 70°C (With Derating)           Features         PFC, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)		AC DC Converters
Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         15A           Power (Watts)         75W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         77%           Operating Temperature         -20°C ~ 70°C (With Derating)           Features         PFC, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	Package	-
Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         15A           Power (Watts)         75W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         77%           Operating Temperature         -20°C ~ 70°C (With Derating)           Features         PFC, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	Series	LEA
Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         15A           Power (Watts)         75W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         77%           Operating Temperature         -20°C ~ 70°C (With Derating)           Features         PFC, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	Туре	Open Frame
Voltage - Output 2  Voltage - Output 3  Voltage - Output 4  Current - Output (Max)  Applications  Voltage - Isolation  Size / Dimension  5V  Voltage - Output 4  -  Current - Output (Max)  15A  Power (Watts)  75W  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  77%  Operating Temperature  -20°C ~ 70°C (With Derating)  Features  PFC, Universal Input  Kounting Type  Size / Dimension  5V  Chassis Mount  8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation Site (3000V) Efficiency Operating Temperature Features PFC, Universal Input Mounting Type Size / Dimension  - Output (Max) - Current - Output (Max)	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  77%  Operating Temperature  -20°C ~ 70°C (With Derating)  Features  PFC, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  - Output (Max)  - Chassis Mount  8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	Voltage - Output 1	5V
Voltage - Output 4  Current - Output (Max)  15A  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  77%  Operating Temperature  -20°C ~ 70°C (With Derating)  Features  PFC, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  -20°C ~ 11 W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	Voltage - Output 2	-
Current - Output (Max)  Power (Watts)  75W  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  77%  Operating Temperature  -20°C ~ 70°C (With Derating)  Features  PFC, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  15A  75W  Commercial)  76W  77%  77%  Commercial)  77%  78  79%  Chassis Mount  8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	Voltage - Output 3	-
Power (Watts) 75W  Applications ITE (Commercial)  Voltage - Isolation 3kV (3000V)  Efficiency 77%  Operating Temperature -20°C ~ 70°C (With Derating)  Features PFC, Universal Input  Mounting Type Chassis Mount  Size / Dimension 8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	Voltage - Output 4	-
ApplicationsITE (Commercial)Voltage - Isolation $3kV (3000V)$ Efficiency $77\%$ Operating Temperature $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)FeaturesPFC, Universal InputMounting TypeChassis MountSize / Dimension $8.74$ " L x $2.17$ " W x $1.14$ " H ( $222.0$ mm x $55.0$ mm x $29.0$ mm)	Current - Output (Max)	15A
Voltage - Isolation 3kV (3000V)  Efficiency 77%  Operating Temperature -20°C ~ 70°C (With Derating)  Features PFC, Universal Input  Mounting Type Chassis Mount  Size / Dimension 8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	Power (Watts)	75W
Efficiency 77%  Operating Temperature -20°C ~ 70°C (With Derating)  Features PFC, Universal Input  Mounting Type Chassis Mount  Size / Dimension 8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	Applications	ITE (Commercial)
Operating Temperature  -20°C ~ 70°C (With Derating)  PFC, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  -20°C ~ 70°C (With Derating)  PFC, Universal Input  Chassis Mount  8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	Voltage - Isolation	3kV (3000V)
Features PFC, Universal Input  Mounting Type Chassis Mount  Size / Dimension 8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	Efficiency	77%
Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	Operating Temperature	-20°C ~ 70°C (With Derating)
Size / Dimension 8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)	Features	PFC, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	8.74" L x 2.17" W x 1.14" H (222.0mm x 55.0mm x 29.0mm)
		Report errors?

#### **LEA75F-5-S Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **LEA75F-5-S Payment Methods**



















### **LEA75F-5-S Shipping Methods**













If you have any question about LEA75F-5-S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com