



### **LEBRP-02V-S Information**



For Reference Only

Part Number LEBRP-02V-S

Manufacturer JST Sales America Inc.

Category Connectors, Interconnects
Solid State Lighting Connectors

**Description** CONN SSL PLUG HSG 2POS CRIMP

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **LEBRP-02V-S Specifications**

| Manufacturer Part Number       LEBRP-02V-S         Manufacturer       JST Sales America Inc.         Category       Connectors, Interconnects         Solid State Lighting Connectors         Package       -         Series       LEB         Style       Board to Cable/Wire         Connector Type       Plug Housing for Tab Contact         Number of Positions       2         Mounting Type       Free Hanging (In-Line)         Termination       Crimp         Pitch       -         Fastening Type       -         Features       -         Housing Color       Natural         Wire Gauge       -         Contact Material       -         Contact Finish       -         Housing Material       Polybutylene Terephthalate (PBT)         Operating Temperature       -55°C ~ 105°C         Report errors? |                          |                                  |
|---|--------------------------|----------------------------------|
| CategoryConnectors, InterconnectsPackage-SeriesLEBStyleBoard to Cable/WireConnector TypePlug Housing for Tab ContactNumber of Positions2Mounting TypeFree Hanging (In-Line)TerminationCrimpPitch-Fastening Type-Features-Housing ColorNaturalWire Gauge-Contact Material-Contact Finish-Housing MaterialPolybutylene Terephthalate (PBT)Operating Temperature-55°C ~ 105°C  | Manufacturer Part Number | LEBRP-02V-S                      |
| Package-SeriesLEBStyleBoard to Cable/WireConnector TypePlug Housing for Tab ContactNumber of Positions2Mounting TypeFree Hanging (In-Line)TerminationCrimpPitch-Fastening Type-Features-Housing ColorNaturalWire Gauge-Contact Material-Contact Finish-Housing MaterialPolybutylene Terephthalate (PBT)Operating Temperature-55°C ~ 105°C   | Manufacturer             | JST Sales America Inc.           |
| Package-SeriesLEBStyleBoard to Cable/WireConnector TypePlug Housing for Tab ContactNumber of Positions2Mounting TypeFree Hanging (In-Line)TerminationCrimpPitch-Fastening Type-Features-Housing ColorNaturalWire Gauge-Contact Material-Contact Finish-Housing MaterialPolybutylene Terephthalate (PBT)Operating Temperature-55°C ~ 105°C   | Category                 | Connectors, Interconnects        |
| SeriesLEBStyleBoard to Cable/WireConnector TypePlug Housing for Tab ContactNumber of Positions2Mounting TypeFree Hanging (In-Line)TerminationCrimpPitch-Fastening Type-Features-Housing ColorNaturalWire Gauge-Contact Material-Contact Finish-Housing MaterialPolybutylene Terephthalate (PBT)Operating Temperature-55°C ~ 105°C   |                          | Solid State Lighting Connectors  |
| StyleBoard to Cable/WireConnector TypePlug Housing for Tab ContactNumber of Positions2Mounting TypeFree Hanging (In-Line)TerminationCrimpPitch-Fastening Type-Features-Housing ColorNaturalWire Gauge-Contact Material-Contact Finish-Housing MaterialPolybutylene Terephthalate (PBT)Operating Temperature-55°C ~ 105°C  | Package                  | -                                |
| Connector Type Plug Housing for Tab Contact  Number of Positions 2  Mounting Type Free Hanging (In-Line)  Termination Crimp  Pitch - Fastening Type - Features - Housing Color Natural  Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT) Operating Temperature -  Plug Housing for Tab Contact  Analog Contact  Number of Positions 2  Natural  Polybutylene Terephthalate (PBT) -55°C ~ 105°C  | Series                   | LEB                              |
| Number of Positions2Mounting TypeFree Hanging (In-Line)TerminationCrimpPitch-Fastening Type-Features-Housing ColorNaturalWire Gauge-Contact Material-Contact Finish-Housing MaterialPolybutylene Terephthalate (PBT)Operating Temperature-55°C ~ 105°C  | Style                    | Board to Cable/Wire              |
| Mounting TypeFree Hanging (In-Line)TerminationCrimpPitch-Fastening Type-Features-Housing ColorNaturalWire Gauge-Contact Material-Contact Finish-Housing MaterialPolybutylene Terephthalate (PBT)Operating Temperature-55°C ~ 105°C  | Connector Type           | Plug Housing for Tab Contact     |
| Termination Crimp  Pitch - Fastening Type - Features - Housing Color Natural  Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT) Operating Temperature -  Crimp  - Crimp  - Crimp  - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT)  | Number of Positions      | 2                                |
| Pitch - Fastening Type - Features - Housing Color Natural Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT) Operating Temperature55°C ~ 105°C  | Mounting Type            | Free Hanging (In-Line)           |
| Fastening Type - Features - Housing Color Natural Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT) Operating Temperature -55°C ~ 105°C  | Termination              | Crimp                            |
| Features - Housing Color Natural Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT) Operating Temperature -55°C ~ 105°C   | Pitch                    | -                                |
| Housing Color  Wire Gauge  Contact Material  Contact Finish  Housing Material  Polybutylene Terephthalate (PBT)  Operating Temperature  -55°C ~ 105°C   | Fastening Type           | -                                |
| Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT) Operating Temperature -55°C ~ 105°C  | Features                 | -                                |
| Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT) Operating Temperature -55°C ~ 105°C   | Housing Color            | Natural                          |
| Contact Finish-Housing MaterialPolybutylene Terephthalate (PBT)Operating Temperature $-55^{\circ}$ C $\sim 105^{\circ}$ C   | Wire Gauge               | -                                |
| Housing Material Polybutylene Terephthalate (PBT)  Operating Temperature $-55^{\circ}\text{C} \sim 105^{\circ}\text{C}$   | Contact Material         | -                                |
| Operating Temperature $-55^{\circ}\text{C} \sim 105^{\circ}\text{C}$  | Contact Finish           | -                                |
|   | Housing Material         | Polybutylene Terephthalate (PBT) |
| Report errors?  | Operating Temperature    | -55°C ~ 105°C                    |
|   |                          | Report errors?                   |

#### **LEBRP-02V-S Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **LEBRP-02V-S Payment Methods**



















## **LEBRP-02V-S Shipping Methods**













If you have any question about LEBRP-02V-S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com