



LED50W-060-C0830 Information



For Reference Only

Part Number LED50W-060-C0830

Manufacturer Thomas Research Products

Category Power Supplies - External/Internal (Off-Board)

LED Drivers

Description LED DRIVER CC AC/DC 20-60V 830MA

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LED50W-060-C0830 Specifications

Manufacturer Part Number LED50W-060-C0830 Manufacturer Thomas Research Products Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series LED-50W Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 20 ~ 60 V Current - Output (Max) 830mA Power (Watts) 50W Voltage - Isolation - Dimming - Features OCP, OVP, SCP Ratings IP66 Operating Temperature -30°C ~ 60°C Efficiency 88% Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)		
Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series LED-50W Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 20 ~ 60 V Current - Output (Max) 830mA Power (Watts) 50W Voltage - Isolation - Dimming - Features OCP, OVP, SCP Ratings IP66 Operating Temperature -30°C ~ 60°C Efficiency 88% Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	Manufacturer Part Number	LED50W-060-C0830
LED Drivers Package - Series LED-50W Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 20 ~ 60 V Current - Output (Max) 830mA Power (Watts) 50W Voltage - Isolation - Dimming - Features OCP, OVP, SCP Ratings IP66 Operating Temperature -30°C ~ 60°C Efficiency 88% Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	Manufacturer	Thomas Research Products
Package - Series LED-50W Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 20 ~ 60 V Current - Output (Max) 830mA Power (Watts) 50W Voltage - Isolation - Dimming - Features OCP, OVP, SCP Ratings IP66 Operating Temperature -30°C ~ 60°C Efficiency 88% Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series LED-50W Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90V AC Voltage - Input (Max) 305V AC Voltage - Output 20 ~ 60 V Current - Output (Max) 830m A Power (Watts) 50W Voltage - Isolation - Dimming - Features OCP, OVP, SCP Ratings IP66 Operating Temperature -30°C ~ 60°C Efficiency 88% Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)		LED Drivers
Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 20 ~ 60 V Current - Output (Max) 830mA Power (Watts) 50W Voltage - Isolation - Dimming - Features OCP, OVP, SCP Ratings IP66 Operating Temperature -30°C ~ 60°C Efficiency 88% Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	Package	-
Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 20 ~ 60 V Current - Output (Max) 830mA Power (Watts) 50W Voltage - Isolation - Dimming - Features OCP, OVP, SCP Ratings IP66 Operating Temperature -30°C ~ 60°C Efficiency 88% Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	Series	LED-50W
Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 20 ~ 60 V Current - Output (Max) 830mA Power (Watts) 50W Voltage - Isolation - Dimming - Features OCP, OVP, SCP Ratings IP66 Operating Temperature -30°C ~ 60°C Efficiency 88% Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	Туре	Constant Current
Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 20 ~ 60 V Current - Output (Max) 830mA Power (Watts) 50W Voltage - Isolation - Dimming - Features OCP, OVP, SCP Ratings IP66 Operating Temperature -30°C ~ 60°C Efficiency 88% Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	Topology	AC DC Converter
Voltage - Input (Max) 305VAC Voltage - Output 20 ~ 60 V Current - Output (Max) 830mA Power (Watts) 50W Voltage - Isolation - Dimming - Features OCP, OVP, SCP Ratings IP66 Operating Temperature -30°C ~ 60°C Efficiency 88% Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	Number of Outputs	1
Voltage - Output 20 ~ 60 V Current - Output (Max) 830mA Power (Watts) 50W Voltage - Isolation - Dimming - Features OCP, OVP, SCP Ratings IP66 Operating Temperature -30°C ~ 60°C Efficiency 88% Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	Voltage - Input (Min)	90VAC
Current - Output (Max) 830mA Power (Watts) 50W Voltage - Isolation - Dimming - Features OCP, OVP, SCP Ratings IP66 Operating Temperature -30°C ~ 60°C Efficiency 88% Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	Voltage - Input (Max)	305VAC
Power (Watts) 50W Voltage - Isolation - Dimming - Features OCP, OVP, SCP Ratings IP66 Operating Temperature -30°C ~ 60°C Efficiency 88% Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	Voltage - Output	20 ~ 60 V
Voltage - Isolation Dimming - Features OCP, OVP, SCP Ratings IP66 Operating Temperature -30°C ~ 60°C Efficiency 88% Termination Style Wire Leads Size / Dimension - OCP, OVP, SCP Wx 0.98" H (194.0mm x 43.0mm x 25.0mm)	Current - Output (Max)	830mA
Dimming Features OCP, OVP, SCP Ratings IP66 Operating Temperature -30°C ~ 60°C Efficiency 88% Termination Style Wire Leads Size / Dimension	Power (Watts)	50W
Features OCP, OVP, SCP Ratings IP66 Operating Temperature -30°C ~ 60°C Efficiency 88% Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	Voltage - Isolation	-
Ratings IP66 Operating Temperature -30°C ~ 60°C Efficiency 88% Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	Dimming	-
Operating Temperature -30°C ~ 60°C Efficiency 88% Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	Features	OCP, OVP, SCP
Efficiency 88% Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	Ratings	IP66
Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	Operating Temperature	-30°C ~ 60°C
Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	Efficiency	88%
· · · · · · · · · · · · · · · · · · ·	Termination Style	Wire Leads
Report errors?	Size / Dimension	7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)
		Report errors?

LED50W-060-C0830 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LED50W-060-C0830 Payment Methods



















LED50W-060-C0830 Shipping Methods













If you have any question about LED50W-060-C0830, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com