



LED50W-072-C0700 Information



For Reference Only

Part Number LED50W-072-C0700

Manufacturer Thomas Research Products

Category Power Supplies - External/Internal (Off-Board)

LED Drivers

Description LED DRIVER CC AC/DC 24-72V 700MA

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LED50W-072-C0700 Specifications

Manufacturer Part Number LED50W-072-C0700 Manufacturer Thomas Research Products Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series LED-50W Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 24 ~ 72 V Current - Output (Max) 700mA Power (Watts) 50W Voltage - Isolation - Dimming - Features OCP, OVP, SCP Ratings IP66 Operating Temperature -30°C ~ 65°C Efficiency 88% Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)			
Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series LED-50W Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 24 ~ 72 V Current - Output (Max) 700mA Power (Watts) 50W Voltage - Isolation - Dimming - Features OCP, OVP, SCP Ratings IP66 Operating Temperature -30°C ~ 65°C Efficiency 88% Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	Manufacturer Part Number	LED50W-072-C0700	
LED Drivers Package - Series LED-50W Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 24 ~ 72 V Current - Output (Max) 700mA Power (Watts) 50W Voltage - Isolation - Dimming - Features OCP, OVP, SCP Ratings IP66 Operating Temperature -30°C ~ 65°C Efficiency 88% Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	Manufacturer	Thomas Research Products	
Package - Series LED-50W Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 24 ~ 72 V Current - Output (Max) 700mA Power (Watts) 50W Voltage - Isolation - Dimming - Features OCP, OVP, SCP Ratings IP66 Operating Temperature -30°C ~ 65°C Efficiency 88% Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series LED-50W Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 24 ~ 72 V Current - Output (Max) 700mA Power (Watts) 50W Voltage - Isolation - Dimming - Features OCP, OVP, SCP Ratings IP66 Operating Temperature -30°C ~ 65°C Efficiency 88% Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)		LED Drivers	
Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 24 ~ 72 V Current - Output (Max) 700mA Power (Watts) 50W Voltage - Isolation - Dimming - Features OCP, OVP, SCP Ratings IP66 Operating Temperature -30°C ~ 65°C Efficiency 88% Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	Package	-	
Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 24 ~ 72 V Current - Output (Max) 700mA Power (Watts) 50W Voltage - Isolation - Dimming - Features OCP, OVP, SCP Ratings IP66 Operating Temperature -30°C ~ 65°C Efficiency 88% Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	Series	LED-50W	
Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 24 ~ 72 V Current - Output (Max) 700mA Power (Watts) 50W Voltage - Isolation - Dimming - Features OCP, OVP, SCP Ratings IP66 Operating Temperature -30°C ~ 65°C Efficiency 88% Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	Туре	Constant Current	
Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 24 ~ 72 V Current - Output (Max) 700mA Power (Watts) 50W Voltage - Isolation - Dimming - Features OCP, OVP, SCP Ratings IP66 Operating Temperature -30°C ~ 65°C Efficiency 88% Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	Topology	AC DC Converter	
Voltage - Input (Max) 305VAC Voltage - Output $24 \sim 72 \text{ V}$ Current - Output (Max) 700mA Power (Watts) 50W Voltage - Isolation-Dimming-Features OCP , OVP , SCP Ratings $IP66$ Operating Temperature $-30^{\circ}\text{C} \sim 65^{\circ}\text{C}$ Efficiency 88% Termination StyleWire LeadsSize / Dimension $7.64^{\circ}\text{L} \times 1.69^{\circ}\text{W} \times 0.98^{\circ}\text{H} (194.0 \text{mm} \times 43.0 \text{mm} \times 25.0 \text{mm})$	Number of Outputs	1	
Voltage - Output 24 ~ 72 V Current - Output (Max) 700mA Power (Watts) 50W Voltage - Isolation - Dimming - Features OCP, OVP, SCP Ratings IP66 Operating Temperature -30°C ~ 65°C Efficiency 88% Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	Voltage - Input (Min)	90VAC	
Current - Output (Max) 700mA Power (Watts) 50W Voltage - Isolation - Dimming - Features OCP, OVP, SCP Ratings IP66 Operating Temperature -30°C ~ 65°C Efficiency 88% Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	Voltage - Input (Max)	305VAC	
Power (Watts) 50W Voltage - Isolation - Dimming - Features OCP, OVP, SCP Ratings IP66 Operating Temperature -30°C ~ 65°C Efficiency 88% Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	Voltage - Output	24 ~ 72 V	
Voltage - Isolation Dimming - Features OCP, OVP, SCP Ratings IP66 Operating Temperature -30°C ~ 65°C Efficiency 88% Termination Style Wire Leads Size / Dimension - OCP, OVP, SCP W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	Current - Output (Max)	700mA	
Dimming - Features OCP, OVP, SCP Ratings IP66 Operating Temperature -30°C ~ 65°C Efficiency 88% Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	Power (Watts)	50W	
Features OCP, OVP, SCP Ratings IP66 Operating Temperature -30°C ~ 65°C Efficiency 88% Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	Voltage - Isolation	-	
Ratings IP66 Operating Temperature $-30^{\circ}\text{C} \sim 65^{\circ}\text{C}$ Efficiency 88% Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	Dimming	-	
Operating Temperature -30°C ~ 65°C Efficiency 88% Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	Features	OCP, OVP, SCP	
Efficiency 88% Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	Ratings	IP66	
Termination Style Wire Leads Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	Operating Temperature	-30°C ~ 65°C	
Size / Dimension 7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	Efficiency	88%	
	Termination Style	Wire Leads	
Report errors?	Size / Dimension	7.64" L x 1.69" W x 0.98" H (194.0mm x 43.0mm x 25.0mm)	
			Report errors?

LED50W-072-C0700 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LED50W-072-C0700 Payment Methods



















LED50W-072-C0700 Shipping Methods













If you have any question about LED50W-072-C0700, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com