



LEV100A6ANG Information



For Reference Only

Part Number LEV100A6ANG

Manufacturer TE Connectivity Aerospace, Defense and Marine

Category Relays

Power Relays, Over 2 Amps

Description RELAY CONTACTOR SPST 100A 48V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LEV100A6ANG Specifications

Manufacturer Part Number LEV100A6ANG Manufacturer TE Connectivity Aerospace, Defense and Marine Category Relays Power Relays, Over 2 Amps Package - Series LEV100, KILOVAC Relay Type Contactor Coil Type Non Latching Coil Current 122mA Coil Voltage 48VDC Contact Form SPST-NO (1 Form X) Contact Rating (Current) 100A Switching Voltage 900VDC - Max Turn On Voltage (Max) 33 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 25ms Release Time 10ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Stud		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesLEV100, KILOVACRelay TypeContactorCoil TypeNon LatchingCoil Current122mACoil Voltage48VDCContact FormSPST-NO (1 Form X)Contact Rating (Current)100ASwitching Voltage900VDC - MaxTurn On Voltage (Max)33 VDCTurn Off Voltage (Min)4.8 VDCOperate Time25msRelease Time10msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleStud	Manufacturer Part Number	LEV100A6ANG
Package-SeriesLEV100, KILOVACRelay TypeContactorCoil TypeNon LatchingCoil Current122mACoil Voltage48VDCContact FormSPST-NO (1 Form X)Contact Rating (Current)100ASwitching Voltage900VDC - MaxTurn On Voltage (Max)33 VDCTurn Off Voltage (Min)4.8 VDCOperate Time25msRelease Time10msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleStud	Manufacturer	TE Connectivity Aerospace, Defense and Marine
Package - Series LEV100, KILOVAC Relay Type Contactor Coil Type Non Latching Coil Current 122mA Coil Voltage 48VDC Contact Form SPST-NO (1 Form X) Contact Rating (Current) 100A Switching Voltage 900VDC - Max Turn On Voltage (Max) 33 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 25ms Release Time 10ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Stud	Category	Relays
SeriesLEV100, KILOVACRelay TypeContactorCoil TypeNon LatchingCoil Current122mACoil Voltage48VDCContact FormSPST-NO (1 Form X)Contact Rating (Current)100ASwitching Voltage900VDC - MaxTurn On Voltage (Max)33 VDCTurn Off Voltage (Min)4.8 VDCOperate Time25msRelease Time10msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleStud		Power Relays, Over 2 Amps
Relay TypeContactorCoil TypeNon LatchingCoil Current12mACoil Voltage48VDCContact FormSPST-NO (1 Form X)Contact Rating (Current)100ASwitching Voltage900VDC - MaxTurn On Voltage (Max)33 VDCTurn Off Voltage (Min)4.8 VDCOperate Time25msRelease Time10msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleStud	Package	-
Coil TypeNon LatchingCoil Current122mACoil Voltage48VDCContact FormSPST-NO (1 Form X)Contact Rating (Current)100ASwitching Voltage900VDC - MaxTurn On Voltage (Max)33 VDCTurn Off Voltage (Min)4.8 VDCOperate Time25msRelease Time10msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleStud	Series	LEV100, KILOVAC
Coil Current122mACoil Voltage48VDCContact FormSPST-NO (1 Form X)Contact Rating (Current)100ASwitching Voltage900VDC - MaxTurn On Voltage (Max)33 VDCTurn Off Voltage (Min)4.8 VDCOperate Time25msRelease Time10msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleStud	Relay Type	Contactor
Coil Voltage 48VDC Contact Form SPST-NO (1 Form X) Contact Rating (Current) 100A Switching Voltage 900VDC - Max Turn On Voltage (Max) 33 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 25ms Release Time 10ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Stud	Coil Type	Non Latching
Contact Form SPST-NO (1 Form X) Contact Rating (Current) 100A Switching Voltage 900VDC - Max Turn On Voltage (Max) 33 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 25ms Release Time 10ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Stud	Coil Current	122mA
Contact Rating (Current) Switching Voltage 900VDC - Max 33 VDC Turn On Voltage (Max) 4.8 VDC Operate Time 25ms Release Time 10ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style	Coil Voltage	48VDC
Switching Voltage 900VDC - Max Turn On Voltage (Max) 33 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 25ms Release Time 10ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Stud	Contact Form	SPST-NO (1 Form X)
Turn On Voltage (Max) Turn Off Voltage (Min) 4.8 VDC Operate Time 25ms Release Time 10ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Stud	Contact Rating (Current)	100A
Turn Off Voltage (Min) 4.8 VDC Operate Time 25ms Release Time 10ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Stud	Switching Voltage	900VDC - Max
Operate Time25msRelease Time10msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleStud	Turn On Voltage (Max)	33 VDC
Release Time 10ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Stud	Turn Off Voltage (Min)	4.8 VDC
Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Stud	Operate Time	25ms
Mounting Type Chassis Mount Termination Style Stud	Release Time	10ms
Termination Style Stud	Features	Sealed - Hermetically
	Mounting Type	Chassis Mount
Report errors?	Termination Style	Stud
		Report errors?

LEV100A6ANG Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LEV100A6ANG Payment Methods



















LEV100A6ANG Shipping Methods













If you have any question about LEV100A6ANG, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com