



LEV200A4ANA Information



For Reference Only

Part Number LEV200A4ANA

Manufacturer TE Connectivity Aerospace, Defense and Marine

Category Relays

Power Relays, Over 2 Amps

Description RELAY CONTACTOR SPST 500A 12V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LEV200A4ANA Specifications

Manufacturer Part Number Manufacturer TE Connectivity Aerospace, Defense and Marine Category Relays Power Relays, Over 2 Amps Package Series LEV200, KILOVAC Relay Type Contactor Coil Type Non Latching Coil Current 1.1A Coil Voltage 12VDC Contact Form SPST-NO (1 Form X) Contact Rating (Current) Switching Voltage 900VDC - Max Turn On Voltage (Max) 9 VDC Operate Time 25ms		
Category Relays Power Relays, Over 2 Amps Package - Series LEV200, KILOVAC Relay Type Contactor Coil Type Non Latching Coil Current 1.1A Coil Voltage 12VDC Contact Form SPST-NO (1 Form X) Contact Rating (Current) 500A Switching Voltage 900VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 2 VDC Operate Time 25ms	Manufacturer Part Number	LEV200A4ANA
Package - Series LEV200, KILOVAC Relay Type Contactor Coil Type Non Latching Coil Current 1.1A Coil Voltage 12VDC Contact Form SPST-NO (1 Form X) Contact Rating (Current) 500A Switching Voltage 900VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 2 VDC Operate Time 25ms	Manufacturer	TE Connectivity Aerospace, Defense and Marine
Package - LEV200, KILOVAC Relay Type Contactor Coil Type Non Latching Coil Current 1.1A Coil Voltage 12VDC Contact Form SPST-NO (1 Form X) Contact Rating (Current) 500A Switching Voltage 900VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 2 VDC Operate Time 25ms	Category	Relays
Series LEV200, KILOVAC Relay Type Contactor Coil Type Non Latching Coil Current 1.1A Coil Voltage 12VDC Contact Form SPST-NO (1 Form X) Contact Rating (Current) 500A Switching Voltage 900VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 2 VDC Operate Time 25ms		Power Relays, Over 2 Amps
Relay TypeContactorCoil TypeNon LatchingCoil Current1.1ACoil Voltage12VDCContact FormSPST-NO (1 Form X)Contact Rating (Current)500ASwitching Voltage900VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)2 VDCOperate Time25ms	Package	-
Coil Type Non Latching Coil Current 1.1A Coil Voltage 12VDC Contact Form SPST-NO (1 Form X) Contact Rating (Current) 500A Switching Voltage 900VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 2 VDC Operate Time 25ms	Series	LEV200, KILOVAC
Coil Current 1.1A Coil Voltage 12VDC Contact Form SPST-NO (1 Form X) Contact Rating (Current) 500A Switching Voltage 900VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 2 VDC Operate Time 25ms	Relay Type	Contactor
Coil Voltage 12VDC Contact Form SPST-NO (1 Form X) Contact Rating (Current) 500A Switching Voltage 900VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 2 VDC Operate Time 25ms	Coil Type	Non Latching
Contact Form SPST-NO (1 Form X) Contact Rating (Current) 500A Switching Voltage 900VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 2 VDC Operate Time 25ms	Coil Current	1.1A
Contact Rating (Current) 500A Switching Voltage 900VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 2 VDC Operate Time 25ms	Coil Voltage	12VDC
Switching Voltage 900VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 2 VDC Operate Time 25ms	Contact Form	SPST-NO (1 Form X)
Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 2 VDC Operate Time 25ms	Contact Rating (Current)	500A
Turn Off Voltage (Min) 2 VDC Operate Time 25ms	Switching Voltage	900VDC - Max
Operate Time 25ms	Turn On Voltage (Max)	9 VDC
	Turn Off Voltage (Min)	2 VDC
D. 1. (12)	Operate Time	25ms
Release Time 12ms	Release Time	12ms
Features Sealed - Hermetically	Features	Sealed - Hermetically
Mounting Type Chassis Mount	Mounting Type	Chassis Mount
Termination Style Stud, Wire Leads	Termination Style	Stud, Wire Leads
Report errors?		Report errors?

LEV200A4ANA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LEV200A4ANA Payment Methods



















LEV200A4ANA Shipping Methods













If you have any question about LEV200A4ANA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com