



LEV200A5ANA Information



For Reference Only

Part Number LEV200A5ANA

Manufacturer TE Connectivity Aerospace, Defense and Marine

Category Relays

Power Relays, Over 2 Amps

Description RELAY CONTACTOR SPST 500A 24V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LEV200A5ANA Specifications

Manufacturer Part Number LEV200A5ANA Manufacturer TE Connectivity Aerospace, Defense and Marine Category Relays Power Relays, Over 2 Amps Package - Series LEV200, KILOVAC Relay Type Contactor Coil Type Non Latching Coil Current 600mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form X) Contact Rating (Current) 500A Switching Voltage 900VDC - Max Turn On Voltage (Max) 19 VDC Turn Off Voltage (Min) 5 VDC Operate Time 25ms Release Time 12ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Stud, Wire Leads		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesLEV200, KILOVACRelay TypeContactorCoil TypeNon LatchingCoil Current600mACoil Voltage24VDCContact FormSPST-NO (1 Form X)Contact Rating (Current)500ASwitching Voltage900VDC - MaxTurn On Voltage (Max)19 VDCTurn Off Voltage (Min)5 VDCOperate Time25msRelease Time12msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleStud, Wire Leads	Manufacturer Part Number	LEV200A5ANA
Package-SeriesLEV200, KILOVACRelay TypeContactorCoil TypeNon LatchingCoil Current600mACoil Voltage24VDCContact FormSPST-NO (1 Form X)Contact Rating (Current)500ASwitching Voltage900VDC - MaxTurn On Voltage (Max)19 VDCTurn Off Voltage (Min)5 VDCOperate Time25msRelease Time12msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleStud, Wire Leads	Manufacturer	TE Connectivity Aerospace, Defense and Marine
Package - Series LEV200, KILOVAC Relay Type Contactor Coil Type Non Latching Coil Current 600mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form X) Contact Rating (Current) 500A Switching Voltage 900VDC - Max Turn On Voltage (Max) 19 VDC Turn Off Voltage (Min) 5 VDC Operate Time 25ms Release Time 12ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Stud, Wire Leads	Category	Relays
SeriesLEV200, KILOVACRelay TypeContactorCoil TypeNon LatchingCoil Current600mACoil Voltage24VDCContact FormSPST-NO (1 Form X)Contact Rating (Current)500ASwitching Voltage900VDC - MaxTurn On Voltage (Max)19 VDCTurn Off Voltage (Min)5 VDCOperate Time25msRelease Time12msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleStud, Wire Leads		Power Relays, Over 2 Amps
Relay TypeContactorCoil TypeNon LatchingCoil Current600mACoil Voltage24VDCContact FormSPST-NO (1 Form X)Contact Rating (Current)500ASwitching Voltage900VDC - MaxTurn On Voltage (Max)19 VDCTurn Off Voltage (Min)5 VDCOperate Time25msRelease Time12msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleStud, Wire Leads	Package	-
Coil Type Non Latching Coil Current 600mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form X) Contact Rating (Current) 500A Switching Voltage 900VDC - Max Turn On Voltage (Max) 19 VDC Turn Off Voltage (Min) 5 VDC Operate Time 25ms Release Time 12ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Stud, Wire Leads	Series	LEV200, KILOVAC
Coil Current600mACoil Voltage24VDCContact FormSPST-NO (1 Form X)Contact Rating (Current)500ASwitching Voltage900VDC - MaxTurn On Voltage (Max)19 VDCTurn Off Voltage (Min)5 VDCOperate Time25msRelease Time12msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleStud, Wire Leads	Relay Type	Contactor
Coil Voltage 24VDC Contact Form SPST-NO (1 Form X) Contact Rating (Current) 500A Switching Voltage 900VDC - Max Turn On Voltage (Max) 19 VDC Turn Off Voltage (Min) 5 VDC Operate Time 25ms Release Time 12ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Stud, Wire Leads	Coil Type	Non Latching
Contact Form SPST-NO (1 Form X) Contact Rating (Current) 500A Switching Voltage 900VDC - Max Turn On Voltage (Max) 19 VDC Turn Off Voltage (Min) 5 VDC Operate Time 25ms Release Time 12ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Stud, Wire Leads	Coil Current	600mA
Contact Rating (Current) Switching Voltage 900VDC - Max 19 VDC Turn On Voltage (Max) 5 VDC Operate Time 25ms Release Time 12ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Stud, Wire Leads	Coil Voltage	24VDC
Switching Voltage 900VDC - Max Turn On Voltage (Max) 19 VDC Turn Off Voltage (Min) 5 VDC Operate Time 25ms Release Time 12ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Stud, Wire Leads	Contact Form	SPST-NO (1 Form X)
Turn On Voltage (Max) 19 VDC Turn Off Voltage (Min) 5 VDC Operate Time 25ms Release Time 12ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Stud, Wire Leads	Contact Rating (Current)	500A
Turn Off Voltage (Min) 5 VDC Operate Time 25ms Release Time 12ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Stud, Wire Leads	Switching Voltage	900VDC - Max
Operate Time25msRelease Time12msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleStud, Wire Leads	Turn On Voltage (Max)	19 VDC
Release Time 12ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Stud, Wire Leads	Turn Off Voltage (Min)	5 VDC
Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Stud, Wire Leads	Operate Time	25ms
Mounting Type Chassis Mount Termination Style Stud, Wire Leads	Release Time	12ms
Termination Style Stud, Wire Leads	Features	Sealed - Hermetically
·	Mounting Type	Chassis Mount
Report errors?	Termination Style	Stud, Wire Leads
		Report errors?

LEV200A5ANA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LEV200A5ANA Payment Methods





















LEV200A5ANA Shipping Methods













If you have any question about LEV200A5ANA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com