



## **LEV200HOANA01 Information**

Heisener.com

Part Number LEV200HOANA01

Manufacturer TE Connectivity Aerospace, Defense and Marine

Category

Power Relays, Over 2 Amps

**Description** RELAY CONTACTOR SPST 500A 115V

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **LEV200HOANA01 Specifications**

Manufacturer Part Number       LEV200HOANA01         Manufacturer       TE Connectivity Aerospace, Defense and Marine         Category       Relays         Package       -         Series       LEV200, KILOVAC         Relay Type       Contactor         Coil Type       Non Latching         Coil Current       -         Coil Voltage       115VAC         Contact Form       SPST-NO (1 Form X)         Contact Rating (Current)       500A         Switching Voltage       900VDC - Max         Turn On Voltage (Max)       -         Turn Off Voltage (Min)       -         Operate Time       25ms         Release Time       12ms         Features       Sealed - Hermetically         Mounting Type       Chassis Mount         Termination Style       Stud, Wire Leads		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesLEV200, KILOVACRelay TypeContactorCoil TypeNon LatchingCoil Current-Coil Voltage115VACContact FormSPST-NO (1 Form X)Contact Rating (Current)500ASwitching Voltage900VDC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time25msRelease Time12msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleStud, Wire Leads	Manufacturer Part Number	LEV200HOANA01
Package-SeriesLEV200, KILOVACRelay TypeContactorCoil TypeNon LatchingCoil Current-Coil Voltage115VACContact FormSPST-NO (1 Form X)Contact Rating (Current)500ASwitching Voltage900VDC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time25msRelease Time12msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleStud, Wire Leads	Manufacturer	TE Connectivity Aerospace, Defense and Marine
Package-SeriesLEV200, KILOVACRelay TypeContactorCoil TypeNon LatchingCoil Current-Coil Voltage115VACContact FormSPST-NO (1 Form X)Contact Rating (Current)500ASwitching Voltage900VDC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time25msRelease Time12msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleStud, Wire Leads	Category	Relays
SeriesLEV200, KILOVACRelay TypeContactorCoil TypeNon LatchingCoil Current-Coil Voltage115VACContact FormSPST-NO (1 Form X)Contact Rating (Current)500ASwitching Voltage900VDC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time25msRelease Time12msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleStud, Wire Leads		Power Relays, Over 2 Amps
Relay TypeContactorCoil TypeNon LatchingCoil Current-Coil Voltage115 V A CContact FormSPST-NO (1 Form X)Contact Rating (Current)500 ASwitching Voltage900 V D C - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time25 msRelease Time12 msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleStud, Wire Leads	Package	-
Coil Type Non Latching Coil Current - Coil Voltage 115VAC Contact Form SPST-NO (1 Form X) Contact Rating (Current) 500A Switching Voltage 900VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time 25ms Release Time 12ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Stud, Wire Leads	Series	LEV200, KILOVAC
Coil Current Coil Voltage 115VAC Contact Form SPST-NO (1 Form X) Contact Rating (Current) 500A Switching Voltage 900VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time 25ms Release Time 12ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Stud, Wire Leads	Relay Type	Contactor
Coil Voltage 115VAC Contact Form SPST-NO (1 Form X) Contact Rating (Current) 500A Switching Voltage 900VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time 25ms Release Time 12ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Stud, Wire Leads	Coil Type	Non Latching
Contact Form SPST-NO (1 Form X)  Contact Rating (Current) 500A  Switching Voltage 900VDC - Max  Turn On Voltage (Max) -  Turn Off Voltage (Min) -  Operate Time 25ms  Release Time 12ms  Features Sealed - Hermetically  Mounting Type Chassis Mount  Termination Style Stud, Wire Leads	Coil Current	-
Contact Rating (Current)  Switching Voltage  900VDC - Max  Turn On Voltage (Max)  - Turn Off Voltage (Min)  Operate Time  25ms  Release Time  12ms  Features  Sealed - Hermetically  Mounting Type  Chassis Mount  Termination Style  Stud, Wire Leads	Coil Voltage	115VAC
Switching Voltage 900VDC - Max  Turn On Voltage (Max) -  Turn Off Voltage (Min) -  Operate Time 25ms  Release Time 12ms  Features Sealed - Hermetically  Mounting Type Chassis Mount  Termination Style Stud, Wire Leads	Contact Form	SPST-NO (1 Form X)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  25ms  Release Time  12ms  Features  Sealed - Hermetically  Mounting Type  Chassis Mount  Termination Style  Stud, Wire Leads	Contact Rating (Current)	500A
Turn Off Voltage (Min)  Operate Time  25ms  Release Time  12ms  Features  Sealed - Hermetically  Mounting Type  Chassis Mount  Termination Style  Stud, Wire Leads	Switching Voltage	900VDC - Max
Operate Time 25ms  Release Time 12ms  Features Sealed - Hermetically  Mounting Type Chassis Mount  Termination Style Stud, Wire Leads	Turn On Voltage (Max)	-
Release Time 12ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Stud, Wire Leads	Turn Off Voltage (Min)	-
Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Stud, Wire Leads	Operate Time	25ms
Mounting Type Chassis Mount Termination Style Stud, Wire Leads	Release Time	12ms
Termination Style Stud, Wire Leads	Features	Sealed - Hermetically
	Mounting Type	Chassis Mount
Doport orrors?	Termination Style	Stud, Wire Leads
Report errors?		Report errors?

### **LEV200HOANA01** Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **LEV200HOANA01** Payment Methods



















## **LEV200HOANA01 Shipping Methods**













If you have any question about LEV200HOANA01, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com