



LFA100F-12-CRY Information

Heisener.com

Part Number LFA100F-12-CRY Manufacturer Cosel USA, Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC PS (OPEN FRAME)

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LFA100F-12-CRY Specifications

Manufacturer Part Number LFA100F-12-CRY Manufacturer Cosel USA, Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series * Type - Number of Outputs - Voltage - Input - Voltage - Output 1 - Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) - Power (Watts) - Applications - Voltage - Isolation - Efficiency - Operating Temperature - Features - Mounting Type - Size / Dimension - Report errors?		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series * Type - Number of Outputs - Voltage - Input - Voltage - Output 1 - Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) - Power (Watts) - Applications - Voltage - Isolation - Efficiency - Operating Temperature - Features - Mounting Type - Size / Dimension -	Manufacturer Part Number	LFA100F-12-CRY
Package - Series * Type - Number of Outputs - Voltage - Input - Voltage - Output 1 - Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) - Power (Watts) - Applications - Voltage - Isolation - Efficiency - Operating Temperature - Features - Mounting Type - Size / Dimension -	Manufacturer	Cosel USA, Inc.
Package - Series * Type - Number of Outputs - Voltage - Input - Voltage - Output 1 - Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) - Power (Watts) - Applications - Voltage - Isolation - Efficiency - Operating Temperature - Features - Mounting Type - Size / Dimension -	Category	Power Supplies - External/Internal (Off-Board)
Series * Type - Number of Outputs - Voltage - Input - Voltage - Output 1 - Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) - Power (Watts) - Applications - Voltage - Isolation - Efficiency - Operating Temperature - Features - Mounting Type - Size / Dimension -		AC DC Converters
Type	Package	-
Number of Outputs-Voltage - Input-Voltage - Output 1-Voltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)-Power (Watts)-Applications-Voltage - Isolation-Efficiency-Operating Temperature-Features-Mounting Type-Size / Dimension-	Series	*
Voltage - Input-Voltage - Output 1-Voltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)-Power (Watts)-Applications-Voltage - Isolation-Efficiency-Operating Temperature-Features-Mounting Type-Size / Dimension-	Type	-
Voltage - Output 1-Voltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)-Power (Watts)-Applications-Voltage - Isolation-Efficiency-Operating Temperature-Features-Mounting Type-Size / Dimension-	Number of Outputs	-
Voltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)-Power (Watts)-Applications-Voltage - Isolation-Efficiency-Operating Temperature-Features-Mounting Type-Size / Dimension-	Voltage - Input	-
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications Voltage - Isolation Efficiency Operating Temperature Features Mounting Type Size / Dimension - Control of the problem of the probl	Voltage - Output 1	-
Voltage - Output 4 Current - Output (Max) - Power (Watts) - Applications - Voltage - Isolation - Efficiency - Operating Temperature - Features - Mounting Type - Size / Dimension	Voltage - Output 2	-
Current - Output (Max) - Power (Watts) - Applications - Voltage - Isolation - Efficiency - Operating Temperature - Features - Mounting Type - Size / Dimension -	Voltage - Output 3	-
Power (Watts) - Applications - Voltage - Isolation - Efficiency - Operating Temperature - Features - Mounting Type - Size / Dimension	Voltage - Output 4	-
Applications Voltage - Isolation Efficiency Operating Temperature Features Mounting Type Size / Dimension - - - - - - - - - - - - -	Current - Output (Max)	-
Voltage - Isolation-Efficiency-Operating Temperature-Features-Mounting Type-Size / Dimension-	Power (Watts)	-
Efficiency - Operating Temperature - Features - Mounting Type - Size / Dimension -	Applications	-
Operating Temperature - Features - Mounting Type - Size / Dimension -	Voltage - Isolation	-
Features - Mounting Type - Size / Dimension -	Efficiency	-
Mounting Type - Size / Dimension -	Operating Temperature	-
Size / Dimension -	Features	-
	Mounting Type	-
Report errors?	Size / Dimension	-
		Report errors?

LFA100F-12-CRY Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LFA100F-12-CRY Payment Methods



















LFA100F-12-CRY Shipping Methods













If you have any question about LFA100F-12-CRY, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com