



LFA100F-12-SN Information

Heisener.com

Part Number LFA100F-12-SN Manufacturer Cosel USA, Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 12V 100W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LFA100F-12-SN Specifications

Manufacturer Part Number LFA100F-12-SN Manufacturer Cosel USA, Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series * Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8.5A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation - Efficiency 84.5% Operating Temperature -10°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension - Report errors?		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series * Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8.5A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation - Efficiency 84.5% Operating Temperature -10°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension -	Manufacturer Part Number	LFA100F-12-SN
Package - Series * Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8.5A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation - Efficiency 84.5% Operating Temperature -10°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension -	Manufacturer	Cosel USA, Inc.
Package - Series * Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8.5A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation - Efficiency 84.5% Operating Temperature -10°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension -	Category	Power Supplies - External/Internal (Off-Board)
Series * Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8.5A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation - Efficiency 84.5% Operating Temperature -10°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension -		AC DC Converters
TypeEnclosedNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 112VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)8.5APower (Watts)100WApplicationsITE (Commercial)Voltage - Isolation-Efficiency84.5%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesUniversal InputMounting TypeChassis MountSize / Dimension-	Package	-
Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8.5A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation - Efficiency 84.5% Operating Temperature -10°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension -	Series	*
Voltage - Input85 ~ 264 VACVoltage - Output 112VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)8.5APower (Watts)100WApplicationsITE (Commercial)Voltage - Isolation-Efficiency84.5%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesUniversal InputMounting TypeChassis MountSize / Dimension-	Туре	Enclosed
Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Applications Voltage - Isolation Efficiency Operating Temperature Features Mounting Type Size / Dimension 12V 12V 12V 12V 12V 12V 12V 12	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency Operating Temperature Features Universal Input Mounting Type Size / Dimension - - Current - Output (Max) 8.5A - 100W 8.5A Power (Watts) ITE (Commercial) - Voltage - Isolation - Chassis Mount Chassis Mount - Chassis Mount - Chassis Mount	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency Operating Temperature Features Universal Input Mounting Type Size / Dimension - Commercial Chassis Mount - Chassis Mount	Voltage - Output 1	12V
Voltage - Output 4 Current - Output (Max) 8.5A Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency 84.5% Operating Temperature -10°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension - Current - Output (Max) - 8.5A 100W 8.5A 100W 6.5A 10	Voltage - Output 2	-
Current - Output (Max) 8.5A Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency 84.5% Operating Temperature -10°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension - 8.5A 8.5A 100W ITE (Commercial) - Commercial) - Commercial Commerci	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency 84.5% Operating Temperature -10°C ~ 70°C (With Derating) Features Mounting Type Chassis Mount Size / Dimension 100W 100W	Voltage - Output 4	-
Applications ITE (Commercial) Voltage - Isolation - Efficiency 84.5% Operating Temperature -10°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension -	Current - Output (Max)	8.5A
Voltage - Isolation-Efficiency84.5%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesUniversal InputMounting TypeChassis MountSize / Dimension-	Power (Watts)	100W
Efficiency 84.5% Operating Temperature -10°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension -	Applications	ITE (Commercial)
Operating Temperature -10°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension -	Voltage - Isolation	-
Features Universal Input Mounting Type Chassis Mount Size / Dimension -	Efficiency	84.5%
Mounting Type Chassis Mount Size / Dimension -	Operating Temperature	-10° C ~ 70° C (With Derating)
Size / Dimension -	Features	Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	-
		Report errors?

LFA100F-12-SN Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LFA100F-12-SN Payment Methods



















LFA100F-12-SN Shipping Methods













If you have any question about LFA100F-12-SN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com