

LFA150F-12 Information

Heisener.com

Part Number LFA150F-12 Manufacturer Cosel USA, Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 12V 150W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LFA150F-12 Specifications

Manufacturer Part Number LFA150F-12 Manufacturer Cosel USA, Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series * Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12.5A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation - Efficiency 85% Operating Temperature -10°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension - Report errors?	•	
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series * Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12.5A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation - Efficiency 85% Operating Temperature -10°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension -	Manufacturer Part Number	LFA150F-12
Package - Series * Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12.5A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation - Efficiency 85% Operating Temperature -10°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension -	Manufacturer	Cosel USA, Inc.
Package - Series * Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12.5A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation - Efficiency 85% Operating Temperature -10°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension -	Category	Power Supplies - External/Internal (Off-Board)
Series * Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12.5A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation - Efficiency 85% Operating Temperature -10°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension -		AC DC Converters
Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12.5A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation - Efficiency 85% Operating Temperature -10°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension -	Package	-
Number of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 112VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)12.5APower (Watts)150WApplicationsITE (Commercial)Voltage - Isolation-Efficiency85%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesUniversal InputMounting TypeChassis MountSize / Dimension-	Series	*
Voltage - Input85 ~ 264 VACVoltage - Output 112VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)12.5APower (Watts)150WApplicationsITE (Commercial)Voltage - Isolation-Efficiency85%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesUniversal InputMounting TypeChassis MountSize / Dimension-	Type	Open Frame
Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation Fefficiency 0perating Temperature -10°C ~ 70°C (With Derating) Features Mounting Type Chassis Mount Size / Dimension 12.5A - Current - Output (Max) 12.5A 15.0W 17E (Commercial) - Commercial) Voltage - Isolation - Chassis Mount Chassis Mount - Chassis Mount	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency Operating Temperature Features Universal Input Mounting Type Size / Dimension - - Current - Output (Max) 12.5A 150W 150W 150W 150W 17E (Commercial) Voltage - Isolation - Chassis Mount Chassis Mount - Chassis Mount	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency Operating Temperature Features Universal Input Mounting Type Size / Dimension - Commercial Chassis Mount - Chassis Mount - Chassis Mount - Chassis Mount - Chassis Mount	Voltage - Output 1	12V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency 85% Operating Temperature -10°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension - Current - Output (Max) 12.5A 150W 150W 150W 10°C (With Derating) Universal Input Chassis Mount Size / Dimension	Voltage - Output 2	-
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency 85% Operating Temperature -10°C ~ 70°C (With Derating) Features Mounting Type Chassis Mount Size / Dimension 12.5A 150W 160W 170 (Commercial) - Commercial) - Commercial Commercial	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency 85% Operating Temperature -10°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension - 150W Commercial - Universal Commercial) - Commercial) - Commercial) - Chassis Mount - Chassis Mount - Chassis Mount	Voltage - Output 4	-
Applications ITE (Commercial) Voltage - Isolation - Efficiency 85% Operating Temperature -10°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension -	Current - Output (Max)	12.5A
Voltage - Isolation - Efficiency 85% Operating Temperature -10°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension -	Power (Watts)	150W
Efficiency 85% Operating Temperature -10°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension -	Applications	ITE (Commercial)
Operating Temperature -10°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension -	Voltage - Isolation	-
Features Universal Input Mounting Type Chassis Mount Size / Dimension -	Efficiency	85%
Mounting Type Chassis Mount Size / Dimension -	Operating Temperature	-10°C ~ 70°C (With Derating)
Size / Dimension -	Features	Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	-
		Report errors?

LFA150F-12 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LFA150F-12 Payment Methods





















LFA150F-12 Shipping Methods













If you have any question about LFA150F-12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com