

LG N971-KN-1

LG N971-KN-1 Information

www.heisener.com	 LG N971-KN-1 OSRAM Opto Semiconductors Inc. Optoelectronics LED Indication - Discrete LED GREEN DIFFUSED 1206 SMD 1206 (3216 Metric) For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



LG N971-KN-1 Specifications

ManufacturerOSRAM Opto Semiconductors Inc.CategoryOptoelectronicsEED Indication - DiscretePackage1206 (3216 Metric)SeriesCHIPLEDColorGreenConfiguration-Lens ColorWhiteLens TransparencyDiffusdMillicandela Rating26.05mcdVoltage - Forward (Vf) (Typ)2.2VCurrent - TestOmAViewing Angle610°Munufing TypeSurface MountWavelength - Peak570nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package1206 (3216 Metric)Size / Dimension3.00m L x 1.60mm WHeight (Max)1.20mm		
CategoryOptoelectronicsLED Indication - DiscretePackage1206 (3216 Metric)SeriesCHIPLEDColorGreenConfiguration-Lens ColorWhiteLens TransparencyDiffusedMillicandela Rating26.05mcdVoltage - Forward (Vf) (Typ)2.2VCurrent - TestOmAViewing Angle160°Wavelength - Dominant570nmWavelength - Peak572nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package1206 (3216 Metric)Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.20mm	Manufacturer Part Number	LG N971-KN-1
LED Indication - DiscretePackage1206 (3216 Metric)SeriesCHIPLEDColorGreenConfiguration-Lens ColorWhiteLens TansparencyDiffusedMillicandela Rating26.05mcdLens Style/SizeRectangle with Flat Top, 2.00mm x 1.60mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle160°Wavelength - Dominant570nmWavelength - Peak572nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.20mm	Manufacturer	OSRAM Opto Semiconductors Inc.
Package1206 (3216 Metric)SeriesCHIPLEDColorGreenConfiguration-Lens ColorWhiteLens ColorDiffusedMillicandela Rating26.05mcdLens Style/SizeRectangle with Flat Top, 2.00mm x 1.60mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle60°Wavelength - Dominant570nmWavelength - Peak572nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.20mm	Category	Optoelectronics
SeriesCHIPLEDColorGreenConfiguration-Lens ColorWhiteLens ColorDiffusedMillicandela Rating26.05mcdKetangle with Flat Top, 2.00mm x 1.60mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle160°Mounting TypeSurface MountWavelength - Peak570nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package3.20mm L x 1.60mm WHeight (Max)1.20mm		LED Indication - Discrete
ColorGreenConfiguration-Lens ColorWhiteLens ColorDiffusedLens TransparencyDiffusedMillicandela Rating26.05mcdLens Style/SizeRectangle with Flat Top, 2.00mm x 1.60mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle160°Mounting TypeSurface MountWavelength - Dominant570nmWavelength - Peak572nmPackage / Case1206 (3216 Metric)Supplier Device Package3.20mm L x 1.60mm WHeight (Max)1.20mm	Package	1206 (3216 Metric)
Configuration-Lens ColorWhiteLens TransparencyDiffusedMillicandela Rating26.05mcdLens Style/SizeRectangle with Flat Top, 2.00mm x 1.60mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle160°Mounting TypeSurface MountWavelength - Dominant570nmWavelength - Peak572nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package3.20mm L x 1.60mm WHeight (Max)1.20mm	Series	CHIPLED
Lens TransparencyWhiteLens TransparencyDiffusedMillicandela Rating26.05mcdLens Style/SizeRectangle with Flat Top, 2.00mm x 1.60mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle160°Mounting TypeSurface MountWavelength - Dominant570nmWavelength - Peak572nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package3.20mm L x 1.60mm WHeight (Max)1.20mm	Color	Green
Lens TransparencyDiffusedMillicandela Rating26.05mcdLens Style/SizeRectangle with Flat Top, 2.00mm x 1.60mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mACurrent - Test160°Wounting TypeSurface MountWavelength - Dominant570mmWavelength - Peak572mmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package3.20mm L x 1.60mm WHeight (Max)1.20mm	Configuration	-
Millicandela Rating26.05mcdLens Style/SizeRectangle with Flat Top, 2.00mm x 1.60mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle160°Mounting TypeSurface MountWavelength - Dominant570nmWavelength - Peak572nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package3.20mm L x 1.60mm WHeight (Max)1.20mm	Lens Color	White
Lens Style/SizeRectangle with Flat Top, 2.00mm x 1.60mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle160°Mounting TypeSurface MountWavelength - Dominant570nmWavelength - Peak572nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.20mm	Lens Transparency	Diffused
Voltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle160°Mounting TypeSurface MountWavelength - Dominant570nmWavelength - Peak572nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.20mm	Millicandela Rating	26.05mcd
Current - Test20mAViewing Angle160°Mounting TypeSurface MountWavelength - Dominant570nmWavelength - Peak572nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.20mm	Lens Style/Size	Rectangle with Flat Top, 2.00mm x 1.60mm
Viewing Angle160°Mounting TypeSurface MountWavelength - Dominant570nmWavelength - Peak572nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.20mm	Voltage - Forward (Vf) (Typ)	2.2V
Mounting TypeSurface MountWavelength - Dominant570nmWavelength - Peak572nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.20mm	Current - Test	20mA
Wavelength - Dominant570nmWavelength - Peak572nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.20mm	Viewing Angle	160°
Wavelength - Peak572nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.20mm	Mounting Type	Surface Mount
Features-Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.20mm	Wavelength - Dominant	570nm
Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.20mm	Wavelength - Peak	572nm
Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.20mm	Features	-
Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.20mm	Package / Case	1206 (3216 Metric)
Height (Max) 1.20mm	Supplier Device Package	1206
	Size / Dimension	3.20mm L x 1.60mm W
Report errors?	Height (Max)	1.20mm
		Report errors?

LG N971-KN-1 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE GUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

LG N971-KN-1 Payment Methods



LG N971-KN-1 Shipping Methods



If you have any question about LG N971-KN-1, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com