

**LGJ7045TC-330M-D Information**


For Reference Only

**Part Number** [LGJ7045TC-330M-D](#)  
**Manufacturer** TDK Corporation  
**Category** Inductors, Coils, Chokes  
[Fixed Inductors](#)  
**Description** FIXED IND 33UH 1.4A 110 MOHM SMD  
**Package** Nonstandard  
 For the pricing/inventory/lead time, please contact us  
 Website: <https://www.heisener.com>  
 E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)


[Request a Quote](#)
**Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.


**LGJ7045TC-330M-D Specifications**

Manufacturer Part Number	<a href="#">LGJ7045TC-330M-D</a>
Manufacturer	TDK Corporation
Category	Inductors, Coils, Chokes <a href="#">Fixed Inductors</a>
Package	Nonstandard
Series	LGJ
Type	Wirewound
Material - Core	Ferrite
Inductance	33µH
Tolerance	±20%
Current Rating	1.4A
Current - Saturation	1.55A
Shielding	Shielded
DC Resistance (DCR)	110 mOhm
Q @ Freq	-
Frequency - Self Resonant	-
Ratings	AEC-Q200
Operating Temperature	-40°C ~ 150°C
Frequency - Test	100kHz
Features	-
Mounting Type	Surface Mount
Package / Case	Nonstandard
Supplier Device Package	-
Size / Dimension	0.283" L x 0.272" W (7.20mm x 6.90mm)

Height - Seated (Max)

0.177" (4.50mm)

[Report errors?](#)

## LGJ7045TC-330M-D Guarantees



### Quality Guarantees

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



### Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## LGJ7045TC-330M-D Payment Methods



## LGJ7045TC-330M-D Shipping Methods



If you have any question about LGJ7045TC-330M-D, please do not hesitate to contact us!

Website: <https://www.heisener.com>

E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)