



LKS1H682MESB Information

Heisener.com

Part Number LKS1H682MESB

Manufacturer Nichicon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 6800UF 20% 50V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LKS1H682MESB Specifications

Manufacturer Part NumberLKS1H682MESBManufacturerNichiconCategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesLKSCapacitance6800µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency3.15A @ 120HzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.378" (35.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	*	
Category Capacitors Package Radial, Can - Snap-In Series LKS Capacitance 6800µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications Audio Ripple Current - Low Frequency 3.15A @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.378" (35.00mm) Surface Mount Land Size - Mounting Type Through Hole	Manufacturer Part Number	LKS1H682MESB
PackageRadial, Can - Snap-InSeriesLKSCapacitance6800μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency3.15A @ 120HzRipple Current - High Frequency-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.378" (35.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Manufacturer	Nichicon
PackageRadial, Can - Snap-InSeriesLKSCapacitance6800μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency3.15A @ 120HzRipple Current - High Frequency-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.378" (35.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Category	Capacitors
SeriesLKSCapacitance6800μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency3.15A @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.378" (35.00mm)Surface Mount Land Size-Mounting TypeThrough Hole		Aluminum Electrolytic Capacitors
Capacitance6800µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency3.15A @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.378" (35.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Package	Radial, Can - Snap-In
Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications Audio Ripple Current - Low Frequency 3.15A @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.378" (35.00mm) Surface Mount Land Size - Mounting Type Through Hole	Series	LKS
Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications Audio Ripple Current - Low Frequency 3.15A @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.378" (35.00mm) Surface Mount Land Size - Mounting Type Through Hole	Capacitance	6800μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications Audio Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 0.394" (10.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type -1000 Hrs @ 85°C -40°C ~ 85°C Polar Audio -3.15A @ 120Hz -3.15A @ 120Hz -3.15A @ 120Hz -3.15A @ 120Hz -4.15A @ 120Hz -4.1	Tolerance	±20%
Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications Audio Ripple Current - Low Frequency 3.15A @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.378" (35.00mm) Surface Mount Land Size - Mounting Type Through Hole	Voltage - Rated	50V
Operating Temperature -40°C ~ 85°C Polarization Applications Audio Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing O.394" (10.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type -40°C ~ 85°C Polar Audio -40°C ~ 85°C -40	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications Audio Ripple Current - Low Frequency 3.15A @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.378" (35.00mm) Surface Mount Land Size - Mounting Type Through Hole	Lifetime @ Temp.	1000 Hrs @ 85°C
Applications Ripple Current - Low Frequency 3.15A @ 120Hz Ripple Current - High Frequency Impedance Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.378" (35.00mm) Surface Mount Land Size Mounting Type Through Hole	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing O.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type 3.15A @ 120Hz - Through Hole	Polarization	Polar
Ripple Current - High Frequency Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.378" (35.00mm) Surface Mount Land Size - Mounting Type Through Hole	Applications	Audio
Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.378" (35.00mm) Surface Mount Land Size - Mounting Type Through Hole	Ripple Current - Low Frequency	3.15A @ 120Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.378" (35.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - High Frequency	-
Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.378" (35.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type 1.378" (35.00mm) - Through Hole	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size - Mounting Type Through Hole	Size / Dimension	1.181" Dia (30.00mm)
Mounting Type Through Hole	Height - Seated (Max)	1.378" (35.00mm)
	Surface Mount Land Size	-
Package / Case Radial, Can - Snap-In	Mounting Type	Through Hole
	Package / Case	Radial, Can - Snap-In
Report errors?		Report errors?

LKS1H682MESB Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LKS1H682MESB Payment Methods





















LKS1H682MESB Shipping Methods













If you have any question about LKS1H682MESB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com