



LLS1E183MELB Information



For Reference Only

Part Number LLS1E183MELB

Manufacturer Nichicon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 18000UF 20% 25V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LLS1E183MELB Specifications

Manufacturer Part NumberLLS1E183MELBManufacturerNichiconCategoryCapacitorsPackageRadial, Can - Snap-InSeriesLLSCapacitance18000µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.66A @ 120HzRipple Current - High Frequency5.359A @ 50kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	1	
Category Capacitors Package Radial, Can - Snap-In Series LLS Capacitance 18000µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 3000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.66A @ 120Hz Ripple Current - High Frequency 5.359A @ 50kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole	Manufacturer Part Number	LLS1E183MELB
PackageAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesLLSCapacitance18000μFTolerance±20%Voltage - Rated25 VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.66A @ 120HzRipple Current - High Frequency5.359A @ 50kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Manufacturer	Nichicon
Package Radial, Can - Snap-In Series LLS Capacitance 18000µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 3000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.66A @ 120Hz Ripple Current - High Frequency 5.359A @ 50kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole	Category	Capacitors
Series LLS Capacitance 18000μF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 3000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.66A @ 120Hz Ripple Current - High Frequency 5.359A @ 50kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole		Aluminum Electrolytic Capacitors
Capacitance18000µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.66A @ 120HzRipple Current - High Frequency5.359A @ 50kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Package	Radial, Can - Snap-In
Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 3000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.66A @ 120Hz Ripple Current - High Frequency 5.359A @ 50kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole	Series	LLS
Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.66A @ 120HzRipple Current - High Frequency5.359A @ 50kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Capacitance	18000μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 3000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 4.66A @ 120Hz Ripple Current - High Frequency 5.359A @ 50kHz Impedance Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole	Tolerance	±20%
Lifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.66A @ 120HzRipple Current - High Frequency5.359A @ 50kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Voltage - Rated	25V
Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 4.66A @ 120Hz Ripple Current - High Frequency 5.359A @ 50kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size Mounting Type Through Hole	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.66A @ 120Hz Ripple Current - High Frequency 5.359A @ 50kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole	Lifetime @ Temp.	3000 Hrs @ 85°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency 5.359A @ 50kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency 5.359A @ 50kHz Impedance Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size Mounting Type Through Hole	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size Mounting Type Through Hole	Applications	General Purpose
Impedance - Card Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Through Hole	Ripple Current - Low Frequency	4.66A @ 120Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - High Frequency	5.359A @ 50kHz
Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type 1.457" (37.00mm) - Through Hole	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size - Mounting Type Through Hole	Size / Dimension	1.181" Dia (30.00mm)
Mounting Type Through Hole	Height - Seated (Max)	1.457" (37.00mm)
	Surface Mount Land Size	-
Package / Case Radial, Can - Snap-In	Mounting Type	Through Hole
	Package / Case	Radial, Can - Snap-In
Report errors?		Report errors?

LLS1E183MELB Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LLS1E183MELB Payment Methods



















LLS1E183MELB Shipping Methods













If you have any question about LLS1E183MELB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com