



LLS1V153MELA Information



For Reference Only

Part Number LLS1V153MELA

Manufacturer Nichicon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 15000UF 20% 35V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LLS1V153MELA Specifications

Manufacturer Part NumberLLS1V153MELAManufacturerNichiconCategoryCapacitorsPackageRadial, Can - Snap-InSeriesLLSCapacitance15000μFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.8A @ 120HzRipple Current - High Frequency5.52A @ 50kHz		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series LLS Capacitance 15000μF Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) Lifetime @ Temp. 3000 Hrs @ 85°C Operating Temperature Polarization Applications Ripple Current - Low Frequency Capacitors Radial, Can - Snap-In LLS 15000μF - 20% 35V - 20% General Purpose 4.8A @ 120Hz	er Part Number	LLS1V153MELA
Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In LLS Capacitance 15000µF Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) Lifetime @ Temp. 3000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications Ripple Current - Low Frequency Aluminum Electrolytic Capacitors Radial, Can - Snap-In LLS 15000µF -20% 420% Folar General Purpose Aluminum Electrolytic Capacitors Radial, Can - Snap-In LLS 15000µF -40% Folar General Purpose Aluminum Electrolytic Capacitors Radial, Can - Snap-In LLS 15000µF -40% Folar General Purpose Aluminum Electrolytic Capacitors Radial, Can - Snap-In LLS General Purpose Aluminum Electrolytic Capacitors Radial, Can - Snap-In LLS General Purpose Aluminum Electrolytic Capacitors Radial, Can - Snap-In LLS General Purpose Aluminum Electrolytic Capacitors Radial, Can - Snap-In LLS General Purpose Aluminum Electrolytic Capacitors LLS LLS General Purpose Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Aluminum Plane Alumi	er	Nichicon
PackageRadial, Can - Snap-InSeriesLLSCapacitance $15000\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $35V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $3000 \text{ Hrs } @ 85^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency $4.8A @ 120\text{Hz}$		Capacitors
SeriesLLSCapacitance $15000μF$ Tolerance $\pm 20\%$ Voltage - Rated $35V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $3000 Hrs @ 85°C$ Operating Temperature $-40°C \sim 85°C$ PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency $4.8A @ 120Hz$		Aluminum Electrolytic Capacitors
Capacitance $15000μF$ Tolerance $\pm 20\%$ Voltage - Rated $35V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $3000 Hrs @ 85°C$ Operating Temperature $-40°C \sim 85°C$ PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency $4.8A @ 120Hz$		Radial, Can - Snap-In
Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 3000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.8A @ 120Hz		LLS
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature Polarization Applications Ripple Current - Low Frequency 35V -40°C ~ 85°C Polarization Polar Applications General Purpose 4.8A @ 120Hz		15000μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 3000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.8A @ 120Hz		±20%
Lifetime @ Temp. $3000 \text{Hrs} \@ 85^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency $4.8A \@ 120\text{Hz}$	ated	35V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.8A @ 120Hz	alent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.8A @ 120Hz	Temp.	3000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency 4.8A @ 120Hz	'emperature	-40°C ~ 85°C
Ripple Current - Low Frequency 4.8A @ 120Hz		Polar
	s	General Purpose
Ripple Current - High Frequency 5.52A @ 50kHz	ent - Low Frequency	4.8A @ 120Hz
	ent - High Frequency	5.52A @ 50kHz
Impedance -		-
Lead Spacing 0.394" (10.00mm)	ıg	0.394" (10.00mm)
Size / Dimension 0.984" Dia (25.00mm)	nsion	0.984" Dia (25.00mm)
Height - Seated (Max) 2.047" (52.00mm)	ated (Max)	2.047" (52.00mm)
Surface Mount Land Size -	unt Land Size	-
Mounting Type Through Hole	ype	Through Hole
Package / Case Radial, Can - Snap-In	ase	Radial, Can - Snap-In
Report error		Report errors

LLS1V153MELA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LLS1V153MELA Payment Methods



















LLS1V153MELA Shipping Methods













If you have any question about LLS1V153MELA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com