



LM258AD Information

www.hellanthom

For Reference Only

Part Number LM258AD

Manufacturer STMicroelectronics

Category Integrated Circuits (ICs)

Linear - Amplifiers - Instrumentation, OP Amps,

Buffer Amps

Description IC OPAMP GP 1.1MHZ 8SO **Package** 8-SOIC (0.154", 3.90mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LM258AD Specifications

Manufacturer Part Number LM258AD Manufacturer STMicroelectronics Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-SOIC (0.154", 3.90mm Width) Series - Amplifier Type General Purpose Number of Circuits 2 Output Type - Slew Rate 0.6 V/μs Gain Bandwidth Product 1.1MHz -3db Bandwidth - Current - Input Bias 20nA Voltage - Input Offset ImV Current - Output / Channel 60mA Voltage - Supply, Single/Dual (±) 3 V ~ 30 V, ±1.5 V ~ 15 V Operating Temperature -40°C ~ 105°C Mounting Type Surface Mount Package (Case 8 SOIC (0.154", 3.90mm Width)		
Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-SOIC (0.154", 3.90mm Width) Series - Amplifier Type General Purpose Number of Circuits 2 Output Type - Slew Rate 0.6 V/μs Gain Bandwidth Product 1.1MHz -3db Bandwidth - Current - Input Bias 20nA Voltage - Input Offset ImV Current - Supply 700μA Current - Output / Channel 60mA Voltage - Supply, Single/Dual (±) 3 V ~ 30 V, ±1.5 V ~ 15 V Operating Temperature -40°C ~ 105°C Mounting Type Surface Mount	Manufacturer Part Number	LM258AD
Linear - Amplifiers - Instrumentation, OP Amps, Buffer AmpsPackage8-SOIC (0.154", 3.90mm Width)Series-Amplifier TypeGeneral PurposeNumber of Circuits2Output Type-Slew Rate0.6 V/μsGain Bandwidth Product1.1MHz-3db Bandwidth-Current - Input Bias20nAVoltage - Input OffsetImVCurrent - Supply700μACurrent - Output / Channel60mAVoltage - Supply, Single/Dual (±)3 V ~ 30 V, ±1.5 V ~ 15 VOperating Temperature-40°C ~ 105°CMounting TypeSurface Mount	Manufacturer	STMicroelectronics
Package8-SOIC (0.154", 3.90mm Width)Series-Amplifier TypeGeneral PurposeNumber of Circuits2Output Type-Slew Rate 0.6 V/μs Gain Bandwidth Product 1.1MHz -3db Bandwidth-Current - Input Bias 20nA Voltage - Input Offset 1mV Current - Supply $700\mu\text{A}$ Current - Output / Channel 60mA Voltage - Supply, Single/Dual (±) $3 \text{ V} \sim 30 \text{ V}, \pm 1.5 \text{ V} \sim 15 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Mounting TypeSurface Mount	Category	Integrated Circuits (ICs)
Series - Amplifier Type General Purpose Sumber of Circuits 2 Output Type - Slew Rate 0.6 V/ μ s Gain Bandwidth Product 1.1MHz - 3db Bandwidth - Current - Input Bias 20nA Voltage - Input Offset 1mV Current - Supply 700 μ A Current - Output / Channel 60mA Voltage - Supply, Single/Dual (\pm) 3 V ~ 30 V, \pm 1.5 V ~ 15 V Operating Temperature -40°C ~ 105°C Mounting Type Surface Mount		Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps
Amplifier Type General Purpose Number of Circuits 2 Output Type - Slew Rate 0.6 V/ μ s Gain Bandwidth Product 1.1MHz -3db Bandwidth - Current - Input Bias 20nA Voltage - Input Offset 1mV Current - Supply 700 μ A Current - Output / Channel 60mA Voltage - Supply, Single/Dual (\pm) 3 V ~ 30 V, \pm 1.5 V ~ 15 V Operating Temperature -40°C ~ 105°C Mounting Type Surface Mount	Package	8-SOIC (0.154", 3.90mm Width)
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	Series	-
Output Type - Slew Rate 0.6 V/ μ s Gain Bandwidth Product 1.1MHz -3db Bandwidth - Current - Input Bias 20nA Voltage - Input Offset 1mV Current - Supply 700 μ A Current - Output / Channel 60mA Voltage - Supply, Single/Dual (\pm) 3 V ~ 30 V, \pm 1.5 V ~ 15 V Operating Temperature -40°C ~ 105°C Mounting Type Surface Mount	Amplifier Type	General Purpose
Slew Rate $0.6 \text{ V/}\mu\text{s}$ Gain Bandwidth Product 1.1MHz -3db Bandwidth - Current - Input Bias 20nA Voltage - Input Offset 1mV Current - Supply $700 \mu\text{A}$ Current - Output / Channel 60mA Voltage - Supply, Single/Dual (\pm) $3 \text{ V} \sim 30 \text{ V}, \pm 1.5 \text{ V} \sim 15 \text{ V}$ Operating Temperature $-40 ^{\circ}\text{C} \sim 105 ^{\circ}\text{C}$ Mounting Type Surface Mount	Number of Circuits	2
Gain Bandwidth Product -3db Bandwidth -Current - Input Bias 20nA Voltage - Input Offset 1mV Current - Supply 700 μ A Current - Output / Channel Voltage - Supply, Single/Dual (\pm) Operating Temperature Mounting Type 1.1MHz -40°C ~ 105°C Surface Mount	Output Type	-
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	Slew Rate	0.6 V/μs
Current - Input Bias 20nA Voltage - Input Offset 1mV Current - Supply 700 μ A Current - Output / Channel 60mA Voltage - Supply, Single/Dual (\pm) 3 V ~ 30 V, \pm 1.5 V ~ 15 V Operating Temperature -40°C ~ 105°C Mounting Type Surface Mount	Gain Bandwidth Product	1.1MHz
Voltage - Input Offset $1mV$ Current - Supply $700\mu A$ Current - Output / Channel $60mA$ Voltage - Supply, Single/Dual (\pm) $3V \sim 30V, \pm 1.5V \sim 15V$ Operating Temperature $-40^{\circ}C \sim 105^{\circ}C$ Mounting Type Surface Mount	-3db Bandwidth	-
Current - Supply 700 μ A Current - Output / Channel 60mA Voltage - Supply, Single/Dual (\pm) 3 V ~ 30 V, \pm 1.5 V ~ 15 V Operating Temperature -40°C ~ 105°C Mounting Type Surface Mount	Current - Input Bias	20nA
Current - Output / Channel 60mA Voltage - Supply, Single/Dual (\pm) $3 \text{ V} \sim 30 \text{ V}, \pm 1.5 \text{ V} \sim 15 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Mounting TypeSurface Mount	Voltage - Input Offset	1mV
Voltage - Supply, Single/Dual (\pm) 3 V ~ 30 V, \pm 1.5 V ~ 15 V Operating Temperature -40°C ~ 105°C Mounting Type Surface Mount	Current - Supply	700μΑ
Operating Temperature -40°C ~ 105°C Mounting Type Surface Mount	Current - Output / Channel	60mA
Mounting Type Surface Mount	Voltage - Supply, Single/Dual (±)	3 V ~ 30 V, ±1.5 V ~ 15 V
	Operating Temperature	-40°C ~ 105°C
Package / Case 8 SOIC (0.154" 3.00mm Width)	Mounting Type	Surface Mount
1 ackage / Case 0-301C (0.134, 3.70111111 WIUII)	Package / Case	8-SOIC (0.154", 3.90mm Width)
Supplier Device Package 8-SO	Supplier Device Package	8-SO
Report error		Report errors?

LM258AD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LM258AD Payment Methods





















LM258AD Shipping Methods













If you have any question about LM258AD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com