

LM2904N Information



For Reference Only

Part Number LM2904N

Manufacturer ON Semiconductor
Category Integrated Circuits (ICs)

Linear - Amplifiers - Instrumentation, OP Amps,

Buffer Amps

Description IC OPAMP GP 8DIP **Package** 8-DIP (0.300", 7.62mm)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LM2904N Specifications

Manufacturer Part Number LM2904N Manufacturer ON Semiconductor Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-DIP (0.300", 7.62mm) Series - Amplifier Type General Purpose Number of Circuits 2 Output Type - Slew Rate 0.3 V/μs Gain Bandwidth Product - -3db Bandwidth - Current - Input Bias 45nA Voltage - Input Offset 2.9mV Current - Supply 800μA Current - Output / Channel 30mA Voltage - Supply, Single/Dual (±) 3 V ~ 26 V, ±1.5 V ~ 13 V Operating Temperature -40°C ~ 85°C Mounting Type Through Hole		
CategoryIntegrated Circuits (ICs)Linear - Amplifiers - Instrumentation, OP Amps, Buffer AmpsPackage8-DIP (0.300", 7.62mm)Series-Amplifier TypeGeneral PurposeNumber of Circuits2Output Type-Slew Rate0.3 V/μsGain Bandwidth Product3db Bandwidth-Current - Input Bias45nAVoltage - Input Offset2.9mVCurrent - Supply800μACurrent - Output / Channel30mAVoltage - Supply, Single/Dual (±)3 V ~ 26 V, ±1.5 V ~ 13 VOperating Temperature-40°C ~ 85°C	Manufacturer Part Number	LM2904N
Linear - Amplifiers - Instrumentation, OP Amps, Buffer AmpsPackage8-DIP (0.300", 7.62mm)Series-Amplifier TypeGeneral PurposeNumber of Circuits2Output Type-Slew Rate0.3 V/μsGain Bandwidth Product3db Bandwidth-Current - Input Bias45nAVoltage - Input Offset2.9mVCurrent - Supply800μACurrent - Output / Channel30mAVoltage - Supply, Single/Dual (±)3 V ~ 26 V, ±1.5 V ~ 13 VOperating Temperature-40°C ~ 85°C	Manufacturer	ON Semiconductor
Package 8-DIP (0.300", 7.62mm) Series - Amplifier Type General Purpose Number of Circuits 2 Output Type - Slew Rate 0.3 V/μs Gain Bandwidth Product - -3db Bandwidth - Current - Input Bias 45nA Voltage - Input Offset 2.9mV Current - Supply 800μA Current - Output / Channel 30mA Voltage - Supply, Single/Dual (±) 3 V ~ 26 V, ±1.5 V ~ 13 V Operating Temperature -40°C ~ 85°C	Category	Integrated Circuits (ICs)
Series - Amplifier Type General Purpose Number of Circuits 2 Output Type - Slew Rate 0.3 V/μs Gain Bandwidth Product - -3db Bandwidth - Current - Input Bias 45nA Voltage - Input Offset 2.9mV Current - Supply 800μA Current - Output / Channel 30mA Voltage - Supply, Single/Dual (±) 3 V ~ 26 V, ±1.5 V ~ 13 V Operating Temperature -40°C ~ 85°C		Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps
Amplifier Type General Purpose Number of Circuits 2 Output Type - Slew Rate 0.3 V/ μ s Gain Bandwidth Product3db Bandwidth - Current - Input Bias 45nA Voltage - Input Offset 2.9mV Current - Supply 800 μ A Current - Output / Channel 30mA Voltage - Supply, Single/Dual (\pm) 3 V ~ 26 V, \pm 1.5 V ~ 13 V Operating Temperature -40°C ~ 85°C	Package	8-DIP (0.300", 7.62mm)
Number of Circuits 2 Output Type - Slew Rate 0.3 V/ μ s Gain Bandwidth Product3db Bandwidth Current - Input Bias 45nA Voltage - Input Offset 2.9mV Current - Supply 800 μ A Current - Output / Channel 30mA Voltage - Supply, Single/Dual (\pm) 3 V ~ 26 V, \pm 1.5 V ~ 13 V Operating Temperature -40°C ~ 85°C	Series	-
Output Type - Slew Rate 0.3 V/ μ s Gain Bandwidth Product	Amplifier Type	General Purpose
Slew Rate 0.3 V/ μ s Gain Bandwidth Product3db Bandwidth - Current - Input Bias 45nA Voltage - Input Offset 2.9mV Current - Supply 800 μ A Current - Output / Channel 30mA Voltage - Supply, Single/Dual (±) 3 V ~ 26 V, \pm 1.5 V ~ 13 V Operating Temperature -40°C ~ 85°C	Number of Circuits	2
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	Output Type	-
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	Slew Rate	0.3 V/µs
Current - Input Bias $45nA$ Voltage - Input Offset $2.9mV$ Current - Supply $800\mu A$ Current - Output / Channel $30mA$ Voltage - Supply, Single/Dual (\pm) $3 V \sim 26 V$, $\pm 1.5 V \sim 13 V$ Operating Temperature $-40^{\circ}C \sim 85^{\circ}C$	Gain Bandwidth Product	-
$\begin{tabular}{lllllllllllllllllllllllllllllllllll$	-3db Bandwidth	-
Current - Supply $800\mu A$ Current - Output / Channel $30mA$ Voltage - Supply, Single/Dual (\pm) $3 \ V \sim 26 \ V$, $\pm 1.5 \ V \sim 13 \ V$ Operating Temperature $-40^{\circ}C \sim 85^{\circ}C$	Current - Input Bias	45nA
Current - Output / Channel 30mA Voltage - Supply, Single/Dual (\pm) 3 V ~ 26 V, \pm 1.5 V ~ 13 V Operating Temperature -40°C ~ 85°C	Voltage - Input Offset	2.9mV
Voltage - Supply, Single/Dual (\pm) 3 V ~ 26 V, \pm 1.5 V ~ 13 V Operating Temperature -40°C ~ 85°C	Current - Supply	800μΑ
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Current - Output / Channel	30mA
	Voltage - Supply, Single/Dual (±)	3 V ~ 26 V, ±1.5 V ~ 13 V
Mounting Type Through Hole	Operating Temperature	-40°C ~ 85°C
Tillough Hote	Mounting Type	Through Hole
Package / Case 8-DIP (0.300", 7.62mm)	Package / Case	8-DIP (0.300", 7.62mm)
Supplier Device Package 8-DIP	Supplier Device Package	8-DIP
Report erro		Report errors?

LM2904N Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LM2904N Payment Methods



















LM2904N Shipping Methods













If you have any question about LM2904N, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com