



LM358DT Information

www.hellanter.cm

For Reference Only

Part Number LM358DT

Manufacturer STMicroelectronics

Category Integrated Circuits (ICs)

Linear - Amplifiers - Instrumentation, OP Amps,

Buffer Amps

Description IC OPAMP GP 1.1MHZ 8SO **Package** 8-SOIC (0.154", 3.90mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LM358DT Specifications

Manufacturer Part Number LM358DT Manufacturer STMicroelectronics Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-SOIC (0.154", 3.90mm Width) Series - Amplifier Type General Purpose Number of Circuits 2 Output Type - Slew Rate 0.6 V/μs Gain Bandwidth Product 1.1MHz -3db Bandwidth - Current - Input Bias 20nA Voltage - Input Offset 2mV Current - Supply 700μA Current - Output / Channel 60mA Voltage - Supply, Single/Dual (±) 3 V ~ 30 V, ±1.5 V ~ 15 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SO		
Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-SOIC (0.154", 3.90mm Width) Series - Amplifier Type General Purpose Number of Circuits 2 Output Type - Slew Rate 0.6 V/μs Gain Bandwidth Product 1.1MHz -3db Bandwidth - Current - Input Bias 20nA Voltage - Input Offset 2mV Current - Supply 700μA Current - Output / Channel 60mA Voltage - Supply, Single/Dual (±) 3 V ~ 30 V, ±1.5 V ~ 15 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)	Manufacturer Part Number	LM358DT
Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-SOIC (0.154", 3.90mm Width) Series - Amplifier Type General Purpose Number of Circuits 2 Output Type - Slew Rate 0.6 V/μs Gain Bandwidth Product 1.1MHz -3db Bandwidth - Current - Input Bias 20nA Voltage - Input Offset 2mV Current - Supply 700μA Current - Output / Channel 60mA Voltage - Supply, Single/Dual (±) 3 V ~ 30 V, ±1.5 V ~ 15 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)	Manufacturer	STMicroelectronics
Package8-SOIC (0.154", 3.90mm Width)Series-Amplifier TypeGeneral PurposeNumber of Circuits2Output Type-Slew Rate 0.6 V/μs Gain Bandwidth Product 1.1MHz -3db Bandwidth-Current - Input Bias 20nA Voltage - Input Offset 2mV Current - Supply $700\mu\text{A}$ Current - Output / Channel 60mA Voltage - Supply, Single/Dual (±) $3 \text{ V} \sim 30 \text{ V}, \pm 1.5 \text{ V} \sim 15 \text{ V}$ Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Mounting TypeSurface MountPackage / Case $8\text{-SOIC (0.154", 3.90mm Width)}$	Category	Integrated Circuits (ICs)
Series - Amplifier Type General Purpose Number of Circuits 2 Output Type - Slew Rate 0.6 V/μs Gain Bandwidth Product 1.1MHz -3db Bandwidth - Current - Input Bias 20nA Voltage - Input Offset 2mV Current - Supply 700μA Current - Output / Channel 60mA Voltage - Supply, Single/Dual (±) 3 V ~ 30 V, ±1.5 V ~ 15 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)		Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps
Amplifier Type General Purpose Number of Circuits 2 2 Output Type - Slew Rate 0.6 V/ μ s Gain Bandwidth Product 1.1MHz -3db Bandwidth - Current - Input Bias 20nA Voltage - Input Offset 2mV Current - Supply 700 μ A Current - Output / Channel 60mA Voltage - Supply, Single/Dual (\pm) 3 V ~ 30 V, \pm 1.5 V ~ 15 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)	Package	8-SOIC (0.154", 3.90mm Width)
Number of Circuits 2 Output Type - Slew Rate 0.6 V/μs Gain Bandwidth Product 1.1MHz -3db Bandwidth - Current - Input Bias 20nA Voltage - Input Offset 2mV Current - Supply 700μA Current - Output / Channel 60mA Voltage - Supply, Single/Dual (±) 3 V ~ 30 V, ±1.5 V ~ 15 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)	Series	-
Output Type - Slew Rate 0.6 V/μs Gain Bandwidth Product 1.1MHz -3db Bandwidth - Current - Input Bias 20nA Voltage - Input Offset 2mV Current - Supply 700μA Current - Output / Channel 60mA Voltage - Supply, Single/Dual (±) 3 V ~ 30 V, ±1.5 V ~ 15 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)	Amplifier Type	General Purpose
Slew Rate $0.6 \text{ V/}\mu\text{s}$ Gain Bandwidth Product 1.1MHz -3db Bandwidth - Current - Input Bias 20nA Voltage - Input Offset 2mV Current - Supply $700 \mu\text{A}$ Current - Output / Channel 60mA Voltage - Supply, Single/Dual (±) $3 \text{ V} \sim 30 \text{ V}, \pm 1.5 \text{ V} \sim 15 \text{ V}$ Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Mounting Type $8 \text{-SOIC } (0.154^{\circ}, 3.90 \text{mm Width})$	Number of Circuits	2
Gain Bandwidth Product -3db Bandwidth - Current - Input Bias 20nA Voltage - Input Offset 2mV Current - Supply 700μA Current - Output / Channel 60mA Voltage - Supply, Single/Dual (±) 3 V ~ 30 V, ±1.5 V ~ 15 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)	Output Type	-
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	Slew Rate	0.6 V/μs
Current - Input Bias 20nA Voltage - Input Offset 2mV Current - Supply 700 μ A Current - Output / Channel 60mA Voltage - Supply, Single/Dual (\pm) 3 V ~ 30 V, \pm 1.5 V ~ 15 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)	Gain Bandwidth Product	1.1MHz
$\begin{tabular}{lllllllllllllllllllllllllllllllllll$	-3db Bandwidth	-
Current - Supply $700\mu A$ Current - Output / Channel $60mA$ Voltage - Supply, Single/Dual (±) $3 V \sim 30 V$, $\pm 1.5 V \sim 15 V$ Operating Temperature $0^{\circ}C \sim 70^{\circ}C$ Mounting Type Surface Mount Package / Case 8 -SOIC $(0.154^{\circ}, 3.90mm Width)$	Current - Input Bias	20nA
Current - Output / Channel $60mA$ Voltage - Supply, Single/Dual (\pm) $3 \text{ V} \sim 30 \text{ V}, \pm 1.5 \text{ V} \sim 15 \text{ V}$ Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Mounting TypeSurface MountPackage / Case $8\text{-SOIC }(0.154\text{"}, 3.90\text{mm Width})$	Voltage - Input Offset	2mV
Voltage - Supply, Single/Dual (\pm) 3 V ~ 30 V, \pm 1.5 V ~ 15 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)	Current - Supply	700μΑ
Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)	Current - Output / Channel	60mA
Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)	Voltage - Supply, Single/Dual (±)	3 V ~ 30 V, ±1.5 V ~ 15 V
Package / Case 8-SOIC (0.154", 3.90mm Width)	Operating Temperature	0°C ~ 70°C
-	Mounting Type	Surface Mount
Supplier Device Package 8-SO	Package / Case	8-SOIC (0.154", 3.90mm Width)
	Supplier Device Package	8-SO
Report errors		Report errors?

LM358DT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LM358DT Payment Methods



















LM358DT Shipping Methods













If you have any question about LM358DT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com