




LM3S1150-IBZ50-A2 Information



For Reference Only

Part Number LM3S1150-IBZ50-A2

Manufacturer Texas Instruments

Category Integrated Circuits (ICs)
Embedded - Microcontrollers

Description IC MCU 32BIT 64KB FLASH 108BGA

Package 108-LFBGA

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LM3S1150-IBZ50-A2 Specifications

Manufacturer Part NumberLM3S1150-IBZ50-A2ManufacturerTexas InstrumentsCategoryIntegrated Circuits (ICs)Embedded - MicrocontrollersPackage108-LFBGASeriesStellaris? ARM? Cortex?-M3S 1000Core ProcessorARM? Cortex?-M3Core Size32-BitSpeed50MHzConnectivityI2C, IrDA, Microwire, QEI, SPI, SSI, UART/USARTPeripheralsBrown-out Detect/Reset, POR, PWM, WDTNumber of I/O52Program Memory Size64KB (64K x 8)Program Memory TypeFLASHEEPROM Size-RAM Size16K x 8Voltage - Supply (Vcc/Vdd)2.25 V ~ 2.75 V
Category Integrated Circuits (ICs) Embedded - Microcontrollers Package 108-LFBGA Series Stellaris? ARM? Cortex?-M3S 1000 Core Processor ARM? Cortex?-M3 Core Size 32-Bit Speed 50MHz Connectivity I2C, IrDA, Microwire, QEI, SPI, SSI, UART/USART Peripherals Brown-out Detect/Reset, POR, PWM, WDT Number of I/O 52 Program Memory Size 64KB (64K x 8) Program Memory Type FLASH EEPROM Size - RAM Size I08-LFBGA Stellaris? ARM? Cortex?-M3S 1000 ARM? Cortex?-M3S 1
Embedded - Microcontrollers Package 108-LFBGA Series Stellaris? ARM? Cortex?-M3S 1000 Core Processor ARM? Cortex?-M3 Core Size 32-Bit Speed 50MHz Connectivity I2C, IrDA, Microwire, QEI, SPI, SSI, UART/USART Peripherals Brown-out Detect/Reset, POR, PWM, WDT Number of I/O 52 Program Memory Size 64KB (64K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 16K x 8
Package 108-LFBGA Series Stellaris? ARM? Cortex?-M3S 1000 Core Processor ARM? Cortex?-M3 Core Size 32-Bit Speed 50MHz Connectivity I2C, IrDA, Microwire, QEI, SPI, SSI, UART/USART Peripherals Brown-out Detect/Reset, POR, PWM, WDT Number of I/O 52 Program Memory Size 64KB (64K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 16K x 8
Series Stellaris? ARM? Cortex?-M3S 1000 Core Processor ARM? Cortex?-M3 Core Size 32-Bit Speed 50MHz Connectivity I2C, IrDA, Microwire, QEI, SPI, SSI, UART/USART Peripherals Brown-out Detect/Reset, POR, PWM, WDT Number of I/O 52 Program Memory Size 64KB (64K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 16K x 8
Core Processor Core Size 32-Bit Speed 50MHz Connectivity I2C, IrDA, Microwire, QEI, SPI, SSI, UART/USART Peripherals Brown-out Detect/Reset, POR, PWM, WDT Number of I/O 52 Program Memory Size 64KB (64K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 16K x 8
Core Size 32-Bit Speed 50MHz Connectivity I2C, IrDA, Microwire, QEI, SPI, SSI, UART/USART Peripherals Brown-out Detect/Reset, POR, PWM, WDT Number of I/O 52 Program Memory Size 64KB (64K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 16K x 8
Speed 50MHz Connectivity I2C, IrDA, Microwire, QEI, SPI, SSI, UART/USART Peripherals Brown-out Detect/Reset, POR, PWM, WDT Number of I/O 52 Program Memory Size 64KB (64K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 16K x 8
Connectivity I2C, IrDA, Microwire, QEI, SPI, SSI, UART/USART Peripherals Brown-out Detect/Reset, POR, PWM, WDT Number of I/O 52 Program Memory Size 64KB (64K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 16K x 8
Peripherals Brown-out Detect/Reset, POR, PWM, WDT Number of I/O 52 Program Memory Size 64KB (64K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 16K x 8
Number of I/O 52 Program Memory Size 64KB (64K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 16K x 8
Program Memory Size 64KB (64K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 16K x 8
Program Memory Type FLASH EEPROM Size - RAM Size 16K x 8
EEPROM Size - RAM Size 16K x 8
RAM Size 16K x 8
Voltage - Supply (Vcc/Vdd) $2.25 \text{ V} \sim 2.75 \text{ V}$
Data Converters -
Oscillator Type Internal
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C} \text{ (TA)}$
Mounting Type -
Package / Case 108-LFBGA
Supplier Device Package 108-BGA (10x10)
Report error

LM3S1150-IBZ50-A2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LM3S1150-IBZ50-A2 Payment Methods



















LM3S1150-IBZ50-A2 Shipping Methods













If you have any question about LM3S1150-IBZ50-A2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com