



LM3S1968-IBZ50-A2 Information



For Reference Only

Part Number LM3S1968-IBZ50-A2

Manufacturer Texas Instruments

Category Integrated Circuits (ICs)
Embedded - Microcontrollers

Description IC MCU 32BIT 256KB FLASH 108BGA

Package 108-LFBGA

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LM3S1968-IBZ50-A2 Specifications

Manufacturer Part NumberLM3S1968-IBZ50-A2ManufacturerTexas InstrumentsCategoryIntegrated Circuits (ICs)Embedded - MicrocontrollersPackage108-LFBGASeriesStellaris? ARM? Cortex?-M3S 1000Core ProcessorARM? Cortex?-M3Core Size32-BitSpeed50MHzConnectivityI2C, IrDA, Microwire, QEI, SPI, SSI, UART/USARTPeripheralsBrown-out Detect/Reset, POR, PWM, WDTNumber of I/O52Program Memory Size256KB (256K x 8)Program Memory TypeFLASHEEPROM Size-RAM Size64K x 8Voltage - Supply (Vcc/Vdd)2.25 V ~ 2.75 VData ConvertersA/D 8x10b
Category Integrated Circuits (ICs) Embedded - Microcontrollers Package 108-LFBGA Series Stellaris? ARM? Cortex?-M3S 1000 Core Processor ARM? Cortex?-M3 Core Size 32-Bit Speed 50MHz Connectivity 12C, IrDA, Microwire, QEI, SPI, SSI, UART/USART Peripherals Brown-out Detect/Reset, POR, PWM, WDT Number of I/O 52 Program Memory Size 256KB (256K x 8) Program Memory Type FLASH EEPROM Size RAM Size 64K x 8 Voltage - Supply (Vcc/Vdd) 2.25 V ~ 2.75 V
Embedded - Microcontrollers Package 108-LFBGA Series Stellaris? ARM? Cortex?-M3S 1000 Core Processor ARM? Cortex?-M3 Core Size 32-Bit Speed 50MHz Connectivity I2C, IrDA, Microwire, QEI, SPI, SSI, UART/USART Peripherals Brown-out Detect/Reset, POR, PWM, WDT Number of I/O 52 Program Memory Size 256KB (256K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 64K x 8 Voltage - Supply (Vcc/Vdd) 2.25 V ~ 2.75 V
Package 108-LFBGA Series Stellaris? ARM? Cortex?-M3S 1000 Core Processor ARM? Cortex?-M3 Core Size 32-Bit Speed 50MHz Connectivity I2C, IrDA, Microwire, QEI, SPI, SSI, UART/USART Peripherals Brown-out Detect/Reset, POR, PWM, WDT Number of I/O 52 Program Memory Size 256KB (256K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 64K x 8 Voltage - Supply (Vcc/Vdd) 2.25 V ~ 2.75 V
Series Stellaris? ARM? Cortex?-M3S 1000 Core Processor ARM? Cortex?-M3 Core Size 32-Bit Speed 50MHz Connectivity I2C, IrDA, Microwire, QEI, SPI, SSI, UART/USART Peripherals Brown-out Detect/Reset, POR, PWM, WDT Number of I/O 52 Program Memory Size 256KB (256K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 64K x 8 Voltage - Supply (Vcc/Vdd) 2.25 V ~ 2.75 V
Core Processor Core Size 32-Bit Speed 50MHz Connectivity I2C, IrDA, Microwire, QEI, SPI, SSI, UART/USART Peripherals Brown-out Detect/Reset, POR, PWM, WDT Number of I/O 52 Program Memory Size 256KB (256K x 8) Program Memory Type FLASH EEPROM Size RAM Size 64K x 8 Voltage - Supply (Vcc/Vdd) 2.25 V ~ 2.75 V
Core Size 32-Bit Speed 50MHz Connectivity I2C, IrDA, Microwire, QEI, SPI, SSI, UART/USART Peripherals Brown-out Detect/Reset, POR, PWM, WDT Number of I/O 52 Program Memory Size 256KB (256K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 64K x 8 Voltage - Supply (Vcc/Vdd) 2.25 V ~ 2.75 V
Speed 50MHz Connectivity I2C, IrDA, Microwire, QEI, SPI, SSI, UART/USART Peripherals Brown-out Detect/Reset, POR, PWM, WDT Number of I/O 52 Program Memory Size 256KB (256K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 64K x 8 Voltage - Supply (Vcc/Vdd) 2.25 V ~ 2.75 V
Connectivity I2C, IrDA, Microwire, QEI, SPI, SSI, UART/USART Brown-out Detect/Reset, POR, PWM, WDT Number of I/O 52 Program Memory Size 256KB (256K x 8) Program Memory Type FLASH EEPROM Size RAM Size 64K x 8 Voltage - Supply (Vcc/Vdd) 2.25 V ~ 2.75 V
Peripherals Brown-out Detect/Reset, POR, PWM, WDT Number of I/O 52 Program Memory Size 256KB (256K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 64K x 8 Voltage - Supply (Vcc/Vdd) 2.25 V ~ 2.75 V
Number of I/O 52 Program Memory Size 256KB (256K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 64K x 8 Voltage - Supply (Vcc/Vdd) 2.25 V ~ 2.75 V
Program Memory Size 256KB (256K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 64K x 8 Voltage - Supply (Vcc/Vdd) 2.25 V ~ 2.75 V
Program Memory Type FLASH EEPROM Size - RAM Size 64K x 8 Voltage - Supply (Vcc/Vdd) 2.25 V ~ 2.75 V
EEPROM Size - RAM Size 64K x 8 Voltage - Supply (Vcc/Vdd) 2.25 V ~ 2.75 V
RAM Size $64K \times 8$ Voltage - Supply (Vcc/Vdd) $2.25 \text{ V} \sim 2.75 \text{ V}$
Voltage - Supply (Vcc/Vdd) 2.25 V ~ 2.75 V
Data Convertors A/D 8v10h
Data Converters A/D 6x100
Oscillator Type Internal
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C} \text{ (TA)}$
Mounting Type -
Package / Case 108-LFBGA
Supplier Device Package 108-BGA (10x10)
Report error

LM3S1968-IBZ50-A2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LM3S1968-IBZ50-A2 Payment Methods



















LM3S1968-IBZ50-A2 Shipping Methods













If you have any question about LM3S1968-IBZ50-A2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com