

LM3S1N11-IBZ50-C5T

LM3S1N11-IBZ50-C5T Information



For Reference Only

Part Number LM3S1N11-IBZ50-C5T

Manufacturer Texas Instruments

Category Integrated Circuits (ICs)
Embedded - Microcontrollers

Description IC MCU 32BIT 64KB FLASH 108BGA

Package 108-LFBGA

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LM3S1N11-IBZ50-C5T Specifications

Manufacturer Part Number Manufacturer Category Integrated Circuits (ICs) Embedded - Microcontrollers Package 108-LFBGA Series Stellaris? ARM? Cortex?-M3S 1000 Core Processor Core Size 32-Bit Speed Connectivity I2C, IrDA, LIN, Microwire, SPI, SSI, UART/USART Peripherals Brown-out Detect/Reset, DMA, POR, PWM, WDT Number of I/O Program Memory Size 64KB (64K x 8) Program Memory Type FLASH EEPROM Size RAM Size Voltage - Supply (Vcc/Vdd) 1ne Maioroutis (ICs) Embedded - Microcontrollers 108-LFBGA Stellaris? ARM? Cortex?-M3S 1000 ARM? Cortex?-M3S 1000 ARM? Cortex?-M3 Stellaris? ARM? Cortex?-M3S 1000 ARM? Cortex?
Category Integrated Circuits (ICs) Embedded - Microcontrollers Package 108-LFBGA Series Stellaris? ARM? Cortex?-M3S 1000 Core Processor ARM? Cortex?-M3 Core Size 32-Bit Speed 50MHz Connectivity I2C, IrDA, LIN, Microwire, SPI, SSI, UART/USART Peripherals Brown-out Detect/Reset, DMA, POR, PWM, WDT Number of I/O Program Memory Size 64KB (64K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 12K x 8
Embedded - Microcontrollers Package 108-LFBGA Series Stellaris? ARM? Cortex?-M3S 1000 Core Processor ARM? Cortex?-M3 Core Size 32-Bit Speed 50MHz Connectivity I2C, IrDA, LIN, Microwire, SPI, SSI, UART/USART Peripherals Brown-out Detect/Reset, DMA, POR, PWM, WDT Number of I/O 67 Program Memory Size 64KB (64K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 12K x 8
Package 108-LFBGA Series Stellaris? ARM? Cortex?-M3S 1000 Core Processor ARM? Cortex?-M3 Core Size 32-Bit Speed 50MHz Connectivity I2C, IrDA, LIN, Microwire, SPI, SSI, UART/USART Peripherals Brown-out Detect/Reset, DMA, POR, PWM, WDT Number of I/O 67 Program Memory Size 64KB (64K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 12K x 8
Series Stellaris? ARM? Cortex?-M3S 1000 Core Processor ARM? Cortex?-M3 Core Size 32-Bit Speed 50MHz Connectivity I2C, IrDA, LIN, Microwire, SPI, SSI, UART/USART Peripherals Brown-out Detect/Reset, DMA, POR, PWM, WDT Number of I/O 67 Program Memory Size 64KB (64K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 12K x 8
Core Processor Core Size 32-Bit Speed 50MHz Connectivity I2C, IrDA, LIN, Microwire, SPI, SSI, UART/USART Peripherals Brown-out Detect/Reset, DMA, POR, PWM, WDT Number of I/O 67 Program Memory Size 64KB (64K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 12K x 8
Core Size 32-Bit Speed 50MHz Connectivity I2C, IrDA, LIN, Microwire, SPI, SSI, UART/USART Peripherals Brown-out Detect/Reset, DMA, POR, PWM, WDT Number of I/O 67 Program Memory Size 64KB (64K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 12K x 8
Speed 50MHz Connectivity I2C, IrDA, LIN, Microwire, SPI, SSI, UART/USART Peripherals Brown-out Detect/Reset, DMA, POR, PWM, WDT Number of I/O 67 Program Memory Size 64KB (64K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 12K x 8
Connectivity I2C, IrDA, LIN, Microwire, SPI, SSI, UART/USART Peripherals Brown-out Detect/Reset, DMA, POR, PWM, WDT Number of I/O Program Memory Size 64KB (64K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 12K x 8
Peripherals Brown-out Detect/Reset, DMA, POR, PWM, WDT Number of I/O Program Memory Size 64KB (64K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 12K x 8
Number of I/O 67 Program Memory Size 64KB (64K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 12K x 8
Program Memory Size 64KB (64K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 12K x 8
Program Memory Type FLASH EEPROM Size - RAM Size 12K x 8
EEPROM Size - RAM Size 12K x 8
RAM Size 12K x 8
Voltage Cumby (Vog Wid) 100 W 26 W
Voltage - Supply (Vcc/Vdd) $1.08 \text{ V} \sim 3.6 \text{ V}$
Data Converters A/D 8x10b
Oscillator Type Internal
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C} \text{ (TA)}$
Mounting Type -
Package / Case 108-LFBGA
Supplier Device Package 108-BGA (10x10)
Report error

LM3S1N11-IBZ50-C5T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LM3S1N11-IBZ50-C5T Payment Methods



















LM3S1N11-IBZ50-C5T Shipping Methods













If you have any question about LM3S1N11-IBZ50-C5T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com