



### LM4040CIX3-4.1+T Information



For Reference Only

Part Number LM4040CIX3-4.1+T

Manufacturer Maxim Integrated

Category Integrated Circuits (ICs)
PMIC - Voltage Reference

Description IC VREF SHUNT 4.096V SC70

**Description** IC VREF SHUNT **Package** SC-70, SOT-323

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# LM4040CIX3-4.1+T Specifications

Manufacturer Part Number         LM4040CIX3-4.1+T           Manufacturer         Maxim Integrated           Category         Integrated Circuits (ICs)           PMIC - Voltage Reference           Package         SC-70, SOT-323           Series         -           Reference Type         Shunt           Output Type         Fixed           Voltage - Output (Min/Fixed)         4.096V           Voltage - Output (Max)         -           Current - Output         15mA           Tolerance         ±0.5%           Temperature Coefficient         100ppm/°C           Noise - 0.1Hz to 10Hz         64µVrms           Voltage - Input         -           Current - Supply         -           Current - Supply         -           Operating Temperature         40°C ~ 85°C (TA)           Mounting Type         Surface Mount           Package / Case         SC-70, SOT-323           Supplier Device Package         SC-70-3		
Category         Integrated Circuits (ICs)           PMIC - Voltage Reference           Package         SC-70, SOT-323           Series         -           Reference Type         Shunt           Output Type         Fixed           Voltage - Output (Min/Fixed)         4.096V           Voltage - Output (Max)         -           Current - Output         15mA           Tolerance         ±0.5%           Temperature Coefficient         100ppm/°C           Noise - 0.1Hz to 10Hz         -           Noise - 10Hz to 10kHz         64μVrms           Voltage - Input         -           Current - Supply         -           Current - Cathode         73μA           Operating Temperature         -40°C ~ 85°C (TA)           Mounting Type         Surface Mount           Package / Case         SC-70, SOT-323           Supplier Device Package         SC-70-3	Manufacturer Part Number	LM4040CIX3-4.1+T
Package         SC-70, SOT-323           Series         -           Reference Type         Shunt           Output Type         Fixed           Voltage - Output (Min/Fixed)         4.096 V           Voltage - Output (Max)         -           Current - Output         15mA           Tolerance         ±0.5%           Temperature Coefficient         100ppm/°C           Noise - 0.1Hz to 10Hz         -           Noise - 10Hz to 10kHz         64μVrms           Voltage - Input         -           Current - Supply         -           Current - Cathode         73μA           Operating Temperature         -40°C ~ 85°C (TA)           Mounting Type         Surface Mount           Package / Case         SC-70, SOT-323           Supplier Device Package         SC-70-3	Manufacturer	Maxim Integrated
Package         SC-70, SOT-323           Series         -           Reference Type         Shunt           Output Type         Fixed           Voltage - Output (Min/Fixed)         4.096V           Voltage - Output (Max)         -           Current - Output         15mA           Tolerance         ±0.5%           Temperature Coefficient         100ppm/°C           Noise - 0.1Hz to 10Hz         -           Noise - 10Hz to 10kHz         64μVrms           Voltage - Input         -           Current - Supply         -           Current - Cathode         73μA           Operating Temperature         -40°C ~ 85°C (TA)           Mounting Type         Surface Mount           Package / Case         SC-70, SOT-323           Supplier Device Package         SC-70-3	Category	Integrated Circuits (ICs)
Series         -           Reference Type         Shunt           Output Type         Fixed           Voltage - Output (Min/Fixed)         4.096V           Voltage - Output (Max)         -           Current - Output         15mA           Tolerance         ±0.5%           Temperature Coefficient         100ppm/°C           Noise - 0.1Hz to 10Hz         -           Noise - 10Hz to 10kHz         64µVrms           Voltage - Input         -           Current - Supply         -           Current - Cathode         73µA           Operating Temperature         -40°C ~ 85°C (TA)           Mounting Type         Surface Mount           Package / Case         SC-70, SOT-323           Supplier Device Package         SC-70-3		PMIC - Voltage Reference
Reference Type         Shunt           Output Type         Fixed           Voltage - Output (Min/Fixed)         4.096V           Voltage - Output (Max)         -           Current - Output         15mA           Tolerance         ±0.5%           Temperature Coefficient         100ppm/°C           Noise - 0.1Hz to 10Hz         -           Noise - 10Hz to 10kHz         64μVrms           Voltage - Input         -           Current - Supply         -           Current - Cathode         73μA           Operating Temperature         -40°C ~ 85°C (TA)           Mounting Type         Surface Mount           Package / Case         SC-70, SOT-323           Supplier Device Package         SC-70-3	Package	SC-70, SOT-323
Output Type Fixed  Voltage - Output (Min/Fixed) 4.096V  Voltage - Output (Max) - Current - Output 15mA  Tolerance ±0.5%  Temperature Coefficient 100ppm/°C  Noise - 0.1Hz to 10Hz - Noise - 10Hz to 10kHz 64µVrms  Voltage - Input - Current - Supply - Current - Cathode 73µA  Operating Temperature -40°C ~ 85°C (TA)  Mounting Type Surface Mount  Package / Case SC-70, SOT-323  Supplier Device Package	Series	-
Voltage - Output (Min/Fixed)4.096VVoltage - Output (Max)-Current - Output15mATolerance±0.5%Temperature Coefficient100ppm/°CNoise - 0.1Hz to 10Hz-Noise - 10Hz to 10kHz64μVrmsVoltage - Input-Current - Supply-Current - Cathode73μAOperating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseSC-70, SOT-323Supplier Device PackageSC-70-3	Reference Type	Shunt
Voltage - Output (Max)-Current - Output15mATolerance±0.5%Temperature Coefficient100ppm/°CNoise - 0.1Hz to 10Hz-Noise - 10Hz to 10kHz64μVrmsVoltage - Input-Current - Supply-Current - Cathode73μAOperating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseSC-70, SOT-323Supplier Device PackageSC-70-3	Output Type	Fixed
Current - Output15mATolerance±0.5%Temperature Coefficient100ppm/°CNoise - 0.1Hz to 10Hz-Noise - 10Hz to 10kHz64μVrmsVoltage - Input-Current - Supply-Current - Cathode73μAOperating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseSC-70, SOT-323Supplier Device PackageSC-70-3	Voltage - Output (Min/Fixed)	4.096V
Tolerance±0.5%Temperature Coefficient100ppm/°CNoise - 0.1Hz to 10Hz-Noise - 10Hz to 10kHz64μVrmsVoltage - Input-Current - Supply-Current - Cathode73μAOperating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseSC-70, SOT-323Supplier Device PackageSC-70-3	Voltage - Output (Max)	-
Temperature Coefficient  Noise - 0.1Hz to 10Hz  Noise - 10Hz to 10kHz  64μVrms  Voltage - Input  - Current - Supply  - Current - Cathode  73μA  Operating Temperature  40°C ~ 85°C (TA)  Mounting Type  Surface Mount  Package / Case  SC-70, SOT-323  Supplier Device Package	Current - Output	15mA
Noise - 0.1Hz to 10Hz-Noise - 10Hz to 10kHz64μVrmsVoltage - Input-Current - Supply-Current - Cathode73μAOperating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseSC-70, SOT-323Supplier Device PackageSC-70-3	Tolerance	±0.5%
Noise - 10Hz to 10kHz64μVrmsVoltage - Input-Current - Supply-Current - Cathode73μAOperating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseSC-70, SOT-323Supplier Device PackageSC-70-3	Temperature Coefficient	100ppm/°C
Voltage - Input  Current - Supply  - Current - Cathode  73μA  Operating Temperature  -40°C ~ 85°C (TA)  Mounting Type  Surface Mount  Package / Case  SC-70, SOT-323  Supplier Device Package	Noise - 0.1Hz to 10Hz	-
Current - Supply-Current - Cathode $73\mu A$ Operating Temperature $-40^{\circ}C \sim 85^{\circ}C$ (TA)Mounting TypeSurface MountPackage / CaseSC-70, SOT-323Supplier Device PackageSC-70-3	Noise - 10Hz to 10kHz	64μVrms
Current - Cathode $73\mu A$ Operating Temperature $-40^{\circ}C \sim 85^{\circ}C$ (TA)  Mounting Type Surface Mount  Package / Case SC-70, SOT-323  Supplier Device Package SC-70-3	Voltage - Input	-
Operating Temperature  -40°C ~ 85°C (TA)  Mounting Type  Surface Mount  Package / Case  SC-70, SOT-323  Supplier Device Package  SC-70-3	Current - Supply	-
Mounting TypeSurface MountPackage / CaseSC-70, SOT-323Supplier Device PackageSC-70-3	Current - Cathode	73μΑ
Package / Case SC-70, SOT-323 Supplier Device Package SC-70-3	Operating Temperature	-40°C ~ 85°C (TA)
Supplier Device Package SC-70-3	Mounting Type	Surface Mount
	Package / Case	SC-70, SOT-323
Report errors?	Supplier Device Package	SC-70-3
		Report errors?

#### LM4040CIX3-4.1+T Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## LM4040CIX3-4.1+T Payment Methods





















## LM4040CIX3-4.1+T Shipping Methods













If you have any question about LM4040CIX3-4.1+T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com