



LM4040D33FTA Information

Heisener.com

Part Number LM4040D33FTA

Manufacturer Diodes Incorporated

Category Integrated Circuits (ICs)
PMIC - Voltage Reference

Description VREG SHUNT REFERENCE SSOT23

Package TO-236-3, SC-59, SOT-23-3

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LM4040D33FTA Specifications

Manufacturer Part Number LM4040D33FTA Manufacturer Diodes Incorporated Category Integrated Circuits (ICs) PMIC - Voltage Reference Package TO-236-3, SC-59, SOT-23-3 Series - Reference Type Shunt Output Type Fixed Voltage - Output (Min/Fixed) 3.3V Voltage - Output (Max) - Current - Output 15mA Tolerance ±1% Temperature Coefficient - Noise - 0.1Hz to 10Hz - Noise - 10Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode - Operating Temperature -40°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23		
Category Integrated Circuits (ICs) PMIC - Voltage Reference Package TO-236-3, SC-59, SOT-23-3 Series - Reference Type Shunt Output Type Fixed Voltage - Output (Min/Fixed) 3.3V Voltage - Output (Max) - Current - Output 15mA Tolerance ±1% Temperature Coefficient - Noise - 0.1Hz to 10Hz - Noise - 10Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode - Operating Temperature 440°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23	Manufacturer Part Number	LM4040D33FTA
Package TO-236-3, SC-59, SOT-23-3 Series - Reference Type Shunt Output Type Fixed Voltage - Output (Min/Fixed) 3.3V Voltage - Output (Max) - Current - Output 15mA Tolerance ±1% Temperature Coefficient - Noise - 0.1Hz to 10Hz - Noise - 10Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode - Operating Temperature -40°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23	Manufacturer	Diodes Incorporated
Package TO-236-3, SC-59, SOT-23-3 Series - Reference Type Shunt Output Type Fixed Voltage - Output (Min/Fixed) 3.3V Voltage - Output (Max) - Current - Output 15mA Tolerance ±1% Temperature Coefficient - Noise - 0.1Hz to 10Hz - Noise - 10Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode - Operating Temperature -40°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23	Category	Integrated Circuits (ICs)
Series - Reference Type Shunt Output Type Fixed Voltage - Output (Min/Fixed) 3.3V Voltage - Output (Max) - Current - Output 15mA Tolerance ±1% Temperature Coefficient - Noise - 0.1Hz to 10Hz - Noise - 10Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode - Operating Temperature -40°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23		PMIC - Voltage Reference
Reference TypeShuntOutput TypeFixedVoltage - Output (Min/Fixed)3.3VVoltage - Output (Max)-Current - Output15mATolerance±1%Temperature Coefficient-Noise - 0.1Hz to 10Hz-Noise - 10Hz to 10kHz-Voltage - Input-Current - Supply-Current - Cathode-Operating Temperature-40°C ~ 125°C (TA)Mounting TypeSurface MountPackage / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackageSOT-23	Package	TO-236-3, SC-59, SOT-23-3
Output Type Fixed Voltage - Output (Min/Fixed) 3.3V Voltage - Output (Max) - Current - Output 15mA Tolerance ±1% Temperature Coefficient - Noise - 0.1Hz to 10Hz Noise - 10Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode - Operating Temperature Operating Temperature Mounting Type Surface Mount Package / Case SOT-23	Series	-
Voltage - Output (Min/Fixed) Voltage - Output (Max) Current - Output 15mA Tolerance ±1% Temperature Coefficient Noise - 0.1Hz to 10Hz Noise - 10Hz to 10kHz Voltage - Input Current - Supply Current - Cathode Operating Temperature Operating Temperature August Aug	Reference Type	Shunt
Voltage - Output (Max) Current - Output 15mA Tolerance ±1% Temperature Coefficient Noise - 0.1Hz to 10Hz Noise - 10Hz to 10kHz Voltage - Input Current - Supply Current - Cathode Operating Temperature Mounting Type Surface Mount Package / Case Supplier Device Package	Output Type	Fixed
Current - Output 15mA Tolerance ±1% Temperature Coefficient - Noise - 0.1Hz to 10Hz - Noise - 10Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode - Operating Temperature -40°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23	Voltage - Output (Min/Fixed)	3.3V
Tolerance ±1% Temperature Coefficient - Noise - 0.1Hz to 10Hz - Noise - 10Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode - Operating Temperature -40°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package	Voltage - Output (Max)	-
Temperature Coefficient Noise - 0.1Hz to 10Hz Noise - 10Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode Operating Temperature Mounting Type Surface Mount Package / Case Supplier Device Package - One Compensation of the package of the packag	Current - Output	15mA
Noise - 0.1Hz to 10Hz Noise - 10Hz to 10kHz Voltage - Input Current - Supply Current - Cathode Operating Temperature Operating Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package	Tolerance	±1%
Noise - 10Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode - Operating Temperature -40°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23	Temperature Coefficient	-
Voltage - Input Current - Supply - Current - Cathode Operating Temperature -40°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package	Noise - 0.1Hz to 10Hz	-
Current - Supply Current - Cathode Operating Temperature -40°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package	Noise - 10Hz to 10kHz	-
Current - Cathode Operating Temperature -40°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23	Voltage - Input	-
Operating Temperature-40°C ~ 125°C (TA)Mounting TypeSurface MountPackage / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackageSOT-23	Current - Supply	-
Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23	Current - Cathode	-
Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23	Operating Temperature	-40°C ~ 125°C (TA)
Supplier Device Package SOT-23	Mounting Type	Surface Mount
	Package / Case	TO-236-3, SC-59, SOT-23-3
Report errors?	Supplier Device Package	SOT-23
		Report errors?

LM4040D33FTA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LM4040D33FTA Payment Methods



















LM4040D33FTA Shipping Methods













If you have any question about LM4040D33FTA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com