



## LM4120IM5X-3.3 Information



For Reference Only

Part Number LM4120IM5X-3.3

Manufacturer Texas Instruments

Category Integrated Circuits (ICs)
PMIC - Voltage Reference

**Description** IC VREF SERIES 3.3V SOT23-5

Package SC-74A, SOT-753

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## LM4120IM5X-3.3 Specifications

Manufacturer Part Number         LM4120IM5X-3.3           Manufacturer         Texas Instruments           Category         Integrated Circuits (ICs)           Package         SC-74A, SOT-753           Series         -           Reference Type         Series           Output Type         Fixed           Voltage - Output (Min/Fixed)         3.3V           Voltage - Output (Max)         -           Current - Output         5mA           Tolerance         ±0.5%           Temperature Coefficient         50pm/°C           Noise - 0.1Hz to 10Hz         20µVp-p           Noise - 10Hz to 10kHz         36µVp-p           Voltage - Input         2 V ~ 12 V           Current - Supply         275µA           Current - Cathode         -           Operating Temperature         40°C ~ 85°C (TA)           Mounting Type         Surface Mount           Package / Case         SC-74A, SOT-753           Supplier Device Package         SOT-23-5		
Category         Integrated Circuits (ICs)           PMIC - Voltage Reference           Package         SC-74A, SOT-753           Series         -           Reference Type         Series           Output Type         Fixed           Voltage - Output (Min/Fixed)         3.3V           Voltage - Output (Max)         -           Current - Output         5mA           Tolerance         ±0.5%           Temperature Coefficient         50ppm/°C           Noise - 0.1Hz to 10Hz         20μVp-p           Noise - 10Hz to 10kHz         36μVp-p           Voltage - Input         2 V ~ 12 V           Current - Supply         275μA           Current - Cathode         -           Operating Temperature         -40°C ~ 85°C (TA)           Mounting Type         Surface Mount           Package / Case         SC-74A, SOT-753           Supplier Device Package         SOT-23-5	Manufacturer Part Number	LM4120IM5X-3.3
Package         SC-74A, SOT-753           Series         -           Reference Type         Series           Output Type         Fixed           Voltage - Output (Min/Fixed)         3.3V           Voltage - Output (Max)         -           Current - Output         5mA           Tolerance         ±0.5%           Temperature Coefficient         50ppm/°C           Noise - 0.1Hz to 10Hz         20μVp-p           Noise - 10Hz to 10kHz         36μVp-p           Voltage - Input         2 V ~ 12 V           Current - Supply         275μA           Current - Cathode         -           Operating Temperature         -40°C ~ 85°C (TA)           Mounting Type         Surface Mount           Package / Case         SC-74A, SOT-753           Supplier Device Package         SOT-23-5	Manufacturer	Texas Instruments
Package         SC-74A, SOT-753           Series         -           Reference Type         Series           Output Type         Fixed           Voltage - Output (Min/Fixed)         3.3V           Voltage - Output (Max)         -           Current - Output         5mA           Tolerance         ±0.5%           Temperature Coefficient         50ppm/°C           Noise - 0.1Hz to 10Hz         20μVp-p           Noise - 10Hz to 10kHz         36μVp-p           Voltage - Input         2 V ~ 12 V           Current - Supply         275μA           Current - Cathode         -           Operating Temperature         40°C ~ 85°C (TA)           Mounting Type         Surface Mount           Package / Case         SC-74A, SOT-753           Supplier Device Package         SOT-23-5	Category	Integrated Circuits (ICs)
Series         -           Reference Type         Series           Output Type         Fixed           Voltage - Output (Min/Fixed)         3.3V           Voltage - Output (Max)         -           Current - Output         5mA           Tolerance         ±0.5%           Temperature Coefficient         50ppm/°C           Noise - 0.1Hz to 10Hz         20μVp-p           Noise - 10Hz to 10kHz         36μVp-p           Voltage - Input         2 V ~ 12 V           Current - Supply         275μA           Current - Cathode         -           Operating Temperature         -40°C ~ 85°C (TA)           Mounting Type         Surface Mount           Package / Case         SC-74A, SOT-753           Supplier Device Package         SOT-23-5		PMIC - Voltage Reference
Reference TypeSeriesOutput TypeFixedVoltage - Output (Min/Fixed)3.3VVoltage - Output (Max)-Current - Output5mATolerance±0.5%Temperature Coefficient50ppm/°CNoise - 0.1Hz to 10Hz20μVp-pNoise - 10Hz to 10kHz36μVp-pVoltage - Input2 V ~ 12 VCurrent - Supply275μACurrent - Cathode-Operating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseSC-74A, SOT-753Supplier Device PackageSOT-23-5	Package	SC-74A, SOT-753
Output TypeFixedVoltage - Output (Min/Fixed)3.3VVoltage - Output (Max)-Current - Output5mATolerance±0.5%Temperature Coefficient50ppm/°CNoise - 0.1Hz to 10Hz20μVp-pNoise - 10Hz to 10kHz36μVp-pVoltage - Input2 V ~ 12 VCurrent - Supply275μACurrent - Cathode-Operating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseSC-74A, SOT-753Supplier Device PackageSOT-23-5	Series	-
Voltage - Output (Min/Fixed)  Voltage - Output (Max)  Current - Output  5mA  Tolerance ±0.5%  Temperature Coefficient 50ppm/°C  Noise - 0.1Hz to 10Hz 20μVp-p  Noise - 10Hz to 10kHz 36μVp-p  Voltage - Input 2 V ~ 12 V  Current - Supply  Current - Cathode Operating Temperature  -40°C ~ 85°C (TA)  Mounting Type Surface Mount  Package / Case SC-74A, SOT-753  Supplier Device Package	Reference Type	Series
Voltage - Output (Max)-Current - Output5mATolerance±0.5%Temperature Coefficient50ppm/°CNoise - 0.1Hz to 10Hz20μVp-pNoise - 10Hz to 10kHz36μVp-pVoltage - Input2 V ~ 12 VCurrent - Supply275μACurrent - Cathode-Operating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseSC-74A, SOT-753Supplier Device PackageSOT-23-5	Output Type	Fixed
Current - Output $5mA$ Tolerance $\pm 0.5\%$ Temperature Coefficient $50ppm/^{\circ}C$ Noise - $0.1Hz$ to $10Hz$ $20\mu Vp-p$ Noise - $10Hz$ to $10kHz$ $36\mu Vp-p$ Voltage - Input $2 V \sim 12 V$ Current - Supply $275\mu A$ Current - Cathode-Operating Temperature $-40^{\circ}C \sim 85^{\circ}C$ (TA)Mounting TypeSurface MountPackage / CaseSC-74A, SOT-753Supplier Device PackageSOT-23-5	Voltage - Output (Min/Fixed)	3.3V
Tolerance $\pm 0.5\%$ Temperature Coefficient $50ppm/^{\circ}C$ Noise - 0.1Hz to 10Hz $20\mu Vp$ -p  Noise - 10Hz to 10kHz $36\mu Vp$ -p  Voltage - Input $2V \sim 12V$ Current - Supply $275\mu A$ Current - Cathode -  Operating Temperature $-40^{\circ}C \sim 85^{\circ}C$ (TA)  Mounting Type Surface Mount  Package / Case $SC-74A$ , $SOT-753$ Supplier Device Package	Voltage - Output (Max)	-
Temperature Coefficient $50ppm/^{\circ}C$ Noise - 0.1Hz to 10Hz $20\mu Vp-p$ Noise - 10Hz to 10kHz $36\mu Vp-p$ Voltage - Input $2 V \sim 12 V$ Current - Supply $275\mu A$ Current - Cathode-Operating Temperature $-40^{\circ}C \sim 85^{\circ}C$ (TA)Mounting TypeSurface MountPackage / CaseSC-74A, SOT-753Supplier Device PackageSOT-23-5	Current - Output	5mA
Noise - 0.1Hz to 10Hz $20\mu Vp-p$ Noise - 10Hz to 10kHz $36\mu Vp-p$ Voltage - Input $2 V \sim 12 V$ Current - Supply $275\mu A$ Current - Cathode-Operating Temperature $-40^{\circ}C \sim 85^{\circ}C$ (TA)Mounting TypeSurface MountPackage / CaseSC-74A, SOT-753Supplier Device PackageSOT-23-5	Tolerance	±0.5%
Noise - 10Hz to 10kHz $36\mu Vp-p$ $2 V \sim 12 V$ Current - Supply $275\mu A$ Current - Cathode - Qperating Temperature $-40^{\circ}C \sim 85^{\circ}C$ (TA) Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Supplier Device Package	Temperature Coefficient	50ppm/°C
Voltage - Input $2 \text{ V} \sim 12 \text{ V}$ Current - Supply $275\mu\text{A}$ Current - Cathode-Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ (TA)Mounting TypeSurface MountPackage / CaseSC-74A, SOT-753Supplier Device PackageSOT-23-5	Noise - 0.1Hz to 10Hz	$20\mu Vp$ -p
Current - Supply275μACurrent - Cathode-Operating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseSC-74A, SOT-753Supplier Device PackageSOT-23-5	Noise - 10Hz to 10kHz	36μVp-p
Current - Cathode - Operating Temperature -40°C ~ 85°C (TA)  Mounting Type Surface Mount  Package / Case SC-74A, SOT-753  Supplier Device Package SOT-23-5	Voltage - Input	2 V ~ 12 V
Operating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseSC-74A, SOT-753Supplier Device PackageSOT-23-5	Current - Supply	275μΑ
Mounting TypeSurface MountPackage / CaseSC-74A, SOT-753Supplier Device PackageSOT-23-5	Current - Cathode	-
Package / Case SC-74A, SOT-753 Supplier Device Package SOT-23-5	Operating Temperature	-40°C ~ 85°C (TA)
Supplier Device Package SOT-23-5	Mounting Type	Surface Mount
	Package / Case	SC-74A, SOT-753
Report errors?	Supplier Device Package	SOT-23-5
		Report errors?

#### LM4120IM5X-3.3 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### LM4120IM5X-3.3 Payment Methods



















### LM4120IM5X-3.3 Shipping Methods













If you have any question about LM4120IM5X-3.3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com