



LM4128DMF-4.1 Information



For Reference Only

Part Number LM4128DMF-4.1

Manufacturer Texas Instruments

Category Integrated Circuits (ICs)
PMIC - Voltage Reference

Description IC VREF SERIES 4.096V SOT23-5

Package SC-74A, SOT-753

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LM4128DMF-4.1 Specifications

Manufacturer Part Number LM4128DMF-4.1 Manufacturer Texas Instruments Category Integrated Circuits (ICs) PMIC - Voltage Reference Package SC-74A, SOT-753 Series - Reference Type Series Output Type Fixed Voltage - Output (Min/Fixed) 4.096V Voltage - Output (Max) - Current - Output 20mA Tolerance ±1% Temperature Coefficient 100ppm/°C Noise - 0.1Hz to 10Hz 350μVp-p Noise - 10Hz to 10kHz - Voltage - Input 4.496 V ~ 5.5 V Current - Supply 100μA Current - Cathode - Operating Temperature -40°C ~ 125°C (TI) Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Supplier Device Package SOT-23-5		
Category Integrated Circuits (ICs) PMIC - Voltage Reference Package SC-74A, SOT-753 Series - Reference Type Series Output Type Fixed Voltage - Output (Min/Fixed) 4.096V Voltage - Output (Max) - Current - Output 20mA Tolerance ±1% Temperature Coefficient 100ppm/°C Noise - 0.1Hz to 10Hz 350μVp-p Noise - 10Hz to 10kHz - Voltage - Input 4.496 V ~ 5.5 V Current - Supply 100μA Current - Cathode - Operating Temperature -40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Supplier Device Package SOT-23-5	Manufacturer Part Number	LM4128DMF-4.1
Package SC-74A, SOT-753 Series - Reference Type Series Output Type Fixed Voltage - Output (Min/Fixed) 4.096V Voltage - Output (Max) - Current - Output 20mA Tolerance ±1% Temperature Coefficient 100ppm/°C Noise - 0.1Hz to 10Hz 350μVp-p Noise - 10Hz to 10kHz - Voltage - Input 4.496 V ~ 5.5 V Current - Supply 100μA Current - Cathode - Operating Temperature -40°C ~ 125°C (TI) Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Supplier Device Package SOT-23-5	Manufacturer	Texas Instruments
Package SC-74A, SOT-753 Series - Reference Type Series Output Type Fixed Voltage - Output (Min/Fixed) 4.096V Voltage - Output (Max) - Current - Output 20mA Tolerance ±1% Temperature Coefficient 100ppm/°C Noise - 0.1Hz to 10Hz 350μVp-p Noise - 10Hz to 10kHz - Voltage - Input 4.496 V ~ 5.5 V Current - Supply 100μA Current - Cathode - Operating Temperature -40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Supplier Device Package SOT-23-5	Category	Integrated Circuits (ICs)
Series - Reference Type Series Output Type Fixed Voltage - Output (Min/Fixed) 4.096V Voltage - Output (Max) - Current - Output 20mA Tolerance ±1% Temperature Coefficient 100ppm/°C Noise - 0.1Hz to 10Hz 350μVp-p Noise - 10Hz to 10kHz - Voltage - Input 4.496 V ~ 5.5 V Current - Supply 100μA Current - Cathode - Operating Temperature -40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Supplier Device Package SOT-23-5		PMIC - Voltage Reference
Reference TypeSeriesOutput TypeFixedVoltage - Output (Min/Fixed)4.096VVoltage - Output (Max)-Current - Output20mATolerance±1%Temperature Coefficient100ppm/°CNoise - 0.1Hz to 10Hz350μVp-pNoise - 10Hz to 10kHz-Voltage - Input4.496 V ~ 5.5 VCurrent - Supply100μACurrent - Cathode-Operating Temperature-40°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / CaseSC-74A, SOT-753Supplier Device PackageSOT-23-5	Package	SC-74A, SOT-753
Output TypeFixedVoltage - Output (Min/Fixed)4.096VVoltage - Output (Max)-Current - Output20mATolerance±1%Temperature Coefficient100ppm/°CNoise - 0.1Hz to 10Hz350μVp-pNoise - 10Hz to 10kHz-Voltage - Input4.496 V ~ 5.5 VCurrent - Supply100μACurrent - Cathode-Operating Temperature-40°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / CaseSC-74A, SOT-753Supplier Device PackageSOT-23-5	Series	-
Voltage - Output (Min/Fixed) 4.096V Voltage - Output (Max) - Current - Output 20mA Tolerance ±1% Temperature Coefficient 100ppm/°C Noise - 0.1Hz to 10Hz 350μVp-p Noise - 10Hz to 10kHz - Voltage - Input 4.496 V ~ 5.5 V Current - Supply 100μA Current - Cathode - Operating Temperature -40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Supplier Device Package SOT-23-5	Reference Type	Series
Voltage - Output (Max)-Current - Output20mATolerance±1%Temperature Coefficient100ppm/°CNoise - 0.1Hz to 10Hz350μVp-pNoise - 10Hz to 10kHz-Voltage - Input4.496 V ~ 5.5 VCurrent - Supply100μACurrent - Cathode-Operating Temperature-40°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / CaseSC-74A, SOT-753Supplier Device PackageSOT-23-5	Output Type	Fixed
Current - Output $20mA$ Tolerance $\pm 1\%$ Temperature Coefficient $100ppm/^{\circ}C$ Noise - $0.1Hz$ to $10Hz$ $350\mu Vp-p$ Noise - $10Hz$ to $10kHz$ -Voltage - Input $4.496 \text{ V} \sim 5.5 \text{ V}$ Current - Supply $100\mu A$ Current - Cathode-Operating Temperature $-40^{\circ}C \sim 125^{\circ}C$ (TJ)Mounting TypeSurface MountPackage / CaseSC-74A, SOT-753Supplier Device PackageSOT-23-5	Voltage - Output (Min/Fixed)	4.096V
Tolerance $\pm 1\%$ Temperature Coefficient $100 \text{ppm/}^{\circ}\text{C}$ Noise - 0.1Hz to 10Hz $350 \mu \text{Vp-p}$ Noise - 10Hz to 10kHz - Voltage - Input $4.496 \text{ V} \sim 5.5 \text{ V}$ Current - Supply $100 \mu \text{A}$ Current - Cathode - Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ (TJ) Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Supplier Device Package 50 SOT-23-5	Voltage - Output (Max)	-
Temperature Coefficient100ppm/°CNoise - 0.1Hz to 10Hz350μVp-pNoise - 10Hz to 10kHz-Voltage - Input4.496 V ~ 5.5 VCurrent - Supply100μACurrent - Cathode-Operating Temperature-40°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / CaseSC-74A, SOT-753Supplier Device PackageSOT-23-5	Current - Output	20mA
Noise - 0.1Hz to 10Hz $350\mu Vp-p$ $Noise - 10Hz to 10kHz \\ - Voltage - Input \\ - Uurrent - Supply \\ - Uurrent - Cathode \\ - Operating Temperature -40^{\circ}C \sim 125^{\circ}C (TJ) Mounting Type \\ - Surface Mount \\ - Package / Case \\ - Supplier Device Package SOT-23-5$	Tolerance	$\pm 1\%$
Noise - 10Hz to 10kHz-Voltage - Input4.496 V ~ 5.5 VCurrent - Supply100μACurrent - Cathode-Operating Temperature-40°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / CaseSC-74A, SOT-753Supplier Device PackageSOT-23-5	Temperature Coefficient	100ppm/°C
Voltage - Input $4.496 \text{ V} \sim 5.5 \text{ V}$ Current - Supply $100\mu\text{A}$ Current - Cathode-Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ (TJ)Mounting TypeSurface MountPackage / CaseSC-74A, SOT-753Supplier Device PackageSOT-23-5	Noise - 0.1Hz to 10Hz	350μVp-p
Current - Supply100μACurrent - Cathode-Operating Temperature-40°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / CaseSC-74A, SOT-753Supplier Device PackageSOT-23-5	Noise - 10Hz to 10kHz	-
Current - Cathode Operating Temperature -40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Supplier Device Package SOT-23-5	Voltage - Input	4.496 V ~ 5.5 V
Operating Temperature -40°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Supplier Device Package SOT-23-5	Current - Supply	100μΑ
Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Supplier Device Package SOT-23-5	Current - Cathode	-
Package / Case SC-74A, SOT-753 Supplier Device Package SOT-23-5	Operating Temperature	-40°C ~ 125°C (TJ)
Supplier Device Package SOT-23-5	Mounting Type	Surface Mount
	Package / Case	SC-74A, SOT-753
D	Supplier Device Package	SOT-23-5
Report errors?		Report errors?

LM4128DMF-4.1 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LM4128DMF-4.1 Payment Methods



















LM4128DMF-4.1 Shipping Methods













If you have any question about LM4128DMF-4.1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com