



LMH6658MAX Information



For Reference Only

Part Number LMH6658MAX
Manufacturer Texas Instruments
Category Integrated Circuits (ICs)

Linear - Amplifiers - Instrumentation, OP Amps,

Buffer Amps

Description IC OPAMP VFB 140MHZ 8SOIC **Package** 8-SOIC (0.154", 3.90mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LMH6658MAX Specifications

Manufacturer Part Number LMH6658MAX Manufacturer Texas Instruments Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-SOIC (0.154", 3.90mm Width) Series - Amplifier Type Voltage Feedback Number of Circuits 2 Output Type - Slew Rate 700 V/μs Gain Bandwidth Product 140MHz -3db Bandwidth 270MHz Current - Input Bias 5μA Voltage - Input Offset ImV Current - Supply 6.5mA Current - Output / Channel 110mA Voltage - Supply, Single/Dual (±) 3 V ~ 12 V, ±1.5 V ~ 6 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)		
Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-SOIC (0.154", 3.90mm Width) Series - Amplifier Type Voltage Feedback Number of Circuits 2 Output Type - Slew Rate 700 V/μs Gain Bandwidth Product 140MHz -3db Bandwidth 270MHz Current - Input Bias 5μA Voltage - Input Offset ImV Current - Supply 6.5mA Current - Output / Channel 110mA Voltage - Supply, Single/Dual (±) 3 V ~ 12 V, ±1.5 V ~ 6 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount	Manufacturer Part Number	LMH6658MAX
Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps 8-SOIC (0.154", 3.90mm Width) Series - Amplifier Type Voltage Feedback Number of Circuits 2 Output Type - Slew Rate 700 V/µs Gain Bandwidth Product -3db Bandwidth 270MHz Current - Input Bias 5µA Voltage - Input Offset ImV Current - Output / Channel Voltage - Supply, Single/Dual (±) Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount	Manufacturer	Texas Instruments
Package 8-SOIC (0.154", 3.90mm Width) Series - Amplifier Type Voltage Feedback Number of Circuits 2 Output Type - Slew Rate 700 V/ μ s Gain Bandwidth Product 140MHz -3db Bandwidth Current - Input Bias 5 μ A Voltage - Input Offset 1mV Current - Supply 6.5mA Current - Output / Channel 110mA Voltage - Supply, Single/Dual (\pm) 3 V ~ 12 V, \pm 1.5 V ~ 6 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount	Category	Integrated Circuits (ICs)
Series - Amplifier Type Voltage Feedback Number of Circuits 2 Output Type - Slew Rate 700 V/μs Gain Bandwidth Product 140MHz -3db Bandwidth Current - Input Bias 5μA Voltage - Input Offset 1mV Current - Supply 6.5mA Current - Output / Channel 110mA Voltage - Supply, Single/Dual (±) 3 V ~ 12 V, ±1.5 V ~ 6 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount		Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps
Amplifier Type Voltage Feedback Number of Circuits 2 Output Type - Slew Rate	Package	8-SOIC (0.154", 3.90mm Width)
Number of Circuits 2 Output Type - Slew Rate 700 V/ μ s Gain Bandwidth Product 140MHz -3db Bandwidth 270MHz Current - Input Bias 5 μ A Voltage - Input Offset 1mV Current - Supply 6.5mA Current - Output / Channel 110mA Voltage - Supply, Single/Dual (\pm) 3 V ~ 12 V, \pm 1.5 V ~ 6 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount	Series	-
Output Type - Slew Rate 700 V/ μ s Gain Bandwidth Product 140MHz -3db Bandwidth 270MHz Current - Input Bias 5 μ A Voltage - Input Offset 1mV Current - Supply 6.5mA Current - Output / Channel 110mA Voltage - Supply, Single/Dual (\pm) 3 V ~ 12 V, \pm 1.5 V ~ 6 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount	Amplifier Type	Voltage Feedback
Slew Rate 700 V/ μ s Gain Bandwidth Product 140MHz -3db Bandwidth 270MHz Current - Input Bias 5 μ A Voltage - Input Offset 1mV Current - Supply 6.5mA Current - Output / Channel 110mA Voltage - Supply, Single/Dual (\pm) 3 V ~ 12 V, \pm 1.5 V ~ 6 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount	Number of Circuits	2
Gain Bandwidth Product 140MHz 270MHz Current - Input Bias 5 μ A Voltage - Input Offset 1mV Current - Supply 6.5mA Current - Output / Channel 110mA Voltage - Supply, Single/Dual (\pm) 3 V ~ 12 V, \pm 1.5 V ~ 6 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount	Output Type	-
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	Slew Rate	700 V/μs
Current - Input Bias $5\mu A$ Voltage - Input Offset $1mV$ Current - Supply $6.5mA$ Current - Output / Channel $110mA$ Voltage - Supply, Single/Dual (\pm) $3V \sim 12V, \pm 1.5V \sim 6V$ Operating Temperature $-40^{\circ}C \sim 85^{\circ}C$ Mounting Type Surface Mount	Gain Bandwidth Product	140MHz
Voltage - Input Offset $1mV$ Current - Supply $6.5mA$ Current - Output / Channel $110mA$ Voltage - Supply, Single/Dual (\pm) $3 V \sim 12 V, \pm 1.5 V \sim 6 V$ Operating Temperature $-40^{\circ}C \sim 85^{\circ}C$ Mounting Type Surface Mount	-3db Bandwidth	270MHz
Current - Supply $6.5 mA$ Current - Output / Channel $110 mA$ Voltage - Supply, Single/Dual (\pm) $3 \text{ V} \sim 12 \text{ V}, \pm 1.5 \text{ V} \sim 6 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface Mount	Current - Input Bias	5μΑ
Current - Output / Channel 110mA Voltage - Supply, Single/Dual (\pm) $3 \text{ V} \sim 12 \text{ V}, \pm 1.5 \text{ V} \sim 6 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface Mount	Voltage - Input Offset	1mV
Voltage - Supply, Single/Dual (\pm) 3 V ~ 12 V, \pm 1.5 V ~ 6 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount	Current - Supply	6.5mA
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting Type Surface Mount	Current - Output / Channel	110mA
Mounting Type Surface Mount	Voltage - Supply, Single/Dual (±)	3 V ~ 12 V, ±1.5 V ~ 6 V
	Operating Temperature	-40°C ~ 85°C
Package / Case 8-SOIC (0.154", 3.90mm Width)	Mounting Type	Surface Mount
	Package / Case	8-SOIC (0.154", 3.90mm Width)
Supplier Device Package 8-SOIC	Supplier Device Package	8-SOIC
Report error		Report errors?

LMH6658MAX Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LMH6658MAX Payment Methods





















LMH6658MAX Shipping Methods













If you have any question about LMH6658MAX, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com