



LMK325F226ZF-T Information



For Reference Only

Part Number LMK325F226ZF-T

Manufacturer Taiyo Yuden Category Capacitors

Ceramic Capacitors

Description CAP CER 22UF 10V Y5V 1210

Package 1210 (3225 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LMK325F226ZF-T Specifications

Manufacturer Part Number LMK325F226ZF-T Manufacturer Taiyo Yuden Category Capacitors Package 1210 (3225 Metric) Series M Capacitance 22μF Tolerance -20%, +80% Voltage - Rated 10V Temperature Coefficient Y5V (F) Operating Temperature -30°C ~ 85°C Features - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.049" (1.25mm)		
Category Capacitors Package 1210 (3225 Metric) Series M Capacitance 22µF Tolerance -20%, +80% Voltage - Rated 10V Temperature Coefficient Y5V (F) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.049" (1.25mm)	Manufacturer Part Number	LMK325F226ZF-T
Package 1210 (3225 Metric) Series M Capacitance 22μF Tolerance -20%, +80% Voltage - Rated 10V Temperature Coefficient Y5V (F) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.049" (1.25mm)	Manufacturer	Taiyo Yuden
Package 1210 (3225 Metric) Series M Capacitance 22μF Tolerance -20%, +80% Voltage - Rated 10V Temperature Coefficient Y5V (F) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.049" (1.25mm)	Category	Capacitors
Series M Capacitance 22μF Tolerance -20%, +80% Voltage - Rated 10V Temperature Coefficient Y5V (F) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.049" (1.25mm)		Ceramic Capacitors
Capacitance 22μF Tolerance -20%, +80% Voltage - Rated 10V Temperature Coefficient Y5V (F) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.049" (1.25mm)	Package	1210 (3225 Metric)
Tolerance -20%, +80% Voltage - Rated 10V Temperature Coefficient Y5V (F) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.049" (1.25mm)	Series	M
Voltage - Rated10VTemperature CoefficientY5V (F)Operating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.049" (1.25mm)	Capacitance	22μF
Temperature Coefficient Y5V (F) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.049" (1.25mm)	Tolerance	-20%, +80%
Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) Thickness (Max) 0.049" (1.25mm)	Voltage - Rated	10V
Features - General Purpose - Applications General Purpose - General Purpose - Mounting Type Surface Mount, MLCC - Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.049" (1.25mm)	Temperature Coefficient	Y5V (F)
Ratings - General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.049" (1.25mm)	Operating Temperature	-30°C ~ 85°C
Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.049" (1.25mm)	Features	-
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.049" (1.25mm)	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.049" (1.25mm)	Applications	General Purpose
Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.049" (1.25mm)	Failure Rate	-
Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.049" (1.25mm)	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) - 0.049" (1.25mm)	Package / Case	1210 (3225 Metric)
Thickness (Max) 0.049" (1.25mm)	Size / Dimension	0.126" L x 0.098" W (3.20mm x 2.50mm)
	Height - Seated (Max)	-
Lead Spacing -	Thickness (Max)	0.049" (1.25mm)
	Lead Spacing	-
Lead Style -	Lead Style	-
Report errors?		Report errors?

LMK325F226ZF-T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LMK325F226ZF-T Payment Methods



















LMK325F226ZF-T Shipping Methods













If you have any question about LMK325F226ZF-T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com