



LMP7717MAE Information



For Reference Only

Part Number LMP7717MAE

Manufacturer Texas Instruments

Category Integrated Circuits (ICs)

Linear - Amplifiers - Instrumentation, OP Amps,

Buffer Amps

Description IC OPAMP GP 88MHZ RRO 8SOIC **Package** 8-SOIC (0.154", 3.90mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LMP7717MAE Specifications

Manufacturer Part Number LMP7717MAE Manufacturer Texas Instruments Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-SOIC (0.154", 3.90mm Width) Series LMP?, PowerWise? Amplifier Type General Purpose Number of Circuits 1 Output Type Rail-to-Rail Slew Rate 35 V/μs Gain Bandwidth Product 88MHz -3db Bandwidth - Current - Input Bias 0.1pA Voltage - Input Offset 10μV Current - Supply 1.15mA Current - Output / Channel 60mA Voltage - Supply, Single/Dual (±) 1.8 V ~ 5.5 V, ±0.9 V ~ 2.75 V Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)		
Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-SOIC (0.154", 3.90mm Width) Series LMP?, PowerWise? Amplifier Type General Purpose Number of Circuits 1 Output Type Rail-to-Rail Slew Rate 35 V/μs Gain Bandwidth Product 88MHz -3db Bandwidth - Current - Input Bias 0.1pA Voltage - Input Offset 10μV Current - Supply 1.15mA Current - Output / Channel 60mA Voltage - Supply, Single/Dual (±) 1.8 V ~ 5.5 V, ±0.9 V ~ 2.75 V Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount	Manufacturer Part Number	LMP7717MAE
Linear - Amplifiers - Instrumentation, OP Amps, Buffer AmpsPackage8-SOIC (0.154", 3.90mm Width)SeriesLMP?, PowerWise?Amplifier TypeGeneral PurposeNumber of Circuits1Output TypeRail-to-RailSlew Rate35 V/μsGain Bandwidth Product88MHz-3db Bandwidth-Current - Input Bias0.1pAVoltage - Input Offset10μVCurrent - Supply1.15mACurrent - Output / Channel60mAVoltage - Supply, Single/Dual (±)1.8 V ~ 5.5 V, ±0.9 V ~ 2.75 VOperating Temperature-40°C ~ 125°CMounting TypeSurface Mount	Manufacturer	Texas Instruments
Package8-SOIC (0.154", 3.90mm Width)SeriesLMP?, PowerWise?Amplifier TypeGeneral PurposeNumber of Circuits1Output TypeRail-to-RailSlew Rate35 V/μsGain Bandwidth Product88MHz-3db Bandwidth-Current - Input Bias0.1pAVoltage - Input Offset10μVCurrent - Supply1.15mACurrent - Output / Channel60mAVoltage - Supply, Single/Dual (±)1.8 V ~ 5.5 V, ±0.9 V ~ 2.75 VOperating Temperature-40°C ~ 125°CMounting TypeSurface Mount	Category	Integrated Circuits (ICs)
Series LMP?, PowerWise? Amplifier Type General Purpose Number of Circuits 1 Output Type Rail-to-Rail Slew Rate 35 V/ μ s Gain Bandwidth Product 88MHz -3db Bandwidth -Current - Input Bias 0.1pA Voltage - Input Offset 10 μ V Current - Supply 1.15mA Current - Output / Channel 60mA Voltage - Supply, Single/Dual (\pm) 1.8 V \sim 5.5 V, \pm 0.9 V \sim 2.75 V Operating Temperature -40°C \sim 125°C Mounting Type Surface Mount		Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps
Amplifier TypeGeneral PurposeNumber of Circuits1Output TypeRail-to-RailSlew Rate $35 \text{ V/}\mu\text{s}$ Gain Bandwidth Product 88MHz -3db Bandwidth-Current - Input Bias 0.1pA Voltage - Input Offset $10\mu\text{V}$ Current - Supply 1.15mA Current - Output / Channel 60mA Voltage - Supply, Single/Dual (\pm) $1.8 \text{ V} \sim 5.5 \text{ V}, \pm 0.9 \text{ V} \sim 2.75 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Mounting TypeSurface Mount	Package	8-SOIC (0.154", 3.90mm Width)
Number of Circuits 1 Output Type Rail-to-Rail Slew Rate 35 V/ μ s Gain Bandwidth Product 88MHz -3db Bandwidth - Current - Input Bias 0.1pA Voltage - Input Offset 10 μ V Current - Supply 1.15mA Current - Output / Channel 60mA Voltage - Supply, Single/Dual (\pm) 1.8 V ~ 5.5 V, \pm 0.9 V ~ 2.75 V Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount	Series	LMP?, PowerWise?
Output Type Rail-to-Rail Slew Rate 35 V/ μ s Gain Bandwidth Product 88MHz -3db Bandwidth - Current - Input Bias 0.1pA Voltage - Input Offset 10 μ V Current - Supply 1.15mA Current - Output / Channel 60mA Voltage - Supply, Single/Dual (\pm) 1.8 V ~ 5.5 V, \pm 0.9 V ~ 2.75 V Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount	Amplifier Type	General Purpose
Slew Rate 35 V/ μ s Gain Bandwidth Product 88MHz -3db Bandwidth - Current - Input Bias 0.1pA Voltage - Input Offset 10 μ V Current - Supply 1.15mA Current - Output / Channel 60mA Voltage - Supply, Single/Dual (\pm) 1.8 V ~ 5.5 V, \pm 0.9 V ~ 2.75 V Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount	Number of Circuits	1
Gain Bandwidth Product 88MHz -3db Bandwidth - Current - Input Bias 0.1pA Voltage - Input Offset 10 μ V Current - Supply 1.15mA Current - Output / Channel 60mA Voltage - Supply, Single/Dual (\pm) 1.8 V \sim 5.5 V, \pm 0.9 V \sim 2.75 V Operating Temperature -40°C \sim 125°C Mounting Type Surface Mount	Output Type	Rail-to-Rail
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	Slew Rate	35 V/μs
Current - Input Bias $0.1pA$ Voltage - Input Offset $10\mu V$ Current - Supply $1.15mA$ Current - Output / Channel $60mA$ Voltage - Supply, Single/Dual (\pm) $1.8\ V \sim 5.5\ V, \pm 0.9\ V \sim 2.75\ V$ Operating Temperature $-40^{\circ}C \sim 125^{\circ}C$ Mounting Type Surface Mount	Gain Bandwidth Product	88MHz
$\begin{tabular}{lllllllllllllllllllllllllllllllllll$	-3db Bandwidth	-
Current - Supply $1.15 mA$ Current - Output / Channel $60 mA$ Voltage - Supply, Single/Dual (\pm) $1.8 \text{ V} \sim 5.5 \text{ V}, \pm 0.9 \text{ V} \sim 2.75 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Mounting TypeSurface Mount	Current - Input Bias	0.1pA
Current - Output / Channel $60mA$ Voltage - Supply, Single/Dual (±) $1.8 \text{ V} \sim 5.5 \text{ V}, \pm 0.9 \text{ V} \sim 2.75 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Mounting Type Surface Mount	Voltage - Input Offset	$10\mu V$
Voltage - Supply, Single/Dual (\pm) 1.8 V ~ 5.5 V, \pm 0.9 V ~ 2.75 V Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount	Current - Supply	1.15mA
Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount	Current - Output / Channel	60mA
Mounting Type Surface Mount	Voltage - Supply, Single/Dual (±)	1.8 V ~ 5.5 V, ±0.9 V ~ 2.75 V
0 71	Operating Temperature	-40°C ~ 125°C
Package / Case 8-SOIC (0.154", 3.90mm Width)	Mounting Type	Surface Mount
	Package / Case	8-SOIC (0.154", 3.90mm Width)
Supplier Device Package 8-SOIC	Supplier Device Package	8-SOIC
Report errors		Report errors?

LMP7717MAE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LMP7717MAE Payment Methods



















LMP7717MAE Shipping Methods













If you have any question about LMP7717MAE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com