



LMV793MF/NOPB Information



For Reference Only

Part Number LMV793MF/NOPB
Manufacturer Texas Instruments
Category Integrated Circuits (ICs)

Linear - Amplifiers - Instrumentation, OP Amps,

Buffer Amps

Description IC OPAMP GP 88MHZ RRO SOT23-5

Package SC-74A, SOT-753

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LMV793MF/NOPB Specifications

Manufacturer Part Number LMV793MF/NOPB Manufacturer Texas Instruments Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package SC-74A, SOT-753 Series - Amplifier Type General Purpose Number of Circuits 1 Output Type Rail-to-Rail Slew Rate 35 V/μs Gain Bandwidth Product 88MHz -3db Bandwidth - Current - Input Bias 0.1pA Voltage - Input Offset 100μV Current - Supply 1.15mA Current - Output / Channel 60mA Voltage - Supply, Single/Dual (±) 1.8 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount Package / Case SC-74A, SOT-753		
CategoryIntegrated Circuits (ICs)Linear - Amplifiers - Instrumentation, OP Amps, Buffer AmpsPackageSC-74A, SOT-753Series-Amplifier TypeGeneral PurposeNumber of Circuits1Output TypeRail-to-RailSlew Rate35 V/μsGain Bandwidth Product88MHz-3db Bandwidth-Current - Input Bias0.1pAVoltage - Input Offset100μVCurrent - Output / Channel60mAVoltage - Supply, Single/Dual (±)1.8 V ~ 5.5 VOperating Temperature-40°C ~ 125°CMounting TypeSurface MountPackage / CaseSC-74A, SOT-753	Manufacturer Part Number	LMV793MF/NOPB
Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package SC-74A, SOT-753 Series - Amplifier Type General Purpose Number of Circuits 1 Output Type Rail-to-Rail Slew Rate 35 V/μs Gain Bandwidth Product 88MHz -3db Bandwidth - Current - Input Bias 0.1pA Voltage - Input Offset 100μV Current - Supply 1.15mA Current - Output / Channel 60mA Voltage - Supply, Single/Dual (±) 1.8 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount Package / Case SC-74A, SOT-753	Manufacturer	Texas Instruments
PackageSC-74A, SOT-753Series-Amplifier TypeGeneral PurposeNumber of Circuits1Output TypeRail-to-RailSlew Rate35 V/μsGain Bandwidth Product88MHz-3db Bandwidth-Current - Input Bias0.1pAVoltage - Input Offset100μVCurrent - Supply1.15mACurrent - Output / Channel60mAVoltage - Supply, Single/Dual (±)1.8 V ~ 5.5 VOperating Temperature-40°C ~ 125°CMounting TypeSurface MountPackage / CaseSC-74A, SOT-753	Category	Integrated Circuits (ICs)
Series - Amplifier Type General Purpose Number of Circuits 1 Output Type Rail-to-Rail Slew Rate 35 V/μs Gain Bandwidth Product 88MHz -3db Bandwidth - Current - Input Bias 0.1pA Voltage - Input Offset 100μV Current - Supply 1.15mA Current - Output / Channel 60mA Voltage - Supply, Single/Dual (±) 1.8 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount Package / Case SC-74A, SOT-753		Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps
Amplifier Type General Purpose Number of Circuits 1 Output Type Rail-to-Rail Slew Rate 35 $V/\mu s$ Gain Bandwidth Product 88MHz -3db Bandwidth - Current - Input Bias 0.1pA Voltage - Input Offset 100 μV Current - Supply 1.15mA Current - Output / Channel 60mA Voltage - Supply, Single/Dual (\pm) 1.8 $V \sim 5.5 V$ Operating Temperature -40°C ~ 125 °C Mounting Type Surface Mount Package / Case SC-74A, SOT-753	Package	SC-74A, SOT-753
Number of Circuits 1 Output Type Rail-to-Rail Slew Rate 35 V/μs Gain Bandwidth Product 88MHz -3db Bandwidth - Current - Input Bias 0.1pA Voltage - Input Offset 100μV Current - Supply 1.15mA Current - Output / Channel 60mA Voltage - Supply, Single/Dual (±) 1.8 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount Package / Case SC-74A, SOT-753	Series	-
Output Type Rail-to-Rail Slew Rate 35 V/µs Gain Bandwidth Product 88MHz -3db Bandwidth - Current - Input Bias 0.1pA Voltage - Input Offset 100µV Current - Supply 1.15mA Current - Output / Channel 60mA Voltage - Supply, Single/Dual (±) 1.8 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount Package / Case SC-74A, SOT-753	Amplifier Type	General Purpose
Slew Rate 35 V/ μ s Gain Bandwidth Product 88MHz -3db Bandwidth - Current - Input Bias 0.1pA Voltage - Input Offset 100 μ V Current - Supply 1.15mA Current - Output / Channel 60mA Voltage - Supply, Single/Dual (\pm) 1.8 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount Package / Case SC-74A, SOT-753	Number of Circuits	1
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	Output Type	Rail-to-Rail
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	Slew Rate	35 V/μs
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	Gain Bandwidth Product	88MHz
Voltage - Input Offset	-3db Bandwidth	-
Current - Supply $1.15 mA$ Current - Output / Channel $60 mA$ Voltage - Supply, Single/Dual (\pm) $1.8 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Mounting TypeSurface MountPackage / CaseSC-74A, SOT-753	Current - Input Bias	0.1pA
Current - Output / Channel $60mA$ Voltage - Supply, Single/Dual (\pm) $1.8 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Mounting Type Surface Mount Package / Case SC-74A, SOT-753	Voltage - Input Offset	$100\mu V$
Voltage - Supply, Single/Dual (\pm) 1.8 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount Package / Case SC-74A, SOT-753	Current - Supply	1.15mA
Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount Package / Case SC-74A, SOT-753	Current - Output / Channel	60mA
Mounting Type Surface Mount Package / Case SC-74A, SOT-753	Voltage - Supply, Single/Dual (±)	1.8 V ~ 5.5 V
Package / Case SC-74A, SOT-753	Operating Temperature	-40°C ~ 125°C
-	Mounting Type	Surface Mount
G 11 D 1 D 1	Package / Case	SC-74A, SOT-753
Supplier Device Package SUT-23-5	Supplier Device Package	SOT-23-5
Report errors		Report errors?

LMV793MF/NOPB Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LMV793MF/NOPB Payment Methods



















LMV793MF/NOPB Shipping Methods













If you have any question about LMV793MF/NOPB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com