

LNC2H272MSEH

Request a Quote

LNC2H272MSEH Information

	Part Number	LNC2H272MSEH
www.heiser.com	Manufacturer	Nichicon
	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 2700UF 20% 500V SCREW
88	Package	Radial, Can - Screw Terminals
For Reference Only		For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



LNC2H272MSEH Specifications

Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Scries LNC Capacitance 2700µF Tolerance ±20% Voltage - Rated 500V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature 40°C ~ 85°C Polarization General Purpose Applications General Purpose Ripple Current - Low Frequency 15.8A @ 120Hz Impedance - Lead Spacing 3.000" Dia (76.20mm) Size / Dimension 3.661" (93.00mm) Size / Dimension 5.661" (93.00mm) Surface Mount Land Size - Mounting Type Chasis Mount Package / Case Radial, Can - Screw Terminals	•	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Scries LNC Capacitance 2700µF Tolerance ±20% Voltage - Rated 500V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature 40°C ~ 85°C Polarization General Purpose Applications General Purpose Ripple Current - Low Frequency 15.8A @ 120Hz Impedance - Lead Spacing 3.000" Dia (76.20mm) Size / Dimension 3.661" (93.00mm) Size / Dimension 5.661" (93.00mm) Surface Mount Land Size - Mounting Type Chasis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	LNC2H272MSEH
Auminum Electrolytic CapacitorsPackageRadial, Can - Screw TerminalsSeriesLNCCapacitance2700µFTolerance±20%Voltage - Rated500VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency15.8A @ 120HzRipple Current - High Frequency22.12A @ 10kHzImpedance-Lead Spacing3.000° Dia (76.20mm)Size / Dimension3.661" (93.00mm)Strace Mount Land Size-Mounting TypeChasis MountPackage / CaseRadial, Can - Screw Terminals	Manufacturer	Nichicon
PackageRadial, Can - Screw TerminalsSeriesLNCCapacitance2700µFTolerance20%Voltage - Rated500VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 85°COperating Temperature600° < 85°C	Category	Capacitors
SeriesLNCCapacitance2700μFTolerance±20%Voltage - Rated500VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency15.8A @ 120HzImpedance-Lead Spacing3.000° Dia (76.20mm)Size / Dimension3.000° Dia (76.20mm)Height - Seated (Max)3.661° (93.00mm)Surface Mount Land Size-Mounting TypeChasis MountPokage / CaseKadia, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance2700µFTolerance±20%Voltage - Rated500VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency15.8A @ 120HzImpedance-Lead Spacing3.000° Dia (76.20mm)Size / Dimension3.661° (93.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRatial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance±20%Voltage - Rated500VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency15.8A @ 120HzImpedance-Lead Spacing3.000" Dia (76.20mm)Size / Dimension3.661" (93.00mm)Height - Seated (Max)3.661" (93.00mm)Surface Mount Land Size-Pokage / CaseKadial, Can - Screw Terminals	Series	LNC
Voltage - Rated500VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency15.8A @ 120HzImpedance-Lead Spacing1.252" (31.80mm)Size / Dimension3.000" Dia (76.20mm)Height - Seated (Max)3.661" (93.00mm)Surface Mount Land Size-Pokage / CaseRatial, Can - Screw Terminals	Capacitance	2700µF
Loc-ESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency15.8A @ 120HzRipple Current - High Frequency22.12A @ 10kHzImpedance-Lead Spacing3.000" Dia (76.20mm)Size / Dimension3.661" (93.00mm)Height - Seated (Max)-Surface Mount Land Size-Pokage / CaseRadial, Can - Screw Terminals	Tolerance	±20%
Lifetime @ Temp.5000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency15.8A @ 120HzRipple Current - High Frequency22.12A @ 10kHzImpedance-Lead Spacing1.252" (31.80mm)Size / Dimension3.000" Dia (76.20mm)Height - Seated (Max)3.661" (93.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Voltage - Rated	500V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency15.8A @ 120HzBipple Current - High Frequency22.12A @ 10kHzImpedance-Lead Spacing1.252" (31.80mm)Size / Dimension3.000" Dia (76.20mm)Height - Seated (Max)3.661" (93.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency15.8A @ 120HzRipple Current - High Frequency22.12A @ 10kHzImpedance-Lead Spacing1.252" (31.80mm)Size / Dimension3.000" Dia (76.20mm)Height - Seated (Max)3.661" (93.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Lifetime @ Temp.	5000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency15.8A @ 120HzRipple Current - High Frequency22.12A @ 10kHzImpedance-Lead Spacing1.252" (31.80mm)Size / Dimension3.000" Dia (76.20mm)Height - Seated (Max)3.661" (93.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency15.8A @ 120HzRipple Current - High Frequency22.12A @ 10kHzImpedance-Lead Spacing1.252" (31.80mm)Size / Dimension3.000" Dia (76.20mm)Height - Seated (Max)3.661" (93.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Polarization	Polar
InInRipple Current - High Frequency22.12A @ 10kHzImpedance-Lead Spacing1.252" (31.80mm)Size / Dimension3.000" Dia (76.20mm)Height - Seated (Max)3.661" (93.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Applications	General Purpose
Impedance-Lead Spacing1.252" (31.80mm)Size / Dimension3.000" Dia (76.20mm)Height - Seated (Max)3.661" (93.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	15.8A @ 120Hz
Lead Spacing1.252" (31.80mm)Size / Dimension3.000" Dia (76.20mm)Height - Seated (Max)3.661" (93.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - High Frequency	22.12A @ 10kHz
Size / Dimension3.000" Dia (76.20mm)Height - Seated (Max)3.661" (93.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Impedance	-
Height - Seated (Max)3.661" (93.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Lead Spacing	1.252" (31.80mm)
Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Size / Dimension	3.000" Dia (76.20mm)
Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Height - Seated (Max)	3.661" (93.00mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
	Mounting Type	Chassis Mount
Report errors'	Package / Case	Radial, Can - Screw Terminals
		Report errors?

LNC2H272MSEH Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

LNC2H272MSEH Payment Methods





If you have any question about LNC2H272MSEH, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com