



# **LNE-36V150WAAA Information**

w.heisener.com

Part Number LNE-36V150WAAA Manufacturer Delta Electronics

Category Power Supplies - External/Internal (Off-Board)

**LED Drivers** 

**Description** LED DRIVER CC/CV AC/DC 36V 4.2A

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **LNE-36V150WAAA Specifications**

Category Power Supplies - External/Internal (Off-Board)  LED Drivers  Package - Series LNE-150W  Type Constant Current, Voltage Topology AC DC Converter  Number of Outputs 1  Voltage - Input (Min) 90VAC  Voltage - Input (Max) 305VAC  Voltage - Output 36V  Current - Output (Max) 4.2A  Power (Watts) 150W  Voltage - Isolation 3.85kV (3850V)  Dimming - Features OCP, OTP, OVP, SCP  Ratings IP65  Operating Temperature -40°C ~ 70°C			
Category         Power Supplies - External/Internal (Off-Board)           LED Drivers           Package         -           Series         LNE-150W           Type         Constant Current, Voltage           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         90VAC           Voltage - Input (Max)         305VAC           Voltage - Output         36V           Current - Output (Max)         4.2A           Power (Watts)         150W           Voltage - Isolation         3.85kV (3850V)           Dimming         -           Features         OCP, OTP, OVP, SCP           Ratings         IP65           Operating Temperature         -40°C ~ 70°C           Efficiency         93%           Termination Style         Wire Leads           Size / Dimension         8.03" L x 2.68" W x 1.53" H (204.0mm x 68.0mm x 38.8mm)	Manufacturer Part Number	LNE-36V150WAAA	
LED Drivers           Package         -           Series         LNE-150W           Type         Constant Current, Voltage           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         90VAC           Voltage - Input (Max)         305VAC           Voltage - Output         36V           Current - Output (Max)         4.2A           Power (Watts)         150W           Voltage - Isolation         3.85kV (3850V)           Dimming         -           Features         OCP, OTP, OVP, SCP           Ratings         IP65           Operating Temperature         -40°C ~ 70°C           Efficiency         93%           Termination Style         Wire Leads           Size / Dimension         8.03" L x 2.68" W x 1.53" H (204.0mm x 68.0mm x 38.8mm)	Manufacturer	Delta Electronics	
Package         -           Series         LNE-150W           Type         Constant Current, Voltage           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         90VAC           Voltage - Input (Max)         305VAC           Voltage - Output         36V           Current - Output (Max)         4.2A           Power (Watts)         150W           Voltage - Isolation         3.85kV (3850V)           Dimming         -           Features         OCP, OTP, OVP, SCP           Ratings         IP65           Operating Temperature         -40°C ~ 70°C           Efficiency         93%           Termination Style         Wire Leads           Size / Dimension         8.03" L x 2.68" W x 1.53" H (204.0mm x 68.0mm x 38.8mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series         LNE-150W           Type         Constant Current, Voltage           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         90VAC           Voltage - Input (Max)         305VAC           Voltage - Output         36V           Current - Output (Max)         4.2A           Power (Watts)         150W           Voltage - Isolation         3.85kV (3850V)           Dimming         -           Features         OCP, OTP, OVP, SCP           Ratings         IP65           Operating Temperature         -40°C ~ 70°C           Efficiency         93%           Termination Style         Wire Leads           Size / Dimension         8.03" L x 2.68" W x 1.53" H (204.0mm x 68.0mm x 38.8mm)		LED Drivers	
Type         Constant Current, Voltage           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         90VAC           Voltage - Input (Max)         305VAC           Voltage - Output         36V           Current - Output (Max)         4.2A           Power (Watts)         150W           Voltage - Isolation         3.85kV (3850V)           Dimming         -           Features         OCP, OTP, OVP, SCP           Ratings         IP65           Operating Temperature         -40°C ~ 70°C           Efficiency         93%           Termination Style         Wire Leads           Size / Dimension         8.03" L x 2.68" W x 1.53" H (204.0mm x 68.0mm x 38.8mm)	Package	-	
Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         90VAC           Voltage - Input (Max)         305VAC           Voltage - Output         36V           Current - Output (Max)         4.2A           Power (Watts)         150W           Voltage - Isolation         3.85kV (3850V)           Dimming         -           Features         OCP, OTP, OVP, SCP           Ratings         IP65           Operating Temperature         -40°C ~ 70°C           Efficiency         93%           Termination Style         Wire Leads           Size / Dimension         8.03" L x 2.68" W x 1.53" H (204.0mm x 68.0mm x 38.8mm)	Series	LNE-150W	
Number of Outputs       1         Voltage - Input (Min)       90VAC         Voltage - Input (Max)       305VAC         Voltage - Output       36V         Current - Output (Max)       4.2A         Power (Watts)       150W         Voltage - Isolation       3.85kV (3850V)         Dimming       -         Features       OCP, OTP, OVP, SCP         Ratings       IP65         Operating Temperature       -40°C ~ 70°C         Efficiency       93%         Termination Style       Wire Leads         Size / Dimension       8.03" L x 2.68" W x 1.53" H (204.0mm x 68.0mm x 38.8mm)	Туре	Constant Current, Voltage	
Voltage - Input (Min)       90VAC         Voltage - Input (Max)       305VAC         Voltage - Output       36V         Current - Output (Max)       4.2A         Power (Watts)       150W         Voltage - Isolation       3.85kV (3850V)         Dimming       -         Features       OCP, OTP, OVP, SCP         Ratings       IP65         Operating Temperature       -40°C ~ 70°C         Efficiency       93%         Termination Style       Wire Leads         Size / Dimension       8.03" L x 2.68" W x 1.53" H (204.0mm x 68.0mm x 38.8mm)	Topology	AC DC Converter	
Voltage - Input (Max)       305VAC         Voltage - Output       36V         Current - Output (Max)       4.2A         Power (Watts)       150W         Voltage - Isolation       3.85kV (3850V)         Dimming       -         Features       OCP, OTP, OVP, SCP         Ratings       IP65         Operating Temperature       -40°C ~ 70°C         Efficiency       93%         Termination Style       Wire Leads         Size / Dimension       8.03" L x 2.68" W x 1.53" H (204.0mm x 68.0mm x 38.8mm)	Number of Outputs	1	
Voltage - Output       36V         Current - Output (Max)       4.2A         Power (Watts)       150W         Voltage - Isolation       3.85kV (3850V)         Dimming       -         Features       OCP, OTP, OVP, SCP         Ratings       IP65         Operating Temperature       -40°C ~ 70°C         Efficiency       93%         Termination Style       Wire Leads         Size / Dimension       8.03" L x 2.68" W x 1.53" H (204.0mm x 68.0mm x 38.8mm)	Voltage - Input (Min)	90VAC	
Current - Output (Max)       4.2A         Power (Watts)       150W         Voltage - Isolation       3.85kV (3850V)         Dimming       -         Features       OCP, OTP, OVP, SCP         Ratings       IP65         Operating Temperature       -40°C ~ 70°C         Efficiency       93%         Termination Style       Wire Leads         Size / Dimension       8.03" L x 2.68" W x 1.53" H (204.0mm x 68.0mm x 38.8mm)	Voltage - Input (Max)	305VAC	
Power (Watts)       150W         Voltage - Isolation       3.85kV (3850V)         Dimming       -         Features       OCP, OTP, OVP, SCP         Ratings       IP65         Operating Temperature       -40°C ~ 70°C         Efficiency       93%         Termination Style       Wire Leads         Size / Dimension       8.03" L x 2.68" W x 1.53" H (204.0mm x 68.0mm x 38.8mm)	Voltage - Output	36V	
Voltage - Isolation  3.85kV (3850V)  Dimming  - Features  OCP, OTP, OVP, SCP  Ratings  IP65  Operating Temperature  -40°C ~ 70°C  Efficiency  93%  Termination Style  Size / Dimension  3.85kV (3850V)  Wire Leads  Size / Dimension  3.85kV (3850V)  Wire Leads  Size / Output	Current - Output (Max)	4.2A	
Dimming Features OCP, OTP, OVP, SCP Ratings IP65 Operating Temperature -40°C ~ 70°C Efficiency 93% Termination Style Size / Dimension	Power (Watts)	150W	
Features OCP, OTP, OVP, SCP  Ratings IP65 Operating Temperature -40°C ~ 70°C  Efficiency 93% Termination Style Wire Leads Size / Dimension 8.03" L x 2.68" W x 1.53" H (204.0mm x 68.0mm x 38.8mm)	Voltage - Isolation	3.85kV (3850V)	
Ratings IP65 Operating Temperature -40°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 8.03" L x 2.68" W x 1.53" H (204.0mm x 68.0mm x 38.8mm)	Dimming	-	
Operating Temperature -40°C ~ 70°C  Efficiency 93%  Termination Style Wire Leads Size / Dimension 8.03" L x 2.68" W x 1.53" H (204.0mm x 68.0mm x 38.8mm)	Features	OCP, OTP, OVP, SCP	
Efficiency 93%  Termination Style Wire Leads  Size / Dimension 8.03" L x 2.68" W x 1.53" H (204.0mm x 68.0mm x 38.8mm)	Ratings	IP65	
Termination Style Wire Leads Size / Dimension 8.03" L x 2.68" W x 1.53" H (204.0mm x 68.0mm x 38.8mm)	Operating Temperature	-40°C ~ 70°C	
Size / Dimension 8.03" L x 2.68" W x 1.53" H (204.0mm x 68.0mm x 38.8mm)	Efficiency	93%	
· · · · · · · · · · · · · · · · · · ·	Termination Style	Wire Leads	
Report errors?	Size / Dimension	8.03" L x 2.68" W x 1.53" H (204.0mm x 68.0mm x 38.8mm)	
			Report errors?

#### **LNE-36V150WAAA Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **LNE-36V150WAAA Payment Methods**



















# **LNE-36V150WAAA Shipping Methods**













If you have any question about LNE-36V150WAAA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com